





ROOF FANS


| MODELS | UNIT | PFF4000 | PFF5500 | PFF6000 |
|------------------------|-------------------|---------------------------------------|---------------------------------------|---------------------------------------|
| AIR FLOW RATE | m ³ /h | 400 | 560 | 970 |
| POWER SUPPLY | V/Hz | 230V 50-60Hz | 230V 50-60Hz | 230V 50-60Hz |
| DIMENSIONS | mm | 364x364x107 | 364x364x107 | 364x364x107 |
| POWER CONSUMPTION | W | 25/32 | 58/75 | 85/90 |
| CURRENT CONSUMPTION | A | 0.11/0,15 | 0.26/0.34 | 0.38/0.44 |
| OVERCURRENT PROTECTION | - | THERMAL | THERMAL | THERMAL |
| ELECTRICAL CONNECTION | - | 3-POLE TERMINAL 2.5mm ² | 4-POLE TERMINAL 2.5mm ² | 4-POLE TERMINAL 2.5mm ² |
| OPERATING TEMPERATURE | °C | -10/+70 | -10/+70 | -10/+70 |
| PROTECTION DEGREE | - | IP54 | IP54 | IP54 |
| NOISE LEVEL | dB(A) | 57(61) | 62 (64) | 72 (73) |
| FLOW DIRECTION | - | INSIDE / OUT | INSIDE / OUT | INSIDE / OUT |
| BEARING | - | BALL | BALL | BALL |
| SERVICE LIFE | Hour | 50.000 | 50.000 | 50.000 |
| PLASTIC MATERIAL | - | UL94 V0 ABS FLAME RETARDANT | UL94 V0 ABS FLAME RETARDANT | UL94 V0 ABS FLAME RETARDANT |
| GASKET | - | POLYURETHANE SEALING | POLYURETHANE SEALING | POLYURETHANE SEALING |
| WEIGHT | kg | 2.68 | 3.16 | 3.74 |
| MOUNTING | - | 8 PCS M4 SCREWS | 8 PCS M4 SCREWS | 8 PCS M4 SCREWS |
| CONFORMITY | - | CE | CE | CE |





ROOF FANS

| MODELS | UNIT | PFF4000G | PFF5000G | PFF6000G |
|------------------------|-------------------|---------------------------------------|---------------------------------------|---------------------------------------|
| AIR FLOW RATE | m ³ /h | 400 | 560 | 970 |
| POWER SUPPLY | V/Hz | 230V 50-60Hz | 230V 50-60Hz | 230V 50-60Hz |
| DIMENSIONS | mm | 364x364x107 | 364x364x107 | 364x364x107 |
| POWER CONSUMPTION | W | 25/32 | 58/75 | 85/90 |
| CURRENT CONSUMPTION | A | 0.11/0.15 | 0.26/0.34 | 0.38/0.44 |
| OVERCURRENT PROTECTION | - | THERMAL | THERMAL | THERMAL |
| ELECTRICAL CONNECTION | - | 3-POLE TERMINAL 2.5mm ² | 4-POLE TERMINAL 2.5mm ² | 4-POLE TERMINAL 2.5mm ² |
| OPERATING TEMPERATURE | °C | -10/+70 | -10/+70 | -10/+70 |
| PROTECTION DEGREE | - | IP54 | IP54 | IP54 |
| NOISE LEVEL | dB(A) | 57(61) | 62 (64) | 72 (73) |
| FLOW DIRECTION | - | INSIDE / OUT | INSIDE / OUT | INSIDE / OUT |
| BEARING | - | BALL | BALL | BALL |
| SERVICE LIFE | Hour | 50.000 | 50.000 | 50.000 |
| PLASTIC MATERIAL | - | UL94 V0 ABS FLAME RETARDANT | UL94 V0 ABS FLAME RETARDANT | UL94 V0 ABS FLAME RETARDANT |
| GASKET | - | POLYURETHANE SEALING | POLYURETHANE SEALING | POLYURETHANE SEALING |
| WEIGHT | kg | 2.68 | 3.16 | 3.74 |
| MOUNTING | - | FAST CLIP ON | FAST CLIP ON | FAST CLIP ON |
| CONFORMITY | - | CE | CE | CE |





ROOF FANS

| MODELS | UNIT | PTS4000 | PTS5500 | PTS6000 |
|------------------------|-------------------|---------------------------------------|---------------------------------------|---------------------------------------|
| AIR FLOW RATE | m ³ /h | 400 | 560 | 970 |
| POWER SUPPLY | V/Hz | 230V 50-60Hz | 230V 50-60Hz | 230V 50-60Hz |
| DIMENSIONS | mm | 364x364x107 | 364x364x107 | 364x364x107 |
| POWER CONSUMPTION | W | 25/32 | 58/75 | 85/90 |
| CURRENT CONSUMPTION | A | 0.11/0.15 | 0.26/0.34 | 0.38/0.44 |
| OVERCURRENT PROTECTION | - | THERMAL | THERMAL | THERMAL |
| ELECTRICAL CONNECTION | - | 3-POLE TERMINAL 2.5mm ² | 3-POLE TERMINAL 2.5mm ² | 3-POLE TERMINAL 2.5mm ² |
| OPERATING TEMPERATURE | °C | -10/+70 | -10/+70 | -10/+70 |
| PROTECTION DEGREE | - | IP54 | IP54 | IP54 |
| NOISE LEVEL | dB(A) | 62 (64) | 62 (64) | 72 (73) |
| FLOW DIRECTION | - | INSIDE / OUT | INSIDE / OUT | INSIDE / OUT |
| BEARING | - | BALL | BALL | BALL |
| SERVICE LIFE | Hour | 50.000 | 50.000 | 50.000 |
| PLASTIC MATERIAL | - | UL94 V0 ABS FLAME RETARDANT | UL94 V0 ABS FLAME RETARDANT | UL94 V0 ABS FLAME RETARDANT |
| GASKET | - | POLYURETHANE SEALING | POLYURETHANE SEALING | POLYURETHANE SEALING |
| WEIGHT | kg | 2.60 | 3.16 | 3.74 |
| MOUNTING | - | FAST CLIP ON | FAST CLIP ON | FAST CLIP ON |
| CONFORMITY | - | CE | CE | CE |

