

# 3668 SIP Ceiling Speaker

## Audio Parameters

- Output:
  - 10W PoE
  - 10W 12V/2A
  - 20W 18V/2A
  - 30W 24V/2A
- Impedance: 4  $\Omega$
- Frequency range: 160Hz~18kHz
- Signal-to-noise ratio:  $\geq 90$ dB
- Audio codes:
  - Narrowband coding: G.711a/u, G.723.1, G.726-32K, G.729AB
  - Wideband coding: G.722, OPUS
  - MP3, WAV



## SIP

- SIP 2.0 (RFC3261)
- 2 SIP lines

## Network

- IPv4
- LAN connection: RJ45 10BASE-T/100BASE-TX PoE
- Protocol: HTTP, TCP/IP, SSL, DNS, SNTP, NTP, RTSP, TCP, UDP, DHCP

## Mechanical properties

- Dimensions (h/w/d):  $\Phi 194 \times 157$ mm
- Weight: 0.75kg
- Color: White
- Grille: Surface-treated metal mesh plate
- Speaker shell: ABS + antioxidation of organic material
- Mounting method: Ceiling mounted
- Installation dimensions:  $\Phi 172$ mm

## Power supply

- External power supply 12V/18V/24V DC / 2A
- PoE IEEE 802.3af

## Configuration and Management

- Via FTP/TFTP DHCP OPT66 / SIP/HTTP/HTTPS/PNP/TR069 automatically
- web management interface
- Web Packet capture (Web -based Packet - dump)
- Configuration export/import
- Software upgrade
- System logs (Syslog)