

Safety data sheet

Page: 1/17

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 31.01.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 31.01.2023

Product: **Glystantin® G30K RM/50 pk IN also suitable for electric vehicles**

(ID no. 30775215/SDS_GEN_DE/EN)

Date of print 13.06.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Glystantin® G30K RM/50 pk IN also suitable for electric vehicles

UFI: UE8F-90GQ-Q00A-GY5E

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Ready-to-use engine coolants

1.3. Details of the supplier of the safety data sheet

Company:

BASF SE

67056 Ludwigshafen

GERMANY

Fuel and Lubricant Solutions

Telephone: +49 621 60-42178

E-mail address: RegXcellenceFuelLubes@basf.com

1.4. Emergency telephone number

International emergency number:

Telephone: +49 180 2273-112

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 31.01.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 31.01.2023

Product: **Glyasantin® G30K RM/50 pk IN also suitable for electric vehicles**

(ID no. 30775215/SDS_GEN_DE/EN)

Date of print 13.06.2023

SECTION 2: Hazards Identification

2.1. Classification of the substance or mixture

For the classification of the mixture the following methods have been applied: extrapolation on the concentration levels of the hazardous substances, on basis of test results and after evaluation of experts. The methodologies used are mentioned at the respective test results.

According to Regulation (EC) No 1272/2008 [CLP]

Acute Tox. 4 (oral)

H302 Harmful if swallowed.

STOT RE 2

H373 May cause damage to organs (Kidney) through prolonged or repeated exposure.

For the classifications not written out in full in this section the full text can be found in section 16.

2.2. Label elements

According to Regulation (EC) No 1272/2008 [CLP]

Pictogram:



Signal Word:

Warning

Hazard Statement:

H302

Harmful if swallowed.

H373

May cause damage to organs (Kidney) through prolonged or repeated exposure.

Precautionary Statements (Prevention):

P260

Do not breathe dust/gas/mist/vapours.

P270

Do not eat, drink or smoke when using this product.

Precautionary Statements (Response):

P314

Get medical advice/attention if you feel unwell.

P301 + P312

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

P330

Rinse mouth

Precautionary Statements (Disposal):

P501

Dispose of contents and container to hazardous or special waste collection point.

Hazard determining component(s) for labelling: ethanediol

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 31.01.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 31.01.2023

Product: **Glyasantin® G30K RM/50 pk IN also suitable for electric vehicles**

(ID no. 30775215/SDS_GEN_DE/EN)

Date of print 13.06.2023

2.3. Other hazards

According to Regulation (EC) No 1272/2008 [CLP]

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture. The product does not contain a substance fulfilling the PBT (persistent/bioaccumulative/toxic) criteria or the vPvB (very persistent/very bioaccumulative) criteria.

Product does not contain a substance above legal limits included in the list established in accordance with Article 59(1) of Regulation (EC) No 1907/2006 for having endocrine disrupting properties or is identified to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

SECTION 3: Composition/Information on Ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Chemical nature

ethanediol
inhibitors

Regulatory relevant ingredients

ethanediol

Content (W/W): $\geq 25\%$ - $< 50\%$	Acute Tox. 4 (oral)
CAS Number: 107-21-1	STOT RE (Kidney) 2
EC-Number: 203-473-3	H302, H373
REACH registration number: 01-2119456816-28	
INDEX-Number: 603-027-00-1	

Substance with EU occupational exposure limit

Disodium sebacate

Content (W/W): $\geq 1\%$ - $< 3\%$	Eye Dam./Irrit. 2
CAS Number: 17265-14-4	H319
EC-Number: 241-300-3	
REACH registration number: 01-2120762063-61	

sodium hydroxide

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 31.01.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 31.01.2023

Product: **Glyasantin® G30K RM/50 pk IN also suitable for electric vehicles**

(ID no. 30775215/SDS_GEN_DE/EN)

Date of print 13.06.2023

Content (W/W): $\geq 0,1\%$ - $< 0,2\%$	Met. Corr. 1
CAS Number: 1310-73-2	Skin Corr./Irrit. 1A
EC-Number: 215-185-5	Eye Dam./Irrit. 1
REACH registration number: 01-2119457892-27	H290, H314
INDEX-Number: 011-002-00-6	<u>Specific concentration limit:</u>
	Skin Corr./Irrit. 1A: $\geq 5\%$
	Skin Corr./Irrit. 1B: $2 - < 5\%$
	Skin Corr./Irrit. 2: $0,5 - < 2\%$
	Eye Dam./Irrit. 2: $0,5 - < 2\%$

For the classifications not written out in full in this section, including the hazard classes and the hazard statements, the full text is listed in section 16.

SECTION 4: First-Aid Measures

4.1. Description of first aid measures

Immediately remove contaminated clothing. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). First aid personnel should pay attention to their own safety.

If inhaled:

Keep patient calm, remove to fresh air, seek medical attention.

On skin contact:

Immediately wash thoroughly with soap and water, seek medical attention.

On contact with eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open.

On ingestion:

Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention. Administer 50 ml of pure ethanol in a drinkable concentration.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11., (Further) symptoms and / or effects are not known so far

4.3. Indication of any immediate medical attention and special treatment needed

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 31.01.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 31.01.2023

Product: **Glyasantin® G30K RM/50 pk IN also suitable for electric vehicles**

(ID no. 30775215/SDS_GEN_DE/EN)

Date of print 13.06.2023

SECTION 5: Fire-Fighting Measures

5.1. Extinguishing media

Suitable extinguishing media:
water spray, dry powder, foam

5.2. Special hazards arising from the substance or mixture

Endangering substances: harmful vapours

Advice: Evolution of fumes/fog. The substances/groups of substances mentioned can be released in case of fire.

5.3. Advice for fire-fighters

Special protective equipment:
Wear a self-contained breathing apparatus.

Further information:

The degree of risk is governed by the burning substance and the fire conditions. Contaminated extinguishing water must be disposed of in accordance with official regulations.

SECTION 6: Accidental Release Measures

High risk of slipping due to leakage/spillage of product.

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective clothing. Breathing protection required.

6.2. Environmental precautions

Contain contaminated water/firefighting water. Do not discharge into drains/surface waters/groundwater.

6.3. Methods and material for containment and cleaning up

For large amounts: Pump off product.

For residues: Pick up with suitable absorbent material. Dispose of absorbed material in accordance with regulations.

6.4. Reference to other sections

Information regarding exposure controls/personal protection and disposal considerations can be found in section 8 and 13.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 31.01.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 31.01.2023

Product: **Glystantin® G30K RM/50 pk IN also suitable for electric vehicles**

(ID no. 30775215/SDS_GEN_DE/EN)

Date of print 13.06.2023

SECTION 7: Handling and Storage

7.1. Precautions for safe handling

Ensure thorough ventilation of stores and work areas. Shut containers immediately after taking product because product takes up the humidity of air.

Wear chemically resistant gloves in combination with specific activity training. Wear suitable coveralls to prevent exposure to the skin.

Protection against fire and explosion:

Take precautionary measures against static discharges.

Exposure estimate and reference to its source

Provide extract ventilation to points where emissions occur (LEV).

7.2. Conditions for safe storage, including any incompatibilities

The product in undamaged packing need not be stored separately.

Further information on storage conditions: Containers should be stored tightly sealed in a dry place.

Storage in galvanized containers is not recommended.

Storage class according to TRGS 510 (originally VCI, Germany): (10) Combustible liquids

7.3. Specific end use(s)

For the relevant identified use(s) listed in Section 1 the advice mentioned in this section 7 is to be observed.

SECTION 8: Exposure Controls/Personal Protection

8.1. Control parameters

Components with occupational exposure limits

The surveillance of the workplace by exposure measurements may be necessary, in order to prove the efficiency of safety measures, for example ventilation or the need of respiratory protection. Since this requires a specific competency, only accredited laboratories should be contracted. Regarding suitable methods to assess inhalation exposure, the European Standards EN 482, 689 and 14042 are to be considered. In addition, the TRGS 402 has to be observed in Germany.

107-21-1: ethanediol

Skin Designation (OEL (EU))

The substance can be absorbed through the skin.

STEL value 104 mg/m³ ; 40 ppm (OEL (EU))

indicative

TWA value 52 mg/m³ ; 20 ppm (OEL (EU))

indicative

Skin Designation (TRGS 900 (DE)), Vapor and aerosol

The substance can be absorbed through the skin.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 31.01.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 31.01.2023

Product: **Glyasantin® G30K RM/50 pk IN also suitable for electric vehicles**

(ID no. 30775215/SDS_GEN_DE/EN)

Date of print 13.06.2023

OEL 26 mg/m³ ; 10 ppm (TRGS 900 (DE)), Vapor and aerosol

Ceiling limit value/factor: 2

If the occupational exposure limit value (AGW) and the biological limit value (BGW) are complied with, there should be no risk of damage for the unborn child (see TRGS 900, Number 2.7)

Short Term Exposure Classification: (TRGS 900 (DE)), Vapor and aerosol

Category I: Substances for which the localized effect has an assigned exposure limit or for substances with a sensitizing effect in respiratory passages

PNEC

No hazard identified.

DNEL

Data refer to the lead substance

Components with DNEL

107-21-1: ethanediol

worker: Long-term exposure - local effects, Inhalation: 35 mg/m³

worker: Long-term exposure- systemic effects, dermal: 106 mg/kg

consumer: Long-term exposure - local effects, Inhalation: 7 mg/m³

consumer: Long-term exposure- systemic effects, dermal: 53 mg/kg

8.2. Exposure controls

Personal protective equipment

Respiratory protection:

Respiratory protection in case of vapour/aerosol release. Combination filter for gases/vapours of organic compounds and solid and liquid particles (f.e. EN 14387 Type A-P2)

Hand protection:

Chemical resistant protective gloves (EN ISO 374-1)

Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1):

e.g. nitrile rubber (0.4 mm), chloroprene rubber (0.5 mm), polyvinylchloride (0.7 mm) and other

Supplementary note: The specifications are based on tests, literature data and information of glove manufacturers or are derived from similar substances by analogy. Due to many conditions (e.g. temperature) it must be considered, that the practical usage of a chemical-protective glove in practice may be much shorter than the permeation time determined through testing.

Manufacturer's directions for use should be observed because of great diversity of types.

Eye protection:

Safety glasses with side-shields (frame goggles) (e.g. EN 166)

Body protection:

chemical-protection suit (f.e. according to EN 14605)

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 31.01.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 31.01.2023

Product: **Glyasantin® G30K RM/50 pk IN also suitable for electric vehicles**

(ID no. 30775215/SDS_GEN_DE/EN)

Date of print 13.06.2023

General safety and hygiene measures

Wearing of closed work clothing is required additionally to the stated personal protection equipment. No eating, drinking, smoking or tobacco use at the place of work. Handle in accordance with good industrial hygiene and safety practice.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

State of matter:	liquid	
Form:	liquid	
Colour:	pink	
Odour:	of glycol	
Odour threshold:	not determined	
solidification temperature:	< -35 °C	
boiling temperature:	108 °C (1.013 hPa)	(ASTM D1120)
Flammability:	not flammable	
Lower explosion limit:	For liquids not relevant for classification and labelling., The lower explosion point may be 5 - 15 °C below the flash point.	
Upper explosion limit:	For liquids not relevant for classification and labelling.	
Flash point:	Aqueous preparation, Not determinable.	(Unspecified)
Auto-ignition temperature:	not applicable, Based on the water content the product does not ignite.	(DIN 51794)
Thermal decomposition:	No decomposition if used as directed.	
pH value:	8	(ASTM D1287)
Viscosity, kinematic:	approx. 4 mm ² /s (23 °C)	(DIN 51562)
Thixotropy:	not thixotropic	
Solubility in water:	miscible	
Solubility (qualitative) solvent(s):	organic solvents soluble	
Partitioning coefficient n-octanol/water (log Kow):	not applicable for mixtures	
Vapour pressure:	approx. 17 mbar (20 °C)	
Density:	1,073 g/cm ³ (20 °C)	(DIN 51757)

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 31.01.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 31.01.2023

Product: **Glyasantin® G30K RM/50 pk IN also suitable for electric vehicles**

(ID no. 30775215/SDS_GEN_DE/EN)

Date of print 13.06.2023

Relative vapour density (air):
not determined, contains water

Particle characteristics

Particle size distribution: The substance / product is marketed or used in a non solid or granular form. -

9.2. Other information

Information with regard to physical hazard classes

Explosives

Explosion hazard: not explosive

Oxidizing properties

Fire promoting properties: not fire-propagating

Self-heating substances and mixtures

Self heating ability: It is not a substance capable of spontaneous heating.

Corrosion to metals

No corrosive effect on metal.

Other safety characteristics

Miscibility with water: miscible in all proportions
Hygroscopy: Non-hygroscopic
Evaporation rate: not determined

SECTION 10: Stability and Reactivity

10.1. Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Corrosion to metals: No corrosive effect on metal.

10.2. Chemical stability

The product is stable if stored and handled as prescribed/indicated.

10.3. Possibility of hazardous reactions

No hazardous reactions when stored and handled according to instructions.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 31.01.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 31.01.2023

Product: **Glyasantin® G30K RM/50 pk IN also suitable for electric vehicles**

(ID no. 30775215/SDS_GEN_DE/EN)

Date of print 13.06.2023

10.4. Conditions to avoid

Avoid open flames.

10.5. Incompatible materials

Substances to avoid:

strong oxidizing agents, alkali metal hydroxides

10.6. Hazardous decomposition products

Hazardous decomposition products:

No hazardous decomposition products known.

SECTION 11: Toxicological Information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Assessment of acute toxicity:

Of moderate toxicity after single ingestion. Of low toxicity after short-term skin contact.

Experimental/calculated data:

LD (human) (oral): approx. 1.600 mg/kg

Irritation

Assessment of irritating effects:

Not irritating to eyes and skin.

Respiratory/Skin sensitization

Assessment of sensitization:

Skin sensitizing effects were not observed in animal studies. Human data do not fully exclude a skin sensitizing potential.

Germ cell mutagenicity

Assessment of mutagenicity:

Based on available data, the classification criteria are not met.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 31.01.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 31.01.2023

Product: **Glyasantin® G30K RM/50 pk IN also suitable for electric vehicles**

(ID no. 30775215/SDS_GEN_DE/EN)

Date of print 13.06.2023

Carcinogenicity

Assessment of carcinogenicity:

The whole of the information assessable provides no indication of a carcinogenic effect.

Reproductive toxicity

Assessment of reproduction toxicity:

Based on the ingredients, there is no suspicion of a toxic effect on reproduction.

Developmental toxicity

Assessment of teratogenicity:

Based on available data, the classification criteria are not met.

Information on: ethanediol

Assessment of teratogenicity:

Developmental toxicity was observed after oral ingestion of high doses in studies with rats and mice, but this effect was not seen in a study with rabbits. Mechanistic studies show that the rabbit is the relevant species for the classification for human health. As such, and since ethylene glycol is not a developmental toxicant in the rabbit, no classification is warranted.

Specific target organ toxicity (single exposure)

Remarks: Based on available data, the classification criteria are not met.

Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:

Repeated exposure may affect certain organs.

Information on: ethanediol

Assessment of repeated dose toxicity:

The substance may cause damage to the kidney after repeated ingestion. The substance may cause damage to the kidney after repeated skin contact with high doses.

Aspiration hazard

No aspiration hazard expected.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 31.01.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 31.01.2023

Product: **Glyasantin® G30K RM/50 pk IN also suitable for electric vehicles**

(ID no. 30775215/SDS_GEN_DE/EN)

Date of print 13.06.2023

Interactive effects

No data available.

11.2. Information on other hazards

Endocrine disrupting properties

Product does not contain a substance above legal limits included in the list established in accordance with Article 59(1) of Regulation (EC) No 1907/2006 for having endocrine disrupting properties or is identified to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

Other information

Other relevant toxicity information

The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.

SECTION 12: Ecological Information

12.1. Toxicity

Assessment of aquatic toxicity:

There is a high probability that the product is not acutely harmful to aquatic organisms.

Microorganisms/Effect on activated sludge:

Inhibition of degradation activity in activated sludge is not to be anticipated during correct introduction of low concentrations.

12.2. Persistence and degradability

Elimination information:

> 70 % DOC reduction (28 d) (OECD 301 A (new version)) Readily biodegradable.

12.3. Bioaccumulative potential

Assessment bioaccumulation potential:

Accumulation in organisms is not to be expected.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 31.01.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 31.01.2023

Product: **Glyasantin® G30K RM/50 pk IN also suitable for electric vehicles**

(ID no. 30775215/SDS_GEN_DE/EN)

Date of print 13.06.2023

12.4. Mobility in soil

Assessment transport between environmental compartments:
Adsorption in soil: No data available.

12.5. Results of PBT and vPvB assessment

According to Annex XIII of Regulation (EC) No.1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH): The product does not contain a substance fulfilling the PBT (persistent/bioaccumulative/toxic) criteria or the vPvB (very persistent/very bioaccumulative) criteria.

12.6. Endocrine disrupting properties

Product does not contain a substance above legal limits included in the list established in accordance with Article 59(1) of Regulation (EC) No 1907/2006 for having endocrine disrupting properties or is identified to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

12.7. Other adverse effects

The product does not contain substances that are listed in Regulation (EC) 1005/2009 on substances that deplete the ozone layer.

12.8. Additional information

Adsorbable organically-bound halogen (AOX):
This product contains no organically-bound halogen.

Other ecotoxicological advice:
The product has not been tested. The statement has been derived from the properties of the individual components.

Do not release untreated into natural waters.

SECTION 13: Disposal Considerations

13.1. Waste treatment methods

Must be disposed of or incinerated in accordance with local regulations.

Waste key:
16 01 14⁰¹ antifreeze fluids containing hazardous substances

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 31.01.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 31.01.2023

Product: **Glyasantin® G30K RM/50 pk IN also suitable for electric vehicles**

(ID no. 30775215/SDS_GEN_DE/EN)

Date of print 13.06.2023

Contaminated packaging:

Uncontaminated packaging can be re-used.

Packs that cannot be cleaned should be disposed of in the same manner as the contents.

SECTION 14: Transport Information

Land transport

ADR

Not classified as a dangerous good under transport regulations

UN number or ID number: Not applicable

UN proper shipping name: Not applicable

Transport hazard class(es): Not applicable

Packing group: Not applicable

Environmental hazards: Not applicable

Special precautions for user: None known

RID

Not classified as a dangerous good under transport regulations

UN number or ID number: Not applicable

UN proper shipping name: Not applicable

Transport hazard class(es): Not applicable

Packing group: Not applicable

Environmental hazards: Not applicable

Special precautions for user: None known

Inland waterway transport

ADN

Not classified as a dangerous good under transport regulations

UN number or ID number: Not applicable

UN proper shipping name: Not applicable

Transport hazard class(es): Not applicable

Packing group: Not applicable

Environmental hazards: Not applicable

Special precautions for user: None known

Transport in inland waterway vessel

Not evaluated

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 31.01.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 31.01.2023

Product: **Glyasantin® G30K RM/50 pk IN also suitable for electric vehicles**

(ID no. 30775215/SDS_GEN_DE/EN)

Date of print 13.06.2023

Sea transport

IMDG

	Not classified as a dangerous good under transport regulations
UN number or ID number:	Not applicable
UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for user	None known

Air transport

IATA/ICAO

	Not classified as a dangerous good under transport regulations
UN number or ID number:	Not applicable
UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for user	None known

14.1. UN number or ID number

See corresponding entries for "UN number or ID number" for the respective regulations in the tables above.

14.2. UN proper shipping name

See corresponding entries for "UN proper shipping name" for the respective regulations in the tables above.

14.3. Transport hazard class(es)

See corresponding entries for "Transport hazard class(es)" for the respective regulations in the tables above.

14.4. Packing group

See corresponding entries for "Packing group" for the respective regulations in the tables above.

14.5. Environmental hazards

See corresponding entries for "Environmental hazards" for the respective regulations in the tables above.

14.6. Special precautions for user

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 31.01.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 31.01.2023

Product: **Glyasantin® G30K RM/50 pk IN also suitable for electric vehicles**

(ID no. 30775215/SDS_GEN_DE/EN)

Date of print 13.06.2023

See corresponding entries for "Special precautions for user" for the respective regulations in the tables above.

14.7. Maritime transport in bulk according to IMO instruments

Maritime transport in bulk is not intended.

SECTION 15: Regulatory Information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Prohibitions, Restrictions and Authorizations

Annex XVII of Regulation (EC) No 1907/2006: Number on List: 3, 75

Hazardous Incident Ordinance (Germany):

Listed in above regulation: no

Directive 2012/18/EU - Control of Major Accident Hazards involving dangerous substances (EU):

Listed in above regulation: no

Water hazard class (§8/§10 AwSV (Self-classification of the mixture according to calculation method)): (1) Weakly water polluting.

German Regulation TA Luft (Technical Instruction on Air Quality Control, i.e. first Directive to the Federal Immission Control Ordinance)

Law on the Protection of Working Youth

15.2. Chemical Safety Assessment

Assessment of safe use has been performed for the mixture and the result is documented in section 7 and 8 of the SDS

SECTION 16: Other Information

Assessment of the hazard classes according to UN GHS criteria (most recent version)

Acute Tox. 4 (oral)

STOT RE (Kidney) 2

Acute Tox.

Acute toxicity

STOT RE

Specific target organ toxicity — repeated exposure

Eye Dam./Irrit.

Serious eye damage/eye irritation

Met. Corr.

Corrosive to metals

Skin Corr./Irrit.

Skin corrosion/irritation

H302

Harmful if swallowed.

H373

May cause damage to organs (Kidney) through prolonged or repeated

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 31.01.2023

Version: 1.0

Date previous version: not applicable

Previous version: none

Date / First version: 31.01.2023

Product: **Glysantin® G30K RM/50 pk IN also suitable for electric vehicles**

(ID no. 30775215/SDS_GEN_DE/EN)

Date of print 13.06.2023

H319	exposure.
H290	Causes serious eye irritation.
H314	May be corrosive to metals.
	Causes severe skin burns and eye damage.

Abbreviations

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road.
 ADN = The European Agreement concerning the International Carriage of Dangerous Goods by Inland waterways. ATE = Acute Toxicity Estimates. CAO = Cargo Aircraft Only. CAS = Chemical Abstract Service. CLP = Classification, Labelling and Packaging of substances and mixtures. DIN = German national organization for standardization. DNEL = Derived No Effect Level. EC50 = Effective concentration median for 50% of the population. EC = European Community. EN = European Standards. IARC = International Agency for Research on Cancer. IATA = International Air Transport Association. IBC-Code = Intermediate Bulk Container code. IMDG = International Maritime Dangerous Goods Code. ISO = International Organization for Standardization. STEL = Short-Term Exposure Limit. LC50 = Lethal concentration median for 50% of the population. LD50 = Lethal dose median for 50% of the population. TLV = Threshold Limit Value. MARPOL = The International Convention for the Prevention of Pollution from Ships. NEN = Dutch Norm. NOEC = No Observed Effect Concentration. OEL = Occupational Exposure Limit. OECD = Organization for Economic Cooperation and Development. PBT = Persistent, Bioaccumulative and Toxic. PNEC = Predicted No Effect Level. PPM = Parts per million. RID = The European Agreement concerning the International Carriage of Dangerous Goods by Rail. TWA = Time Weight Average. UN-number = UN number at transport. vPvB = very Persistent and very Bioaccumulative.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.

Vertical lines in the left hand margin indicate an amendment from the previous version.