



Basic geometry

	S	M	L	XL
Body Height in cm	166 - 174	174 - 186	186 - 196	≥ 196
Seat Height in mm (a)	681 - 831	706 - 856	740 - 890	770 - 920
Seat Tube Length in mm (b)	518	543	577	607
Top Tube Length in mm (c)	489	511	540	570
Head Tube Length in mm (d)	115	140	176	207
Head Tube Angle (e)	73°	73°	73°	73°
Seat Tube Angle (f)	80,5°	80,5°	80,5°	80,5°
Chainstay Length in mm (g)	420	420	420	420
Wheel Base in mm (h)	988	1.014	1.047	1.081
Stack in mm (i)	519	544	578	608
Reach in mm (j)	402	420	443	468
Bottom Bracket Offset in mm (l)	72	72	72	
Armpad Stack in mm (m)	604 - 698	629 - 723	663 - 757	693 - 787
Armpad Reach in mm (n)	387 - 467	416 - 495	448 - 527	474 - 553

Component geometry

	S	M	L	XL
Spacer in mm	25,0	25,0	25,0	25,0
Stem Length in mm	80	80	90	90
Handlebar Width in mm	400	400	400	400
Crank Length in mm	165,0	170,0	170,0	172,5
Chainring Size	50/37	50/37	50/37	50/37
Seat Post Length in mm	345	345	345	345
Maximum Seat Post Insertion Depth in mm	230	230	230	230
Minimum Seat Post Insertion Depth in mm	80	80	80	80
Wheel Size	28"	28"	28"	28"
Disc Size in mm	160 / 160	160 / 160	160 / 160	160 / 160