

# Technical Data Sheet

Electrical Cable

Dimensions , Requirements & Examinations



**Title: KBE Solar DB+ 4,00 mm<sup>2</sup>**

**Art. – No.: 730400015060QU**

## Conductor

- Material E-Cu tinned, DIN EN 60228 Class 5
- Construction 56 x 0,31 mm max.
- Conductor diameter 3,00 mm max.
- Resistance 5,09 mΩ/m max.

## Insulation Core

- Material Crosslinked Polyolefin
- Minimal Thickness 0,53 mm min.

## Insulation Jacket

- Material Crosslinked Spezial Polyolefin
- Minimal Thickness 0,58 mm min.
- Outer diameter 5,50 ± 0,2 mm

## Manufacturer`s identification

KBE SOLAR DB+ 4,00 MM2 H1Z2Z2-K  
62930 IEC 131 PV 1500-K HALOGEN FREE  
LOW SMOKE MADE IN GERMANY

## Requirements & Examinations

EN 50618:2014; IEC 62930:2017;  
2 PFG 1169 /10.19

- Temperature range - 40 °C to + 90 °C (for fixed and flexible installation)
- max. Temperature at conductor + 120 °C (20.000 h, 50 % residual elongation)
- Rated voltage U0/U AC 1,0 / 1,0 kV  
DC 1,5 / 1,5 kV
- Resistance weather-resistant and UV-resistance

## Other properties

- Direct Burial KBE-internal test according to UL 854 (Impact-Resistance test and Crushing - Resistance test)  
Installation instructions: DIN VDE 50174-1; § 5.2.4 and DIN VDE 0891 Part 6 § 4.2
- max. permissible operating voltage AC 1,2 / 1,2 kV
- max. permissible operating voltage DC 1,8 / 1,8 kV
- max. PV system voltage up to 2,0 kV DC possible
- Long-term insulation resistance in water 90 °C; 12 Weeks; 2000 V DC > 3 GΩ·m (following to UL 44)
- Cable weight ca. 56 g/m

Revision: 30.07.2020

The data sheet is not subject to the revision service

KBE Elektrotechnik GmbH

Symeonstraße 8 \* 12279 Berlin \* Germany \* tel.: +49(0)30/25208-100 \* fax.: +49(0)30/25208-100

\* info@kbe-elektrotechnik.com \* www.kbe-elektrotechnik.com