

	HQT-1/PR17YC	HQT-2/PR15YC	HQT-3/TR15C	HQT-4/SR15C	HQT-5/TR14C	HQT-6/JR19	HQT-7/LR15YC	HQT-8/TR17C	HQT-9/DR17YC	HQT-10/UR17	HQT-11/LR19YC
PNC Megapack	597530601	597530701	597530801	597530901	597531001	597531101	597531201	597531301	597531401	597531501	597531601
PNC Single	577484001	590710101	590843801	590710201	590844001	590844101	590844201	590844301	590844401	590844501	596421001
EAN	7,39293E+12		7,39293E+12	7,39293E+12		7,39293E+12			7,39293E+12		
	443223127410EP	443223160413EP	443223153412EP	443223155413EP	443223129411EP	443223043400EP	443221314410EP	443223161413EP	443221326410EP	443223064402EP	443221994418EP

Shell	Thread size	M14	M14	M10	M10	M10	M14	M14	M10	M14	M14	
	Thread pitch (mm)	1,25	1,25	1	1	1	1,25	1,25	1	1,25	1,25	
	Seat type	washer	washer	washer	washer	washer	washer	washer	washer	washer	washer	
	Resistor value (kΩ)	10 ± 5	10 ± 5	10 ± 5	10 ± 5	10 ± 5	10 ± 5	6 ± 3	10 ± 5	6 ± 3	10 ± 5	
	Reach (mm)	6,3	6,3	9,7	6,7	9,7	6,3	15	9,7	15	5,1	
	Hex Size	6HR 19h12	6HR 19h12	6HR 15,9h11	6HR 15,9h11	6HR15,9h11	6HR20,6h11	6HR20,6h11	6HR15,9h11	6HR15,9h11	6HR15,9h11	6HR20,6h11
	Terminal type	integrated	integrated	integrated	integrated	integrated	threaded terminal	threaded terminal	integrated	threaded terminal	threaded terminal	threaded terminal
	Overall Height	ISO28741	ISO28741	ISO28741	ISO28741	ISO28741	ISO28741	ISO28741	ISO28741	ISO28741	ISO28741	ISO28741
	Gap (mm)	0,55 ± 0,05	0,55 ± 0,05	0,55 ± 0,05	0,55 ± 0,05	0,55 ± 0,05	0,75 ± 0,1	0,7 + 0,1	0,55 ± 0,05	0,7 + 0,1	0,6 ± 0,1	0,8 + 0,1
Central electrode	Material	Ni/Cu	Ni/Cu	Ni/Cu	Ni/Cu	Ni/Cu	Ni	Ni/Cu	Ni/Cu	Ni/Cu	Ni	
	Size (ømm)	2,5	2,5	2	2	2	2,5	2,5	2	2,5	2,5	
Ground electrode	Material	NiCr2MnSi	NiCr2MnSi	NiCr2MnSi	NiCr2MnSi	NiCr2MnSi	NiCr2MnSi	NiCr2MnSi	NrCr2MnSi	NrCr2MnSi	NrCr2MnSi	
	Quantity	1	1	1	1	1	1	1	1	1	1	
Torque spec	Cast iron (Nm)	20-40	20-40	10-15	10-15	10-15	20-40	20-40	10-15	20-40	10-20	
	Aluminum (Nm)	20-30	20-30	10-15	10-15	10-15	20-30	20-30	10-15	20-30	10-20	
Heat range		17	15	15	15	14	19	15	17	17	19	

Megapack