

# HYVA CYLINDER

714 05 709



type: UMB 149-5-2480-K258-50-3/4"-HC

tipping weight: 13-25 ton

page # 1 / 2

Stage diameters 149 129 110 91 72	front view cylinder		<table border="1"> <tr><td>A</td><td>205</td></tr> <tr><td>ØC</td><td>170</td></tr> <tr><td>G<sup>1</sup></td><td>739</td></tr> <tr><td>I</td><td>481</td></tr> <tr><td>K<sup>1</sup></td><td>258</td></tr> <tr><td>M<sup>1</sup></td><td>99</td></tr> <tr><td>ØP</td><td>100</td></tr> <tr><td>ØQ</td><td>65</td></tr> <tr><td>S</td><td>488</td></tr> <tr><td>ØW</td><td>50</td></tr> <tr><td>X</td><td>45</td></tr> </table>	A	205	ØC	170	G <sup>1</sup>	739	I	481	K <sup>1</sup>	258	M <sup>1</sup>	99	ØP	100	ØQ	65	S	488	ØW	50	X	45
A	205																								
ØC	170																								
G <sup>1</sup>	739																								
I	481																								
K <sup>1</sup>	258																								
M <sup>1</sup>	99																								
ØP	100																								
ØQ	65																								
S	488																								
ØW	50																								
X	45																								

<sup>1</sup>including 20 mm pull-out [tol. -5; +30 mm]

<sup>2</sup>cylinder is delivered including oil inlet swivel adapter and cup

## specifications

total stroke <sup>1</sup>	2480 mm
dry weight cylinder only	95 kg
total volume	27.4 L
working volume	25.1 L
maximum pressure	220 bar
maximum pump flow	61 l/min
maximum allowable thrust first stage <sup>3</sup>	20.0 ton
oil inlet	3/4" BSP


## technical notes

This cylinder is a lifting device only and may not be used as a structural member or be subjected to side load. Sideload and/or poor alignment might result in cylinder leakage. Hyva therefore strongly recommends the use of a cradle, even in instances where the cylinder only tips to the rear or to the side. The cylinder is painted black RAL9005. For suitable hydraulic oils, please refer to data sheet OIL-0011. For details of available brackets and cradles, please refer data sheet 015BRA06.

Detailed calculations can be made using the HYVA Tipper Program, freely available from [tipper.hyva.com](http://tipper.hyva.com).

<sup>3</sup>The cylinder thrust on the first stage (from the HYVA Tipper Program) must not exceed the maximum allowable (see specifications above).

## tipping view



## tipping weight

PL	3230			mm	2860		
YCOG	600			mm	600		
ROH	600			mm	600		
BL	7660	6960	6380	mm	6920	6290	5770
CYL w.r.t. COG (W)	0	350	640	mm	0	310	580
	Tipping weight for full stroke of 46°				Tipping weight for full stroke of 52°		
Tipping weight	13	14	16	ton	14	16	18
	Tipping weight for second last stage, up to 37°				Tipping weight for 2nd last stage, up to 42°		
Tipping weight	18	22	25	ton	20	22	25


# HYVA CYLINDER

714 05 709

type

UMB 149-5-2480-K258-50-3/4"-HC

page # 2 / 2



## Spare part list

Pos	Part no.	Description	Qty.
1	73506750	BASE 169-0612-N0159	1
2	01226709	O-RING 165 X 4 NBR 70 SHORE	1
3	73101040	THREADED BOTTOM UM 169	1
4	01792571	LOCKING SCREW M6X12 INT. HEX. DIN 916	1
5	73103002	OIL INLET ADAPTOR UM 3/4"OT+O-RING	1
21	73605751	STAGE 149-0612-HC	1
22	71807149 K	SLIDER FL 149	1
23	71812149 K	LIFTRING FL 149/HP 150	1
31	73604751	STAGE 129-0612-HC	1
32	71807129 K	SLIDER FL 129/GF 129 (2 X 1/2)	1
33	71812129 K	LIFTRING FL 129/HP 129	1
41	73603751	STAGE 110-0612-HC	1
42	71807110 K	SLIDER FL 110/GF 110 (2 X 1/2)	1
43	71812110 K	LIFTRING FL 110	1
51	73602751	STAGE 091-0612-HC	1
52	71807091 K	SLIDER FL 091 (2 X 1/2)	1
53	71812091 K	LIFTRING FL 091	1

## Spare part list

Pos	Part no.	Description	Qty.
100	01745102	RETAINER KIT UMB D.65	1
101	73401751	PISTON B 072-0652-HC	1
102	71807072 K	SLIDER FL 072 (2 X 1/2)	1

## Seal kit complete

Part no.	Description
719 04 551K	Complete packset: Consists of all packsets with packset grease and o-ring.