

MOTIP Sanding Key Aid

Ord.-no.: 04057

Technical Information



Use MOTIP Sanding Key Aid as a fast-drying control layer when sanding primers and fillers on your car. Apply the Sanding Key Aid in a thin layer and let it dry. After sanding the marked surface, irregularities such as scratches and small holes (pinholes) remain black. These can then be easily removed with a suitable MOTIP filler.

Quality & properties

- Fast drying
- User-friendly

Physical & chemical data

- Base: Nitrocombi resin
- Colourname: Black
- Degree of gloss: mat, 10 ±2 GU
- Efficiency: 500 ML – 3 - 4 m²
- Dust dry: 5-10 min
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Vapour pressure: 4000/20 bar
- Flash point: n.a.
- Storage stability: 10 years
- Content: 500 ML

How to use

- Before use, carefully read the directions on the packaging and act accordingly.
- Pre Treatment: The surface should be clean, dry and free of grease.
- The aerosol should have room temperature. Best processing temperature 15 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample.
- Distance to the surface to be treated approximately 25 to 30 centimetre.
- Apply a thin layer of sanding aid and allow to dry.
- Sand the surface till the control lacquer is completely removed.
- After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).
- The drying time depends on the ambient temperature, the humidity of the air and the thickness of the lacquer applied.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labeling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

For any further technical questions call our hotline +31 (0) 561 69 44 00 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

As of November 24, 2021 – This release replaces all eventually earlier issued versions.