

Hood Type Touch Panel Dishwashers



- User friendly Touch Control Panel.
- Stainless steel body, washing and boiler tank. Contains stainless steel tank filter.
- Monoblock washing tank with round corners - Hygienic.
- 2.8 l water consumption per cycle.
- Adjustable detergent / rinse aid time from touch panel.
- Digital pressure switch for washing tank.
- Easy to follow washing steps with dynamic and coloured touch screen.
- Suitable for corner or in-line installation.
- Washing arms both available in stainless steel and reinforced polypropylene.
- Adjustable feet for height optimization.
- Easy start up: single button for water filling and heating in the boiler tank.
- Electrical components and wiring according to international standards and security regulations.
- Digital controlled, washing and rinsing temperatures for efficient washing.
- Non-return - Check valve system.
- Digital screen for temperature and error displays.
- Washing temperature at 55-60°C (water supply at a minimum of 2 bar and 50°C).
- Rinsing temperature at 80-85°C (water supply at a minimum of 2 bar and 50°C).
- Gentlewash option , Adjustment of washing pressure level with the minimum wear to dishes.
- The soft start option enables ultra-sensitive and quiet starting of the program.

	HOOD TYPE DISHWASHER CODE							
	OBM 1080T P	OBM 1080T PD	OBM 1080T PDT	OBM 1080T PDR	OBM 1080T PDRT	OBM 1080T R	OBM 1080T RT	
	071I10000.BB	071I11000.BB	071I11010.BB	071I11100.BB	071I11110.BB	071I00100.BB	071I00110.BB	
Detergent Dispenser	-	√	√	√	√	-	-	
Rinse Aid Dispenser	√	√	√	√	√	-	-	
Rinsing Pump	-	-	-	√	√	√	√	
Drain Pump	-	-	√	-	√	-	√	
3 Baskets Promotional (Plate, Glass and Cutlery)	√	√	√	√	√	√	√	
Stainless Steel Washing Arms	OPT	OPT	OPT	OPT	OPT	OPT	OPT	
Soft Start	OPT	OPT	OPT	OPT	OPT	OPT	OPT	
Gentlewash	OPT	OPT	OPT	OPT	OPT	OPT	OPT	

For the models do not have rinsing pump, program times are 5 seconds longer.

08

TECHNICAL FEATURES			
Electric connection	400V 3NPE / 50 Hz	Rinsing pump power	0,25 kW (OBM 1080T PDR / OBM 1080T PDRT OBM 1080T R / OBM 1080T RT)
Total rating	9.66 kW	Water inlet pressure / Temp.	2-4 Bar / 50 °C
Washing capacity (plate/hr)	1152 plate (Max.)	Heat power (Washing/Rinsing)	2 / 9 kW
Washing capacity (basket/hr)	72 / 36 / 27 / 24 / 18	Dirty water discharge connection	1 1/4" (Ø42 mm) OBM 1080T P / OBM 1080T PDR / OBM 1080T R 3/4" (Ø28 mm) OBM 1080T PDT / OBM 1080T PDRT / OBM 1080T RT
Washing / Boiler tank capacity	23 / 7 l.	Maximum noise	75 dBA
Washing program number	5	Gross weight	120 (±5) kg
Program times (seconds)	50 / 100 / 130 / 150 / 190	Dimensions (WxDxH)	700x785x1480 (1960) mm
Washing water temp.	55-60°C	Protection class	IPX5
Rinsing water temp.	80-85 °C (max.)	Rack dimension	50 x 50 cm
Water inlet connection	3/4 "	Useful loading height	445 mm
Washing pump power	0.66 kW	Inclination	6°