

## MOTIP Backlight Paint

Ord.-no.: look at ordering information

## Technical Information



Highlight the rear lights of your car with MOTIP Backlight Spray. The transparent lacquer has a lasting gloss and is scratch-free and shock proof. The lacquer is resistant to petrol, chemicals and the weather.

### Quality & properties

- Not suitable to treat surfaces of polycarbonate!
- Lasting gloss
- Scratch free and shock proof
- Resistant to petrol, chemicals and weather influences
- Good adhesion

### Physical & chemical data

- Base: Alkyd resin
- Colourname:
  - ◊ black
  - ◊ red
- Smell: Characteristic
- Degree of gloss: gloss, >75 GU
- Efficiency: 400 ML – 8 backlights
- Dry to touch: 60 min
- Dust dry: 10 - 20 min
- Completely dry: 4 h
- Overcoatable: 4 min
- Surfaces: Backlights
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Vapour pressure: 8300/20 bar
- Flash point: n.a.
- Relative density: 0.74 g/ml
- Storage stability: 10 y
- Content:
  - ◊ 400 ML
  - ◊ 150 ML

### How to use

- Before use, carefully read the directions on the packaging and act accordingly.
- The surface must be clean, dry and free of grease.
- The aerosol should have room temperature. Best processing temperature 10 to 25°C.
- Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimetre.
- Spray the lacquer in several thin layers, till the desired result has been achieved. (Before applying the next layer, again shake the aerosol).
- After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).
- The drying time depends on the ambient temperature, the humidity of the air and the thickness of the lacquer applied.

### Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

### Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

### Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

European Aerosols GmbH, Kurt-Vogelsang-Straße 6, 74855 Haßmersheim - [info-de@european-aerosols.com](mailto:info-de@european-aerosols.com)  
European Aerosols B.V., Wolframweg 2, NL-8471 XC Wolvega - [info-nl@european-aerosols.com](mailto:info-nl@european-aerosols.com)