

# FEATURES AND BENEFITS



## TYROCK TRA CODE : IND-X

Size	PR	Type	Rim Width in	SW	OD	Static Loaded Radius	Rolling Circum	Infl. Prs.	Load Capacity		
									Load Index	Speed	Max Load
										Speed Symbol	kmph
mm/in	mm/in	mm/in	mm/in	bar	psi	mph	lbs				
18.4-26	16.0	TL	W16L	467	1425	671	4275	3.2	156 A8	40	4750
				18.4	56.1	26.4	168.3	46		25	10470
18.4-26	14	TL	W16L	467	1425	671	4275	2.9	159 A8	40	4375
				18.4	56.1	26.4	168.3	42		25	9645
18.4-26	12.0	TL	W16L	467	1425	671	4275	2.5	156 A8	40	4000
				18.4	56.1	26.4	168.3	36		25	8810
12.5/80-18	14	TL	9.0	308	988	465	2900	4.3	132 A8	40	2000
				39	12	18	114	62		25	4410
12.5/80-18	12	TL	9.0	308	988	465	2900	3.75	129 A8	40	1850
				39	12	18	114	54		25	4080
12.5/80-18	10	TL	9.0	308	988	465	2900	3.1	126 A8	40	1700
				39	12	18	114	45		25	3750