

FEATURES AND BENEFITS

Multi rib low section design

High flotation with minimum soil compaction

Extra wide tread & high volume

High load carrying capacity

Non directional tread pattern

Prevents skidding while turning

Lugs are open & angled at the shoulder

Ensures maximum stability

Large contact area

Designed for both on & off-road application

FARM IMPLEMENT 404

TRA CODE : IND-X

Size	PR	Type	Rim Width	SW	OD	Static Loaded Radius	Rolling Circum	Load Index, Speed Index	Infl. Pres.	speed	Load	
				mm/in	mm/in	mm/in	mm/in		bar	kmph	kg	
										psi	mph	lbs
15.0/70-18	16	TL	13.00	405	1010	450	3000	151 A8	4.25	40	3450	
				16	40	18	118		62	25	7600	
500/50-17	14	TL	16.00DC	500	945	415	2752	152 A8	2.8	40	3550	
				20	37	16	108		41	25	7825	
	10	TL	16.00DC	500	945	415	2752	143 A8	2	40	2725	
				20	37	16	108		29	25	6010	
	18	TL	16.00DC	500	945	415	2752	154 A8	3.6	40	3750	
				20	37	16	108		52	25	8265	
15.0/55-17	14	TL	13.00	15	33	15	98	141 A8	3.7	40	2575	
									54	25	5675	
	18	TL	13.00					146A8	4.7	40	3000	
									68	25	6610	
14.0/65-16	14	TL	11.00	355	875	390	2552	142 A8	2.6	40	2120	
									38	25	4670	
	10	TL	11.00					134A8	4	40	2650	
									58	25	5840	
10	TL	11.00	134 A8	2.8	40	2120						
				41	25	4675						