

# FEATURES AND BENEFITS

**Tilted lug tip**  
Lesser vibration & noise

**Mud breaker**  
Better self cleaning

**Higher angle & lug overlap at centre**  
Better roadability

**Wider tread**  
larger inner volume  
Reduced soil compaction

**R1-W tread depth**  
Longer tire life

**Lower angle at shoulder**  
Superior traction

**Rounded shoulder**  
Lesser damage to soil & crop

\*CTR-Low Compaction, High Traction, High Roadability

## FARMAX R75

WITH THE POWER OF CTR\*



# FARMAX R75

Size	Rim	Infl tire dimension		Static Loaded radius	Rolling circm.	Load Index	Infl. press.	Recommended load, kg (lbs)					
		SW	OD					Speed, km/h (mph)					
		mm/in	mm/in					mm/in	mm/in	Speed	bar	Static	10
						psi		6	12	19	25	31	
400/75 R38	W12, W13, W14	404 15.9	1565 61.6	723 28.5	4646 182.9	138A8/ B	0.8	3610	2360	1930	1680	1570	1570
							12	7950	5200	4250	3700	3460	3460
							1	4120	2690	2200	1920	1790	1790
							15	9070	5930	4850	4230	3940	3940
							1.4	5010	3270	2680	2330	2180	2180
							20	11040	7200	5900	5130	4800	4800
							1.6	5430	3540	2900	2530	2360	2360
							23	11960	7800	6390	5570	5200	5200