

FEATURES AND BENEFITS



Tilted lug tip
Lesser vibration & noise

Mud breaker
Better self cleaning

Higher angle & lug overlap at centre
Better roadability

Wider tread
larger inner volume
Reduced soil compaction

R1-W tread depth
Longer tire life

Lower angle at shoulder
Superior traction

Rounded shoulder
Lesser damage to soil & crop

*CTR-Low Compaction, High Traction, High Roadability

FARMAX R65

WITH THE POWER OF CTR*



FARMAX R65

Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommended load, kg (lbs)								
								Speed, km/h (mph)								
		SW	OD					Non cyclic operation				Cyclic operation				
								mm/in	mm/in	mm/in	mm/in	Speed	Field operation	25	40	50
mm/in	mm/in	mm/in	mm/in	mm/in	mm/in	Symbol	psi	operation	16	25	31	40	psi	6	9	
650/65 R42	DW-20BL W18L	645 25.4	1913 75.3	885 34.8	5775 227.4	158D	0.8	3240	3340	3090	2960	2820	1	4790	4370	
							12	7140	7360	6810	6520	6210	15	10550	9630	
							1.0	3690	3800	3510	3370	3210	1	5460	4980	
							15	8130	8370	7730	7420	7070	18	12030	10970	
							1.3	4270	4400	4060	3900	3710	2	6310	5750	
							19	9410	9690	8940	8590	8170	24	13900	12670	
							1.6	4890	5040	4650	4460	4250	2	7230	6590	
							23	10770	11100	10240	9820	9360	29	15930	14520	
							165D	0.8	3240	3340	3090	2960	2820	1	4790	4370
						12	7140	7360	6810	6520	6210	15	10550	9630		
						1.3	3690	3800	3510	3370	3210	2	5460	4980		
						19	8130	8370	7730	7420	7070	24	12030	10970		
						1.6	4890	5040	4650	4460	4250	2	7230	6590		
						23	10770	11100	10240	9820	9360	29	15930	14520		
						2.0	5470	5640	5210	5000	4760	3	8090	7380		
						29	12050	12420	11480	11010	10480	36	17820	16260		
						2.4	5920	6100	5640	5410	5150	3	8760	7980		
						35	13040	13440	12420	11920	11340	44	19300	17580		
						170D	0.8	3240	3340	3090	2960	2820	1	4790	4370	
						12	7140	7360	6810	6520	6210	15	10550	9630		
						1.3	3690	3800	3510	3370	3210	2	5460	4980		
						19	8130	8370	7730	7420	7070	24	12030	10970		
						1.6	4890	5040	4650	4460	4250	2	7230	6590		
						23	10770	11100	10240	9820	9360	29	15930	14520		
						2.2	5520	5690	5260	5040	4800	3	8160	7440		
						32	12160	12530	11590	11100	10570	40	17970	16390		
						2.7	6280	6470	5980	5730	5460	3	9280	8460		
39	13830	14250	13170	12620	12030	49	20440	18630								
3.2	6900	7110	6570	6300	6000	4	10200	9300								
46	15200	15660	14470	13880	13220	58	22470	20480								

Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommended load, kg (lbs)								
								Speed, km/h (mph)								
		SW	OD					Non cyclic operation						Cyclic operation		
		mm/in	mm/in					mm/in	mm/in	Speed	bar	Field operation	25	40	50	65
				Symbol	psi		16	25	31	40	psi	6	9			
650/65 R38	DW20B	645 25.4	1811 71.3	821 32.3	5490 216.2	157D	0.8	3090	3190	2950	2820	2690	1	4570	4170	
							20	6810	7030	6500	6210	5930	15	10070	9190	
							1	3530	3640	3360	3220	3070	1.3	5220	4760	
							23	7780	8020	7400	7090	6760	18	11500	10480	
							1.3	4070	4190	3880	3720	3540	1.6	6020	5490	
							29	8960	9230	8550	8190	7800	24	13260	12090	
							1.6	4740	4890	4520	4330	4125	2	7010	6390	
							35	10440	10770	9960	9540	9090	29	15440	14070	
							163D	0.8	3160	3260	3010	2890	2750	1.0	4680	4260
						23		10440	10770	9960	9540	9090	29	15440	14070	
						1.2		3970	4090	3780	3620	3450	1.5	5870	5350	
						12		6960	7180	6630	6370	6060	15	10310	9380	
						1.5		4500	4630	4280	4110	3910	1.9	6650	6060	
						22		9910	10200	9430	9050	8610	27	14650	13350	
						2.0		5220	5380	4970	4770	4540	2.5	7720	7040	
						29		11500	11850	10950	10510	10000	36	17000	15510	
						2.4		5610	5780	5340	5120	4875	3	8290	7560	
						35	12360	12730	11760	11280	10740	44	18260	16650		

Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommended load, kg (lbs)								
								Speed, km/h (mph)								
		SW	OD					Non cyclic operation						Cyclic operation		
		mm/in	mm/in					mm/in	mm/in	Speed	bar	Field operation	25	40	50	65
				Symbol	psi		16	25	31	40	psi	6	9			
600/65 R34	DW20B W18L	591 23.3	1644 64.7	780 30.7	5010 197.2	151D	0.8	2600	2680	2470	2370	2260	1	3840	3500	
							12	5730	5900	5440	5220	4980	15	8460	7710	
							1.0	2970	3060	2830	2710	2580	1.25	4390	4000	
							15	6540	6740	6230	5970	5680	18	9670	8810	
							1.3	3420	3520	3250	3120	2970	1.63	5050	4600	
							19	7530	7750	7160	6870	6540	24	11120	10130	
							1.6	3970	4090	3780	3620	3450	2	5870	5350	
							23	8740	9010	8330	7970	7600	29	12930	11780	
							157D	0.8	2600	2680	2470	2370	2260	1	3840	3500
						12		5730	5900	5440	5220	4980	15	8460	7710	
						1.2		3340	3440	3180	3050	2900	1.5	4930	4500	
						17		7360	7580	7000	6720	6390	22	10860	9910	
						1.5		3770	3890	3590	3440	3280	1.875	5580	5080	
						22		8300	8570	7910	7580	7220	27	12290	11190	
						2.0		4380	4510	4170	4000	3810	2.50	6480	5910	
						29		9650	9930	9190	8810	8390	36	14270	13020	
						2.4		4740	4890	4520	4330	4125	3	7010	6390	
						35	10440	10770	9960	9540	9090	44	15440	14070		

Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommended load, kg (lbs)							
		SW	OD					Speed, km/h (mph)							
								Non cyclic operation				Cyclic operation			
								Field operation	25	40	50	65	bar	10	15
mm/in	mm/in	mm/in	mm/in	Speed Symbol	bar psi	16	25	31	40	psi	6	9			
600/65 R30	DW20B W18L	611 24.1	1542 60.7	693 27	4626 182	149D	0.8	2450	2520	2330	2240	2130	1	3620	3300
							12	5400	5550	5130	4930	4690	15	7970	7270
							1.0	3940	4060	3760	3600	3430	1.25	5830	5320
							15	8680	8940	8280	7930	7560	18	12840	11720
							1.3	3230	3330	3080	2950	2810	1.63	4780	4360
							19	7110	7330	6780	6500	6190	24	10530	9600
							1.6	3740	3850	3560	3410	3250	2	5530	5040
							23	8240	8480	7840	7510	7160	29	12180	11100
						152D	0.8	2450	2520	2330	2240	2130	1.00	3620	3300
							12	5400	5550	5130	4930	4690	15	7970	7270
							1.2	3160	3260	3010	2890	2750	1.50	4680	4260
							17	6960	7180	6630	6370	6060	22	10310	9380
							1.6	3740	3850	3560	3410	3250	2.00	5530	5040
							23	8240	8480	7840	7510	7160	29	12180	11100
							1.9	4080	4210	3890	3730	3550	2.375	6040	5500
							28	8990	9270	8570	8220	7820	34	13300	12110
						155D	0.8	2450	2520	2330	2240	2130	1	3620	3300
							12	5400	5550	5130	4930	4690	15	7970	7270
							1.2	3150	3250	3000	2880	2740	1.5	4660	4250
							17	6940	7160	6610	6340	6040	22	10260	9360
							1.6	3740	3850	3560	3410	3250	2	5530	5040
							23	8240	8480	7840	7510	7160	29	12180	11100
							2.0	4140	4270	3940	3780	3600	2.50	6120	5580
							29	9120	9410	8680	8330	7930	36	13480	12290
							2.4	4460	4590	4240	4070	3875	3	6590	6010
							35	9820	10110	9340	8960	8540	44	14520	13240

Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommended load, kg (lbs)							
		SW	OD					Speed, km/h (mph)							
								Non cyclic operation				Cyclic operation			
								Field operation	25	40	50	65	bar	10	15
mm/in	mm/in	mm/in	mm/in	Speed Symbol	bar psi	16	25	31	40	psi	6	9			
540/65 R30	W16L W18L	550 21.7	1464 57.6	666 26	4461 176	143D	0.8	2080	2140	1980	1900	1810	1	3080	2810
							12	4580	4710	4360	4190	3990	15	6780	6190
							1.2	2670	2750	2540	2440	2320	1.5	3940	3600
							17	5880	6060	5590	5370	5110	22	8680	7930
							1.4	2890	2970	2750	2640	2510	1.75	4270	3890
							20	6370	6540	6060	5810	5530	25	9410	8570
							1.6	3130	3230	2980	2860	2725	2	4630	4220
							23	6890	7110	6560	6300	6000	29	10200	9300
						150D	0.8	2080	2140	1980	1900	1810	1	3080	2810
							12	4580	4710	4360	4190	3990	15	6780	6190
							1.6	3170	3270	3020	2900	2760	2	4690	4280
							23	6980	7200	6650	6390	6080	29	10330	9430
							2.0	3460	3570	3300	3160	3010	2.5	5120	4670
							29	7620	7860	7270	6960	6630	36	11280	10290
							2.4	3850	3970	3670	3520	3350	3	5700	5190
							35	8480	8740	8080	7750	7380	44	12560	11430

Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommended load, kg (lbs)							
		Speed, km/h (mph)													
		Non cyclic operation						Cyclic operation							
		SW	OD					mm/in	mm/in	Speed	bar	Field operation	25	40	50
mm/in	mm/in	mm/in	mm/in	Symbol	psi	operation	16	25	31	40	psi	6	9		
540/65 R28	W16L W18L	550 21.7	1413 55.6	640 25.2	4178 164.5	142D	0.8	2020	2090	1930	1850	1760	1	2990	2730
							12	4450	4600	4250	4070	3880	15	6590	6010
							1.0	2310	2380	2200	2110	2010	1.25	3420	3120
							15	5090	5240	4850	4650	4430	18	7530	6870
							1.3	2660	2740	2530	2430	2310	1.625	3930	3580
							19	5860	6040	5570	5350	5090	24	8660	7890
							1.6	3050	3140	2900	2780	2650	2	4510	4110
	23	6720	6920	6390	6120	5840	29	9930	9050						
	149D	0.8	2020	2090	1930	1850	1760	1	2990	2730					
		12	4450	4600	4250	4070	3880	15	6590	6010					
		1.6	3070	3160	2920	2800	2670	2	4540	4140					
		23	6760	6960	6430	6170	5880	29	10000	9120					
		2.0	3420	3520	3250	3120	2970	2.5	5050	4600					
		29	7530	7750	7160	6870	6540	36	11120	10130					
2.4		3740	3850	3560	3410	3250	3	5530	5040						
35	8240	8480	7840	7510	7160	44	12180	11100							

Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommended load, kg (lbs)							
		Speed, km/h (mph)													
		Non cyclic operation						Cyclic operation							
		SW	OD					mm/in	mm/in	Speed	bar	Field operation	25	40	50
mm/in	mm/in	mm/in	mm/in	Symbol	psi	operation	16	25	31	40	psi	6	9		
480/65 R28	W15L W14L	479 18.9	1335 52.6	605.6 24	4068 160	136D	0.8	1680	1730	1600	1530	1460	1	2480	2260
							12	3700	3810	3520	3370	3220	15	5460	4980
							1.0	1920	1980	1830	1750	1670	1.25	2840	2590
							15	4230	4360	4030	3850	3680	18	6260	5700
							1.3	2220	2290	2110	2030	1930	1.63	3280	2990
							19	4890	5040	4650	4470	4250	24	7220	6590
							1.6	2580	2650	2450	2350	2240	2	3810	3470
	23	5680	5840	5400	5180	4930	29	8390	7640						
	142D	0.8	1680	1730	1600	1530	1460	1	2480	2260					
		12	3700	3810	3520	3370	3220	15	5460	4980					
		1.6	2580	2650	2450	2350	2240	2.00	3810	3470					
		23	5680	5840	5400	5180	4930	29	8390	7640					
		2.0	2840	2930	2700	2590	2470	2.50	4200	3830					
		29	6260	6450	5950	5700	5440	36	9250	8440					
2.4		3050	3140	2900	2780	2650	3	4510	4110						
35	6720	6920	6390	6120	5840	44	9930	9050							

Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommended load, kg (lbs)								
		SW	OD					Speed, km/h (mph)								
								Non cyclic operation						Cyclic operation		
								Speed	bar	Field operation	25	40	50	65	bar	10
mm/in	mm/in	mm/in	mm/in	Symbol	psi	operation	16	25	31	40	psi	6	9			
480/65 R24	W15L W14L	479 18.9	1234 48.6	561 22	3644 143	133D	0.8	1580	1620	1500	1440	1370	1	2330	2120	
							12	3480	3570	3300	3170	3020	15	5130	4670	
							1.0	1790	1850	1710	1640	1560	1.25	2650	2420	
							15	3940	4070	3770	3610	3440	18	5840	5330	
							1.4	2170	2240	2070	1980	1890	1.75	3210	2930	
							20	4780	4930	4560	4360	4160	25	7070	6450	
							1.6	2370	2440	2260	2160	2060	2	3500	3190	
	23	5220	5370	4980	4760	4540	29	7710	7030							
	140D	0.8	1580	1620	1500	1440	1370	1	2330	2120						
		12	3480	3570	3300	3170	3020	15	5130	4670						
		1.4	2170	2240	2070	1980	1890	1.75	3210	2930						
		20	4780	4930	4560	4360	4160	25	7070	6450						
		2.0	2660	2740	2530	2430	2310	2.50	3930	3580						
		29	5860	6040	5570	5350	5090	36	8660	7890						
2.4		2880	2960	2740	2630	2500	3	4250	3880							
35	6340	6520	6040	5790	5510	44	9360	8550								

Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommended load, kg (lbs)								
		SW	OD					Speed, km/h (mph)								
								Non cyclic operation						Cyclic operation		
								Speed	bar	Field operation	25	40	50	65	bar	10
mm/in	mm/in	mm/in	mm/in	Symbol	psi	operation	16	25	31	40	psi	6	9			
540/65 R24	W16L W18L	550 21.7	1312 51.7	590 23	3879 153	140D	0.8	1920	1980	1830	1750	1670	1	2840	2590	
							12	4230	4360	4030	3850	3680	15	6260	5700	
							1.0	2160	2230	2060	1970	1880	1.25	3200	2910	
							15	4760	4910	4540	4340	4140	18	7050	6410	
							1.3	2480	2560	2370	2270	2160	1.63	3670	3350	
							19	5460	5640	5220	5000	4760	24	8080	7380	
							1.6	2880	2960	2740	2630	2500	2	4250	3880	
	23	6340	6520	6040	5790	5510	29	9360	8550							
	146D	0.8	1920	1980	1830	1750	1670	1	2840	2590						
		12	4230	4360	4030	3850	3680	15	6260	5700						
		1.3	2480	2560	2370	2270	2160	1.625	3670	3350						
		19	5460	5640	5220	5000	4760	24	8080	7380						
		2.0	3190	3280	3030	2910	2770	2.5	4710	4290						
		29	7030	7220	6670	6410	6100	36	10370	9450						
2.4		3450	3560	3290	3150	3000	3	5100	4650							
35	7600	7840	7250	6940	6610	44	11230	10240								

Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommended load, kg (lbs)							
		SW	OD					Speed, km/h (mph)							
								Non cyclic operation				Cyclic operation			
								Field operation	25	40	50	65	bar	10	15
mm/in	mm/in	mm/in	mm/in	Speed Symbol	bar	psi	16	25	31	40	psi	6	9		
440/65 R24	W13, W14L W15L	441 17.4	1182 46.5	540 21	3565 140	128D	0.8	1370	1410	1300	1250	1190	1	2020	1840
							12	3020	3110	2860	2750	2620	15	4450	4050
							1.0	1560	1610	1490	1430	1360	1.25	2310	2110
							15	3440	3550	3280	3150	3000	18	5090	4650
							1.4	1900	1960	1810	1730	1650	1.75	2810	2560
							20	4190	4320	3990	3810	3630	25	6190	5640
							1.6	2070	2130	1970	1890	1800	2	3060	2790
						23	4560	4690	4340	4160	3960	29	6740	6150	
						135D	0.8	1370	1410	1300	1250	1190	1	2020	1840
							12	3020	3110	2860	2750	2620	15	4450	4050
							1.4	1900	1960	1810	1730	1650	1.75	2810	2560
							20	4190	4320	3990	3810	3630	25	6190	5640
							2.0	2310	2380	2200	2110	2010	2.5	3420	3120
							29	5090	5240	4850	4650	4430	36	7530	6870
2.4	2510	2580	2390	2290	2180		3	3710	3380						
35	5530	5680	5260	5040	4800	44	8170	7440							

Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommended load, kg (lbs)							
		SW	OD					Speed, km/h (mph)							
								Non cyclic operation				Cyclic operation			
								Field operation	25	40	50	65	bar	10	15
mm/in	mm/in	mm/in	mm/in	Speed Symbol	bar	psi	16	25	31	40	psi	6	9		
540/65 R34	W16L W18L	550 21.7	1566 61.7	717 28.2	4659 183.4	145D	0.8	2210	2280	2100	2020	1920	1	3260	2980
							12	4870	5020	4630	4450	4230	15	7180	6560
							1.0	2520	2600	2400	2300	2190	1.25	3720	3390
							15	5550	5730	5290	5070	4820	18	8190	7470
							1.3	2910	3000	2770	2660	2530	1.625	4300	3920
							19	6410	6610	6100	5860	5570	24	9470	8630
							1.6	3340	3440	3180	3050	2900	2	4930	4500
						23	7360	7580	7000	6720	6390	29	10860	9910	
						152D	0.8	2210	2280	2100	2020	1920	1	3260	2980
							12	4870	5020	4630	4450	4230	15	7180	6560
							1.3	2910	3000	2770	2660	2530	1.625	4300	3920
							19	6410	6610	6100	5860	5570	24	9470	8630
							2.0	3730	3840	3550	3400	3240	2.5	5510	5020
							29	8220	8460	7820	7490	7140	36	12140	11060
2.4	4080	4210	3890	3730	3550		3	6040	5500						
35	8990	9270	8570	8220	7820	44	13300	12110							

Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommended load, kg (lbs)							
		SW	OD					Speed, km/h (mph)							
								Non cyclic operation				Cyclic operation			
								Field operation	25	40	50	65	bar	10	15
mm/in	mm/in	mm/in	mm/in	Speed Symbol	bar	psi	16	25	31	40	psi	6	9		
600/65 R38	DW20B W18L	600 23.6	1745 68.7	798 31	5236 206	153D	0.8	2730	2810	2600	2490	2370	1	4030	3670
							12	6010	6190	5730	5480	5220	15	8880	8080
							1.0	3120	3210	2970	2850	2710	1.25	4610	4200
							15	6870	7070	6540	6280	5970	18	10150	9250
							1.3	3600	3710	3430	3290	3130	1.625	5320	4850
							19	7930	8170	7560	7250	6890	24	11720	10680
							1.6	4200	4330	4000	3830	3650	2	6210	5660
							23	9250	9540	8810	8440	8040	29	13680	12470

Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommended load, kg (lbs)							
		Speed, km/h (mph)													
		Non cyclic operation						Cyclic operation							
		SW	OD					mm/in	mm/in	Speed	bar	Field operation	25	40	50
mm/in	mm/in	mm/in	mm/in	Symbol	psi	operation	16	25	31	40	psi	6	9		
540/65 R38	W16L W18L	550 21.7	1667 65.6	767 30	4975 196	147D	0.8	2330	2410	2220	2130	2030	1	3450	3150
							12	5130	5310	4890	4690	4470	15	7600	6940
							1.0	2660	2740	2530	2430	2310	1.25	3930	3580
							15	5860	6040	5570	5350	5090	18	8660	7890
							1.4	3230	3330	3080	2950	2810	1.75	4780	4360
							20	7110	7330	6780	6500	6190	25	10530	9600
							1.6	3540	3640	3370	3230	3075	2	5230	4770
	23	7800	8020	7420	7110	6770	29	11520	10510						
	153D	0.8	2330	2410	2220	2130	2030	1	3450	3150					
		12	5130	5310	4890	4690	4470	15	7600	6940					
		1.4	3230	3330	3080	2950	2810	1.8	4780	4360					
		20	7110	7330	6780	6500	6190	25	10530	9600					
		2.0	3930	4050	3740	3590	3420	2.5	5810	5300					
		29	8660	8920	8240	7910	7530	36	12800	11670					
2.4		4200	4330	4000	3830	3650	3	6210	5660						
35	9250	9540	8810	8440	8040	44	13680	12470							

Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommended load, kg (lbs)							
		Speed, km/h (mph)													
		Non cyclic operation						Cyclic operation							
		SW	OD					mm/in	mm/in	Speed	bar	Field operation	25	40	50
mm/in	mm/in	mm/in	mm/in	Symbol	psi	operation	16	25	31	40	psi	6	9		
440/65 R28	W13 W14L W15L	441 17.4	1283 50.5	590 23	3869 152	138D	0.8	1470	1520	1400	1340	1280	1.0	2180	1980
							12	3240	3350	3080	2950	2820	15	4800	4360
							1.2	1890	1940	1800	1720	1640	1.5	2790	2540
							17	4160	4270	3960	3790	3610	22	6150	5590
							2.0	2480	2560	2370	2270	2160	2.5	3670	3350
							29	5460	5640	5220	5000	4760	36	8080	7380
							2.4	2710	2800	2580	2480	2360	3	4010	3660
							35	5970	6170	5680	5460	5200	44	8830	8060

Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommended load, kg (lbs)							
		Speed, km/h (mph)													
		Non cyclic operation						Cyclic operation							
		SW	OD					mm/in	mm/in	Speed	bar	Field operation	25	40	50
mm/in	mm/in	mm/in	mm/in	Symbol	psi	operation	16	25	31	40	psi	6	9		
600/65 R28	DW20B W18L	611 24.1	1491 58.7	668 26	4473 176	154D	0.6	2040	2100	1940	1860	1770	0.75	3010	2740
							9	4490	4630	4270	4100	3900	11	6630	6040
							0.8	2370	2440	2260	2160	2060	1	3500	3190
							12	5220	5370	4980	4760	4540	15	7710	7030
							1.4	3300	3400	3140	3010	2870	1.8	4880	4450
							20	7270	7490	6920	6630	6320	25	10750	9800
							2.0	4030	4150	3830	3680	3500	2.5	5950	5430
							29	8880	9140	8440	8110	7710	36	13110	11960
							2.4	4310	4440	4110	3940	3750	3	6380	5810
							35	9490	9780	9050	8680	8260	44	14050	12800

Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommended load, kg (lbs)								
		Speed, km/h (mph)														
		Non cyclic operation						Cyclic operation								
		SW	OD					mm/in	mm/in	mm/in	mm/in	Speed	bar	Field	25	40
mm/in	mm/in	mm/in	mm/in	Symbol	psi	operation	16					25	31	40	psi	6
420/65 R24	W13 W11 W12	418 16.5	1156 45.5	524 21	3414 134	138D	0.8	1280	1320	1220	1170	1110	1.0	1890	1720	
							12	2820	2910	2690	2580	2440	15	4160	3790	
							1.2	1630	1680	1550	1490	1420	1.5	2410	2200	
							17	3590	3700	3410	3280	3130	22	5310	4850	
							2.0	2160	2230	2060	1970	1880	2.5	3200	2910	
							29	4760	4910	4540	4340	4140	36	7050	6410	
							2.4	2320	2390	2210	2120	2020	3	3430	3130	
							35	5110	5260	4870	4670	4450	44	7560	6890	
							3.2	2710	2800	2580	2480	2360	4	4010	3660	
46	5970	6170	5680	5460	5200	58	8830	8060								

Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommended load, kg (lbs)								
		Speed, km/h (mph)														
		Non cyclic operation						Cyclic operation								
		SW	OD					mm/in	mm/in	mm/in	mm/in	Speed	bar	Field	25	40
mm/in	mm/in	mm/in	mm/in	Symbol	psi	operation	16					25	31	40	psi	6
440/65 R20	W14 W13L W15L	441 17.4	1080 42.5	483 19	3240 128	138D	0.8	1300	1340	1240	1190	1130	1.0	1920	1750	
							12	2860	2950	2730	2620	2490	15	4230	3850	
							1.2	1680	1730	1600	1530	1460	1.5	2480	2260	
							17	3700	3810	3520	3370	3220	22	5460	4980	
							2.0	2420	2490	2300	2210	2100	2.5	3570	3260	
							29	5330	5480	5070	4870	4630	36	7860	7180	
							2.4	2710	2800	2580	2480	2360	3	4010	3660	
							35	5970	6170	5680	5460	5200	44	8830	8060	

Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommended load, kg (lbs)								
		Speed, km/h (mph)														
		Non cyclic operation						Cyclic operation								
		SW	OD					mm/in	mm/in	mm/in	mm/in	Speed	bar	Field	25	40
mm/in	mm/in	mm/in	mm/in	Symbol	psi	operation	16					25	31	40	psi	6
340/65 R20	W11 W10 W12	343 13.5	950 37.4	431 17	2850 112	124D	0.8	870	900	830	800	760	1.0	1290	1180	
							12	1920	1980	1830	1760	1670	15	2840	2600	
							1.2	1130	1160	1070	1030	980	1.5	1670	1520	
							17	2490	2560	2360	2270	2160	22	3680	3350	
							2.0	1620	1670	1540	1480	1410	2.5	2400	2190	
							29	3570	3680	3390	3260	3110	36	5290	4820	
							2.4	1840	1900	1750	1680	1600	3	2720	2480	
							35	4050	4190	3850	3700	3520	44	5990	5460	

Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommended load, kg (lbs)								
		Speed, km/h (mph)														
		Non cyclic operation						Cyclic operation								
		SW	OD					mm/in	mm/in	mm/in	mm/in	Speed	bar	Field	25	40
mm/in	mm/in	mm/in	mm/in	Symbol	psi	operation	16					25	31	40	psi	6
340/65 R18	W11 W10 W12	343 13.5	899 35.4	406 16	2697 106	122D	0.8	830	850	790	760	720	1.0	1220	1120	
							12	1830	1870	1740	1670	1590	15	2690	2470	
							1.2	1070	1100	1020	980	930	1.5	1580	1440	
							17	2360	2420	2250	2160	2050	22	3480	3170	
							2.0	1540	1590	1470	1410	1340	2.5	2280	2080	
							29	3390	3500	3240	3110	2950	36	5020	4580	
							2.4	1730	1780	1640	1580	1500	3	2550	2330	
							35	3810	3920	3610	3480	3300	44	5620	5130	

Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommended load, kg (lbs)								
								Speed, km/h (mph)								
		SW	OD					Non cyclic operation				Cyclic operation				
		mm/in	mm/in					mm/in	mm/in	mm/in	mm/in	bar	10	15	bar	10
						Speed	bar	Field	25	40	50	65	bar	10	15	
						Symbol	psi	operation	16	25	31	40	psi	6	9	
320/65 R18	W10 W9 W11	319 12.6	873 34.4	395 16	2619 103	109D	0.8	760	780	720	690	660	1	1120	1020	
							12	1670	1720	1590	1520	1450	15	2470	2250	
							1.0	860	890	820	790	750	1.3	1280	1160	
							15	1890	1960	1810	1740	1650	18	2820	2560	
							1.2	980	1010	930	890	850	1.5	1450	1320	
							17	2160	2220	2050	1960	1870	22	3190	2910	
							1.6	1180	1220	1130	1080	1030	2	1750	1600	
							23	2600	2690	2490	2380	2270	29	3850	3520	

Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommended load, kg (lbs)								
								Speed, km/h (mph)								
		SW	OD					Non cyclic operation				Cyclic operation				
		mm/in	mm/in					mm/in	mm/in	mm/in	mm/in	bar	10	15	bar	10
						Speed	bar	Field	25	40	50	65	bar	10	15	
						Symbol	psi	operation	16	25	31	40	psi	6	9	
320/65 R16	W10 W9 W11	319 12.6	822 32.4	370 15	2466 97	117D	0.8	710	730	680	650	620	1.0	1050	960	
							12	1560	1610	1500	1430	1370	15	2310	2110	
							1.6	1130	1160	1070	1030	980	2	1670	1520	
							23	2490	2560	2360	2270	2160	29	3680	3350	
							2.0	1330	1370	1270	1220	1160	2.5	1970	1800	
							29	2930	3020	2800	2690	2560	36	4340	3960	
							2.4	1480	1520	1410	1350	1285	3	2180	1990	
							35	3260	3350	3110	2970	2830	44	4800	4380	

Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommended load, kg (lbs)								
								Speed, km/h (mph)								
		SW	OD					Non cyclic operation				Cyclic operation				
		mm/in	mm/in					mm/in	mm/in	mm/in	mm/in	bar	10	15	bar	10
						Speed	bar	Field	25	40	50	65	bar	10	15	
						Symbol	psi	operation	16	25	31	40	psi	6	9	
420/65 R20	W13 W11 W12	418 16.5	1054 41.5	473 19	3113 123	135D	0.8	1210	1240	1150	1100	1050	1.0	1790	1630	
							12	2670	2730	2530	2420	2310	15	3940	3590	
							1.6	1910	1970	1820	1740	1660	2	2820	2570	
							23	4210	4340	4010	3830	3660	29	6210	5660	
							2.0	2250	2320	2150	2060	1960	2.5	3330	3040	
							29	4960	5110	4740	4540	4320	36	7330	6700	
							2.4	2510	2580	2390	2290	2180	3	3710	3380	
							35	5530	5680	5260	5040	4800	44	8170	7440	