

# FARMAX R65

**FEATURES**

- Greater lug overlap
- More lugs in footprint

**BENEFITS**

- Improved roadability for haulage
- Safe and comfortable ride
- Less vibration on road

**FEATURES**

- Mud breaker
- Variable groove contour
- Smooth flowing step groove

**BENEFITS**

- Better self cleaning properties
- Less soil from field to road



**FEATURE**

- R1-W tread depth

**BENEFIT**

- Long service life

**FEATURES**

- Lower lug angle at shoulder
- Higher lug angle at centre

**BENEFITS**

- Better traction
- Better ride

**FEATURE**

- Rounded shoulder

**BENEFIT**

- Reduced soil disturbance


**FEATURE**

- Wider tread

**BENEFITS**

- Lower soil compaction
- Increased footprint area

## MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed kmph / mph							
				SW	OD				Non cyclic operation				Cyclic operation			
				mm	mm				Static	25	40	50	65	bar	10	15
				in	in				16	25	31	40	psi	6	9	
600/65R28	147D	TL	DW20B W18L	591 23.3	1491 58.7	668 26	4473 176	0.8	2350	2420	2230	2140	2040	1	3470	3160
								12	5180	5330	4910	4710	4490	15	7640	6960
								1	2680	2760	2550	2450	2330	1.25	3960	3610
								15	5900	6080	5620	5400	5130	18	8720	7950
								1.3	3130	3220	2980	2860	2720	1.63	4620	4220
								19	6890	7090	6560	6300	5990	24	10180	9300
								1.6	3540	3640	3370	3230	3075	2	5230	4770
								23	7800	8020	7420	7110	6770	29	11520	10510

All tires confirms ETRTO T&RA & STRO standards