

FEATURES AND BENEFITS

Stepped lug tip

Increase the grip
and reducing the
tractor slip



Lug base tie bar

Additional support to
lugs and also helps to
remove mud from lugs



Extra wide tread

Higher footprint
which gives
better stability



50° lug angle at centre

Smoother road
driving comfort, less
noise and vibration



Rounded shoulder

Provides less soil
damage & better grip



Higher NSD

Provides better
grip and high
traction



*CTR-Low Compaction, High Traction, High Roadability

FARMAX HPT

WITH THE POWER OF CTR*



FARMAX HPT

Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommended load, kg (lbs)							
		SW	OD					Speed, km/h (mph)							
		mm/in	mm/in					Mixed Application							
								Static	10	20	30	40	50	65	
Symbol	bar	psi	6	12	19	25	31	40							
480/80 R50	W14 DW15L DW16	485 19.1	2038 80.2	950 37.4	6082 239.5	159D 162A8	0.8	5290	3450	2830	2650	2520	2420	2300	
							12	11650	7600	6230	5840	5550	5330	5070	
							1.2	6720	4380	3590	3360	3200	3070	2920	
							17	14800	9650	7910	7400	7050	6760	6430	
							1.8	8510	5550	4550	4260	4050	3890	3700	
							26	18740	12220	10020	9380	8920	8570	8150	
							2	9040	5900	4830	4520	4300	4130	3930	
							29	19910	13000	10640	9960	9470	9100	8660	
							2.4	10060	6560	5380	5030	4790	4590	4375	
						35	22160	14450	11850	11080	10550	10110	9640		
						165D 168A8	0.8	5290	3450	2830	2650	2520	2420	2300	
							12	11650	7600	6230	5840	5550	5330	5070	
							1.6	7940	5180	4240	3970	3780	3620	3450	
							23	17490	11410	9340	8740	8330	7970	7600	
							2.4	10060	6560	5380	5030	4790	4590	4375	
							35	22160	14450	11850	11080	10550	10110	9640	
							2.8	10950	7140	5850	5470	5210	5000	4760	
							41	24120	15730	12890	12050	11480	11010	10480	
3.2	11850	7730	6330	5920	5640		5410	5150							
46	26100	17030	13940	13040	12420	11920	11340								

Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommended load, kg (lbs)							
		SW	OD					Speed, km/h (mph)							
		mm/in	mm/in					Mixed Application							
								Static	10	20	30	40	50	65	
Symbol	bar	psi	6	12	19	25	31	40							
480/80 R50	DW15L DW16L	485 19.1	2038 80.2	950 37.4	6082 239.5	176D 179A8	0.8	5290	3450	2830	2650	2520	2420	2300	
							12	11650	7600	6230	5840	5550	5330	5070	
							1.6	7940	5180	4240	3970	3780	3620	3450	
							23	17490	11410	9340	8740	8330	7970	7600	
							3	11410	7440	6100	5700	5430	5210	4960	
							44	25130	16390	13440	12560	11960	11480	10930	
							4	13960	9110	7470	6980	6650	6370	6070	
							58	30750	20070	16450	15370	14650	14030	13370	
							5	16330	10650	8730	8170	7770	7460	7100	
							73	35970	23460	19230	18000	17110	16430	15640	

Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommended load, kg (lbs)							
		SW	OD					Speed, km/h (mph)							
		mm/in	mm/in					mm/in	mm/in	Mixed Application					
										Speed Symbol	bar psi	Static	10 6	20 12	30 19
600/70 R30	DW18L DW20L	610 24.0	1602 63.1	726 28.6	4781 188.2	158D 161A8	0.8	5430	3540	2900	2710	2580	2480	2360	
							12	11960	7800	6390	5970	5680	5460	5200	
							1.2	6900	4500	3690	3450	3290	3150	3000	
							17	15200	9910	8130	7600	7250	6940	6610	
							1.8	8910	5810	4770	4460	4240	4070	3875	
							26	19630	12800	10510	9820	9340	8960	8540	
							2	9200	6000	4920	4600	4380	4200	4000	
							29	20260	13220	10840	10130	9650	9250	8810	
							2.4	9780	6380	5230	4890	4650	4460	4250	
							35	21540	14050	11520	10770	10240	9820	9360	

Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommended load, kg (lbs)							
		SW	OD					Speed, km/h (mph)							
		mm/in	mm/in					mm/in	mm/in	Mixed application					
										Speed Symbol	bar psi	Static	10 6	20 12	30 19
600/70 R30	DW18L DW20L	610 24.0	1602 63.1	726 28.6	4781 188.2	158D 161A8	0.8	5430	3540	2900	2710	2580	2480	2360	
							12	11960	7800	6390	5970	5680	5460	5200	
							1.2	6900	4500	3690	3450	3290	3150	3000	
							17	15200	9910	8130	7600	7250	6940	6610	
							1.8	8910	5810	4770	4460	4240	4070	3875	
							26	19630	12800	10510	9820	9340	8960	8540	
							2	9200	6000	4920	4600	4380	4200	4000	
							29	20260	13220	10840	10130	9650	9250	8810	
							2.4	9780	6380	5230	4890	4650	4460	4250	
							35	21540	14050	11520	10770	10240	9820	9360	
							3.8	12880	8400	6890	6440	6130	5880	5600	
							55.1	28370	18500	15180	14190	13500	12950	12330	

Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommended load, kg (lbs)							
		SW	OD					Speed, km/h (mph)							
		mm/in	mm/in					mm/in	mm/in	Mixed Application					
										Speed Symbol	bar psi	Static	10 6	20 12	30 19
600/70 R28	DW18L DW20L	610 24.0	1551 61.1	700 27.6	4629 182.2	157D 160A8	0.8	5290	3450	2830	2650	2520	2420	2300	
							12	11650	7600	6230	5840	5550	5330	5070	
							1.2	6670	4350	3570	3340	3180	3050	2900	
							17	14690	9580	7860	7360	7000	6720	6390	
							1.6	8170	5330	4370	4080	3890	3730	3550	
							23	18000	11740	9630	8990	8570	8220	7820	
							2	8910	5810	4770	4460	4240	4070	3875	
							29	19630	12800	10510	9820	9340	8960	8540	
							2.4	9490	6190	5070	4740	4520	4330	4125	
							35	20900	13630	11170	10440	9960	9540	9090	

Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommended load, kg (lbs)						
								Speed, km/h (mph)						
		mm/in	mm/in	mm/in	mm/in	Speed Symbol	bar psi	Static	10 6	20 12	30 19	40 25	50 31	65 40
710/75 R42	DW23B, DW21B, DW24B	725 28.5	2140 84.3	976 38.4	6387 251.5	181D 184A8	0.8	5290	3450	2830	2650	2520	2420	2300
							12	11650	7600	6230	5840	5550	5330	5070
							1.2	6670	4350	3570	3340	3180	3050	2900
							17	14690	9580	7860	7360	7000	6720	6390
							1.6	8170	5330	4370	4080	3890	3730	3550
							23	18000	11740	9630	8990	8570	8220	7820
							2.0	8910	5810	4770	4460	4240	4070	3875
							29	19630	12800	10510	9820	9340	8960	8540
							2.4	9490	6190	5070	4740	4520	4330	4125
35	20900	13630	11170	10440	9960	9540	9090							

Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommended load, kg (lbs)						
								Speed, km/h (mph)						
		mm/in	mm/in	mm/in	mm/in	Speed Symbol	bar psi	Static	10 6	20 12	30 19	40 25	50 31	65 40
710/75 R42	DW23B, DW21B, DW24B	725 28.5	2140 84.3	976 38.4	6387 251.5	175D 178A8	0.8	8630	5630	4610	4310	4110	3940	3750
							12	19010	12400	10150	9490	9050	8680	8260
							1.2	11210	7310	6000	5610	5340	5120	4875
							17	24690	16100	13220	12360	11760	11280	10740
							1.6	13800	9000	7380	6900	6570	6300	6000
							23	30400	19820	16260	15200	14470	13880	13220
							2.0	14950	9750	8000	7480	7120	6830	6500
							29	32930	21480	17620	16480	15680	15040	14320
							2.4	15870	10350	8920	7940	7560	7250	6900
35	34960	22800	19650	17490	16650	15970	15200							

Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommended load, kg (lbs)						
								Speed, km/h (mph)						
		mm/in	mm/in	mm/in	mm/in	Speed Symbol	bar psi	Static	10 6	20 12	30 19	40 25	50 31	65 40
800/70 R38	DW27B, DW25B,	820 32.3	2089 82.2	933 36.7	6110 240.5	178D/ 181A8	0.8	9490	6190	5070	4740	4520	4330	4125
							12	20900	13630	11170	10440	9960	9540	9090
							1.2	12190	7950	6520	6100	5800	5570	5300
							17	26850	17510	14360	13440	12780	12270	11670
							1.6	14950	9750	8000	7480	7120	6830	6500
							23	32930	21480	17620	16480	15680	15040	14320
							2.0	16330	10650	8730	8170	7770	7460	7100
							29	35970	23460	19230	18000	17110	16430	15640
							2.4	17250	11250	9690	8630	8210	7880	7500
35	38000	24780	21340	19010	18080	17360	16520							

Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommended load, kg (lbs)							
		SW	OD					Speed, km/h (mph)							
		mm/in	mm/in					Static	10	20	30	40	50	65	
									6	12	19	25	31	40	
710/70 R38	DW23B, DW25B	716 28.2	1960 77.2	881 34.7	5850 230.3	171D / 174A8	0.8	7710	5030	4120	3850	3670	3520	3350	
							12	16980	11080	9070	8480	8080	7750	7380	
							1	8910	5810	4770	4460	4240	4070	3875	
							15	19630	12800	10510	9820	9340	8960	8540	
							1.2	10060	6560	5380	5030	4790	4590	4375	
							17	22160	14450	11850	11080	10550	10110	9640	
							1.4	11210	7310	6000	5610	5340	5120	4875	
							20	24690	16100	13220	12360	11760	11280	10740	
							1.6	12190	7950	6520	6100	5800	5570	5300	
							23	26850	17510	14360	13440	12780	12270	11670	
							2.0	13340	8700	7130	6670	6350	6090	5800	
							29	29380	19160	15700	14690	13990	13410	12780	
							2.4	14150	9230	7950	7070	6730	6460	6150	
35	31170	20330	17510	15570	14820	14230	13550								

Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommended load, kg (lbs)							
		SW	OD					Speed, km/h (mph)							
		mm/in	mm/in					Static	10	20	30	40	50	65	
									6	12	19	25	31	40	
710/70 R42	DW23B, DW25B,	716 28.2	2061 81.1	932 36.7	6151 242.2	173D/ 176A8	0.8	8170	5330	4370	4080	3890	3730	3550	
							12	18000	11740	9630	8990	8570	8220	7820	
							1.2	10350	6750	5540	5180	4930	4730	4500	
							17	22800	14870	12200	11410	10860	10420	9910	
							1.6	12880	8400	6890	6440	6130	5880	5600	
							23	28370	18500	15180	14190	13500	12950	12330	
							2.0	14150	9230	7560	7070	6730	6460	6150	
							29	31170	20330	16650	15570	14820	14230	13550	
							2.4	14950	9750	8400	7480	7120	6830	6500	
							35	32930	21480	18500	16480	15680	15040	14320	

Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommended load, kg (lbs)							
		SW	OD					Speed, km/h (mph)							
		mm/in	mm/in					Static	10	20	30	40	50	65	
									6	12	19	25	31	40	
650/75 R38	DW21B, DW20B, DW23B,	645 25.4	1941 76.4	873 34.4	5793 228.1	169D/ 172A8	0.8	7250	4730	3870	3620	3450	3310	3150	
							12	15970	10420	8520	7970	7600	7290	6940	
							1.2	9200	6000	4920	4600	4380	4200	4000	
							17	20260	13220	10840	10130	9650	9250	8810	
							1.6	11210	7310	6000	5610	5340	5120	4875	
							23	24690	16100	13220	12360	11760	11280	10740	
							2.0	12540	8180	6700	6270	5970	5720	5450	
							29	27620	18020	14760	13810	13150	12600	12000	
							2.4	13340	8700	7490	6670	6350	6090	5800	
							35	29380	19160	16500	14690	13990	13410	12780	

Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommended load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
		mm/in	mm/in					mm/in	mm/in	Speed	bar	Static	10	20
				Symbol	psi		6	12	19	25	31	40		
710/70 R38	DW23B, DW25B	716 28.2	1960 77.2	881 34.7	5850 230.3	178D/ 181A8	0.8	7710	5030	4120	3850	3670	3520	3350
							12	16980	11080	9070	8480	8080	7750	7380
							1	8910	5810	4770	4460	4240	4070	3875
							15	19630	12800	10510	9820	9340	8960	8540
							1.2	10060	6560	5380	5030	4790	4590	4375
							17	22160	14450	11850	11080	10550	10110	9640
							1.4	11210	7310	6000	5610	5340	5120	4875
							20	24690	16100	13220	12360	11760	11280	10740
							1.6	12190	7950	6520	6100	5800	5570	5300
							23	26850	17510	14360	13440	12780	12270	11670
							2.0	13340	8700	7130	6670	6350	6090	5800
							29	29380	19160	15700	14690	13990	13410	12780
							2.4	14150	9230	7950	7070	6730	6460	6150
							35	31170	20330	17510	15570	14820	14230	13550
3.4	17250	11250	9230	8630	8210	7880	7500							
49	38000	24780	20330	19010	18080	17360	16520							

Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommended load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
		mm/in	mm/in					mm/in	mm/in	Speed	bar	Static	10	20
				Symbol	psi		6	12	19	25	31	40		
710/70 R42	DW23B, DW25B	716 28.2	2061 81.1	932 36.7	6151 242.2	176D/ 179A8	0.8	8170	5330	4370	4080	3890	3730	3550
							12	18000	11740	9630	8990	8570	8220	7820
							1.2	10350	6750	5540	5180	4930	4730	4500
							17	22800	14870	12200	11410	10860	10420	9910
							1.6	12880	8400	6890	6440	6130	5880	5600
							23	28370	18500	15180	14190	13500	12950	12330
							2.0	14150	9230	7560	7070	6730	6460	6150
							29	31170	20330	16650	15570	14820	14230	13550
							2.4	14950	9750	8400	7480	7120	6830	6500
							35	32930	21480	18500	16480	15680	15040	14320
							2.8	16330	10650	8730	8170	7770	7460	7100
							41	35970	23460	19230	18000	17110	16430	15640

Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommended load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
		mm/in	mm/in					mm/in	mm/in	Speed	bar	Static	10	20
				Symbol	psi		6	12	19	25	31	40		
600/70 R30	DW18L DW20L	610 24.0	1602 63.1	726 28.6	4781 188.2	168D 171A8	0.8	5430	3540	2900	2710	2580	2480	2360
							12	11960	7800	6390	5970	5680	5460	5200
							1.2	6900	4500	3690	3450	3290	3150	3000
							17	15200	9910	8130	7600	7250	6940	6610
							1.8	8910	5810	4770	4460	4240	4070	3875
							26	19630	12800	10510	9820	9340	8960	8540
							2	9200	6000	4920	4600	4380	4200	4000
							29	20260	13220	10840	10130	9650	9250	8810
							2.4	9780	6380	5230	4890	4650	4460	4250
							35	21540	14050	11520	10770	10240	9820	9360
							3.8	12880	8400	6890	6440	6130	5880	5600
							55	28370	18500	15180	14190	13500	12950	12330

Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommended load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
		mm/in	mm/in	mm/in	mm/in	Speed Symbol	bar psi	Static	10 6	20 12	30 19	40 25	50 31	65 40
650/85 R38	DW23B, DW21B, DW20B	675 26.6	2071 81.5	947 37	6181 243	170D/ 173A8	0.8	4080	5330	4370	4080	3890	3730	3550
							12	8990	11740	9630	8990	8570	8220	7820
							1.2	5180	6750	5540	5180	4930	4730	4500
							17	11410	14870	12200	11410	10860	10420	9910
							1.6	6270	8180	6700	6270	5970	5720	5450
							23	13810	18020	14760	13810	13150	12600	12000
							1.8	6670	8700	7130	6670	6350	6090	5800
							26	14690	19160	15700	14690	13990	13410	12780
							2.1	6900	9000	7750	6900	6570	6300	6000
						30	15200	19820	17070	15200	14470	13880	13220	
						173D/ 176A8	0.8	4080	5330	4370	4080	3890	3730	3550
							12	8990	11740	9630	8990	8570	8220	7820
							1.0	4600	6000	4920	4600	4380	4200	4000
							15	10130	13220	10840	10130	9650	9250	8810
							1.4	5750	7500	6150	5750	5480	5250	5000
							20	12670	16520	13550	12670	12070	11560	11010
							1.6	6270	8180	6700	6270	5970	5720	5450
							23	13810	18020	14760	13810	13150	12600	12000
2.4	7480	9750	8400	7480	7120		6830	6500						
35	16480	21480	18500	16480	15680	15040	14320							

Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommended load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
		mm/in	mm/in	mm/in	mm/in	Speed	bar	Tractor Application						
						Symbol		psi	Static	10 6	20 12	30 19	40 25	50 31
600/70 R34	DW18L DW20L	610 24.0	1702 67.0	767 30.2	5110 201.2	160D 163A8	0.8	5750	3750	3080	2880	2740	2630	2500
							12	12670	8260	6780	6340	6040	5790	5510
							1.2	7250	4730	3870	3620	3450	3310	3150
							17	15970	10420	8520	7970	7600	7290	6940
							1.8	9490	6190	5070	4740	4520	4330	4125
							26	20900	13630	11170	10440	9960	9540	9090
							2	9780	6380	5230	4890	4650	4460	4250
							29	21540	14050	11520	10770	10240	9820	9360
							2.2	10060	6560	5380	5030	4790	4590	4375
							32	22160	14450	11850	11080	10550	10110	9640
							2.4	10350	6750	5540	5180	4930	4730	4500
							35	22800	14870	12200	11410	10860	10420	9910

Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommended load, kg (lbs)						
								Speed, km/h (mph)						
								Tractor Application						
		SW	OD					Static	10	20	30	40	50	65
mm/in	mm/in	mm/in	mm/in	mm/in	mm/in	mm/in	mm/in		mm/in					
				bar	psi	6	12	19	25	31	40			
						Symbol								
650/65 R34	DW20B, DW21B, DW23B	645 25.4	1710 67.3	779 30.7	5104 200.9	161D 164A8	0.8	5920	3860	3170	2960	2820	2700	2575
							12	13040	8500	6980	6520	6210	5950	5670
							1.2	7480	4880	4000	3740	3560	3410	3250
							17	16480	10750	8810	8240	7840	7510	7160
							1.8	9490	6190	5070	4740	4520	4330	4125
							26	20900	13630	11170	10440	9960	9540	9090
							2	10060	6560	5380	5030	4790	4590	4375
							29	22160	14450	11850	11080	10550	10110	9640
							2.2	10350	6750	5540	5180	4930	4730	4500
							32	22800	14870	12200	11410	10860	10420	9910
							2.4	10640	6940	5690	5320	5060	4860	4625
							35	23440	15290	12530	11720	11150	10700	10190

Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommended load, kg (lbs)						
								Speed, km/h (mph)						
								Tractor Application						
		SW	OD					Static	10	20	30	40	50	65
mm/in	mm/in	mm/in	mm/in	mm/in	mm/in	mm/in	mm/in							
				bar	psi	6	12	19	25	31	40			
						Symbol								
600/65 R28	DW20B, W18L	615 24.2	1500 59.1	679 26.7	4477 176.3	154D 157A8	0.8	4740	3090	2530	2370	2260	2160	2060
							12	10440	6810	5570	5220	4980	4760	4540
							1.2	6100	3980	3260	3050	2900	2780	2650
							17	13440	8770	7180	6720	6390	6120	5840
							1.8	7710	5030	4120	3850	3670	3520	3350
							26	16980	11080	9070	8480	8080	7750	7380
							2	8170	5330	4370	4080	3890	3730	3550
							29	18000	11740	9630	8990	8570	8220	7820
							2.2	8400	5480	4490	4200	4000	3830	3650
							32	18500	12070	9890	9250	8810	8440	8040
							2.4	8630	5630	4610	4310	4110	3940	3750
							35	19010	12400	10150	9490	9050	8680	8260