

FEATURES AND BENEFITS

Triple angle lug

Enhanced traction
& roadability



High centre lug
overlap & tie bar

Improved stability



Reinforced carcass
Longer service life



FARMAX R1

TRA CODE : R-1



FARMAX R1

Size	Rim	Type	Infl tire dimension		Static Loaded radius	Rolling circm.	Load Index	Infl. press.	Recommended load, kg (lbs)	
			SW	OD					Speed, km/h (mph)	
			mm/in	mm/in	mm/in	mm/in	Speed	bar	30	40
							Symbol	psi	19	25
20.8-38	W18	TL	535	1840	830	5610	14 PR TL 159A6/155A8	2.2	4375	3875
			99.1	340.7	153.7	1038.9			32	9640
20.8-38	W18	TT	535	1840	830	5610	10 PR 152A6/148A8	1.5	3550	3150
			99.1	340.7	153.7	1038.9			22	7820

Size	PR	Type	Rim Width in	SW	OD	Static Loaded Radius	Rolling Circum	Infl. Prs.	Load , Speed Symbol	Max Speed	Max Load
				mm/in	mm/in					mm/in	mm/in
								psi		mph	lbs
18.4-38	8	TT / TL	W16L	465	1750	819	5250	1.4	143	40	2725
		TT							20	A8	25
	12	TT	18	69	32	207	2.3	152	40	3550	
16.9-38	8	TT	W15L	429	1685	789	5055	1.7	141	40	2575
		TT							25	A8	25
	10	TT	17	66	31	199	2.0	143	40	2725	
							29	A8	25	6010	
							2.3	146	40	3000	
12	TT / TL	34	A8	25	6615						
						1.8	133	40	2060		
15.5-38	8	TT / TL	W14	400	1577	738	4731	26	A8	25	4540
		TT							2.3	137	40
	10	TT	16	62	29	186	3.3	A8	25	5070	
							2.8	141	40	2575	
							4.1	A8	25	5675	
13.6-38	8	TT / TL	W12	350	1585	742	4755	2	131	40	1950
				14	62	29	187	29	A8	25	4300

Size	Rim Width in	SW	OD	Static Loaded Radius	Rolling Circum	PR	Infl. Prs.	Load , Speed Symbol	Max Speed
		mm/in	mm/in						mm/in
									psi
13.6-38	W12	350	1585	742	4755	14	3.5	139	40
		14	62	29	187			51	A8

Size	Rim	Infl tire dimension		Static Loaded radius	Rolling circm.	Load Index	Infl. press.	Recommended load, kg (lbs) Speed, km/h (mph)	
		SW	OD					Speed	bar
		mm/in	mm/in	mm/in	mm/in	Symbol	psi		
12.4-38	W11X38	323	1514	708	4540	8 PR TT 124A8	2.2	1600	
		12.7	59.6	27.9	178.7		32	3530	

SIZE	PR	Type	Rim Width in	SW	OD	Static Loaded Radius	Rolling Circum	Infl. Prs.	Load , Speed Symbol	Max Speed	Max Load
				mm/in	mm/in					mm/in	mm/in
				mm/in	mm/in	mm/in	mm/in	psi		mph	lbs
12.4-38	14 PR TT	TT	W11X38	323	1514	708	4540	3.9	135A8	40	2180
				12.7	59.6	27.9	178.7	57		25	4800
13.6-36	8	TT / TL	W12	350	1535	718	4605	2	129	40	1855
				14	60	28	181	29	A8	25	4090

Size	LI/SS	PR	Rim	Unloaded Dimension		SLR	RC	Load Carrying Capacity		
				SW	OD			Infl. Pre	Max. Speed	Max Load
				mm/in	mm/in	mm/in	mm/in	bar	Kmph	kg
12.4-36	126 A8	8	W11x36	325	1465	694	4545	2.4	40	1700
				12.8	57.6	27.3	178.9	35	25	3750

SIZE	PR	Type	Rim Width in	SW	OD	Static Loaded Radius	Rolling Circum	Infl. Prs.	Load , Speed Symbol	Max Speed	Max Load
				mm/in	mm/in					mm/in	mm/in
				mm/in	mm/in	mm/in	mm/in	psi		mph	lbs
12.4-36	TT / TL	135 A8	12	W11	325	1465	694	4545	3.5	40	2180
					12.8	57.6	27.3	178.9	51	25	4800
18.4-34	8	TT	W16L	465	1650	772	4950	1.4	142	40	2650
								20	A8	25	5840
	14	TT / TL		18	65	30	195	2.6	153	40	3650
								38	A8	25	8048
	12	TT		18	65	30	195	2.3	150	40	3450
								33	A8	25	7605
10	TT	465	1650	772	4950	1.8	146	40	3000		
						26	A8	25	6615		

Size	TYPE	LI/SS	PR	Rim	Unloaded Dimension		SLR	RC	Load Carrying Capacity		
					SW	OD			Infl. Pre	Max. Speed	Max Load
					mm/in	mm/in	mm/in	mm/in	bar	kmph	kg
16.9-34	TT / TL	139 A8	8	W15L	435	1585	742	4755	1.7	40	2430
					17.1	62.4	29.2	187.2	25	25	5358
16.9-34	TT	149 A8	14	W15L	435	1585	742	4755	2.8	40	3250
					17.1	62.4	29.2	187.2	41	25	7165
16.9-34	TT	142 A8	10	W15L	435	1585	742	4755	2	40	2650
					17.1	62.4	29.2	187.2	29	25	5840
12.4-32	TT	121A8	8	W11	323	1360	634	4040	2.3	40	1450
					12.7	53.5	25	159.1	33	25	3200
23.1-30	TL	151A8	12 PR TL	DW20B	587	1707	750	5120	1.7	40	3450
					23.1	67.2	29.5	201.6	25	25	7600

SIZE	PR	Type	Rim Width in	SW	OD	Static Loaded Radius	Rolling Circum	Infl. Prs.	Load, Speed Symbol	Max Speed	Max Load
				mm/in	mm/in	mm/in	mm/in	bar		kmph	kg
								psi		mph	lbs
18.4-30	8	TT / TL	W16L	465	1564	732	4692	1.4	139	40	2430
				18	62	29	185	20		A8	25
18.4-30	14	TT	W16L	465	1564	732	4692	2.6	151	40	3450
				18	62	29	185	38		A8	25
18.4-30	12	TT	W16L	465	1564	732	4692	2.3	149	40	3250
				18	62	29	185	33		A8	25
16.9-30	8	TT	W15L	440	1495	700	4485	1.7	137	40	2300
				17	59	28	177	25		A8	25
16.9-30	6	TT	W15L	440	1495	700	4485	1.2	126	40	1700
				17	59	28	177	17		A8	25
16.9-30	12	TT / TL	W15L	440	1495	700	4485	2.5	144	40	2800
				17	59	28	177	36		A8	25
16.9-30	10	TT	W15L	440	1495	700	4485	2	140	40	2455
				17	59	28	177	29		A8	25

Size	Rim	Type	Infl tire dimension		Static Loaded radius	Rolling circum.	Load Index	Infl. press.	Recommended load, kg (lbs)	
			SW	OD					Speed, km/h (mph)	
			mm/in	mm/in					30	40
14.9-30	W13	TT	378	1415	602	4200	8PR TT 132A8	1.8	2220	2000
			14.9	55.7	23.7	165.4		26	4890	4410

Size	PR	Type	Rim Width in	SW	OD	Static Loaded Radius	Rolling Circum	Infl. Prs.	Load , Speed Symbol	Max Speed	Max Load
				mm/in	mm/in	mm/in	mm/in	bar		kmph	kg
								psi		mph	lbs
16.9-28	8	TT	W15L	429	1435	672	4305	2.1	135	40	2180
				17	57	26	170	30		A8	25
16.9-28	12	TT / TL	W15L	429	1435	672	4305	2.4	143	40	2725
				17	57	26	170	35		A8	25
14.9-28	8	TT	W13	386	1375	644	4125	1.8	130	40	2070
				15	54	25	162	26		A8	25
14.9-28	12	TT / TL	W13	386	1375	644	4125	2.6	138	40	2360
				15	54	25	162	38		A8	25

Size	Rim inches	Outer Diameter	Section Width	Static Loaded radius	Rolling Circum - ference	PR	Inflation Pressure	Load Index / Speed Symbol	Speed kmph/ mph	Load capacity
		mm/in	mm/in	mm/in	mm/in		bar			(kg)
							psi			(lbs)
14.9-28	W13	386	1375	644	4125	10	2.3	134	40	2360
		15	54	25	162		33			A8

Size	PR	Type	Rim Width in	SW	OD	Static Loaded Radius	Rolling Circum	Infl. Prs.	Load , Speed Symbol	Max Speed	Max Load
				mm/in	mm/in	mm/in	mm/in	bar		kmph	kg
								psi		mph	lbs
13.6-28	8	TT	W12	343	1310	613	3930	2	125	40	1650
				14	52	24	155	29	A8	25	3638
13.6-28	12	TT / TL	W12	343	1310	613	3930	3	134	40	2120
				14	52	24	155	44	A8	25	4675
12.4-28	8	TT / TL	W11	323	1258	589	3774	2.4	123	40	1550
				13	50	23	149	35	A8	25	3415
12.4-28	4	TL	W11	323	1258	589	3774	1.1	104	40	900
				13	50	23	149	16	A8	25	1980
11.2-28	8	TT / TL	W10	295	1205	564	3615	2.5	118	40	1320
				12	47	22	142	36	A8	25	2910
11.2-28	10	TL	W10	295	1205	564	3615	3.0	122	40	1500
				12	47	22	142	44	A8	25	3305
23.1-26	16	TL	DW 20	587	1585	742	4755	2.3	159	40	4375
				23	62	29	187	33	A8	25	9645
18.4-26	12	TT / TL	W16L	492	1480	693	4440	2.3	146	40	3000
				19	58	27	175	33	A8	25	6615

Size	TYPE	LI/SS	PR	Rim	Unloaded Dimension		SLR	RC	Load Carrying Capacity					
					SW	OD			Infl. Pre	Max. Speed	Max Load			
					mm/in	mm/in						bar	kmph	kg
												psi	mph	lbs
16.9-26	TT	130A8	8	W15L	429	1384	627	4150	1.7	40	1900			
					16.9	54.5	24.7	163.4	25	25	4190			
14.9-26	TL	125A8	8	W13	385	1310	613	3890	1.8	40	1650			
					15.2	51.6	24.1	153.1	26	25	3640			
14.9-26	TL	132A8	12	W13	385	1310	613	3890	2.7	40	2000			
					15.2	51.6	24.1	153.1	39	25	4410			

SIZE	PR	Type	Rim Width in	SW	OD	Static Loaded Radius	Rolling Circum	Infl. Prs.	Load , Speed Symbol	Max Speed	Max Load
				mm/in	mm/in	mm/in	mm/in	bar		kmph	kg
								psi		mph	lbs
9.5-24	8	TT / TL	W8	241	1050	491	3150	2.8	112	40	1120
				10	41	19	124	41	A8	25	2470
8.3-24	8	TT / TL	W7	209	994	465	2982	3.1	105	40	925
				8	39	18	117	45	A8	25	2040
16.9-24	8	TT / TL	W15L	426	1330	622	3990	1.7	133	40	2040
				17	52	25	157	25	A8	25	4498
14.9-24	8	TT	W13	402	1275	597	3825	1.8	128	40	1800
				16	50	24	151	26	A8	25	3970
14.9-24	12	TT	W13	402	1275	597	3825	2.6	136	40	2240
				16	50	24	151	37.7	A8	25	4939
14.9-24	10	TT	W13	402	1275	597	3825	2.2	132	40	2000
				15.8	50.2	23.5	150.6	32	A8	25	4410
13.6-24	8	TT / TL	W12	345	1210	560	3555	1.9	122	40	1500
				14	48	22	140	28	A8	25	3300

SIZE	PR	Type	Rim Width in	SW	OD	Static Loaded Radius	Rolling Circum	Infl. Prs.	Load , Speed Symbol	Max Speed	Max Load
				mm/in	mm/in	mm/in	mm/in	bar		kmph	kg
								psi		mph	lbs
12.4-24	8	TT / TL	W11	307	1159	542	3477	2.3	121	40	1415
				12	46	21	137	33	A8	25	3120
12.4-24	12	TT	W11	307	1159	542	3477	3.5	129	40	1850
				12	46	21	137	51	A8	25	4079
12.4-24	10	TT	W11	307	1159	542	3477	3	125	40	1650
				12	46	21	137	44	A8	25	3638
11.2-24	8	TT / TL	W10	282	1103	516	3309	2.4	116	40	1250
				11	43	20	130	35	A8	25	2755
11.2-24	10	TT	W10	285	1103	516	3309	3.0	120	40	1400
				11.2	43.4	20.3	130.9	44	A8	25	3086

Size	TYPE	LI/SS	PR	Rim	Unloaded Dimension		SLR	RC	Load Carrying Capacity					
					SW	OD			Infl. Pre	Max. Speed	Max Load			
					mm/in	mm/in						bar	kmph	kg
												psi	mph	lbs
9.5-22	TT	106 A8	8	W8	240	995	465	3010	2.7	40	950			
					9.5	39.2	18.3	118.5	39	25	2095			

Size	Rim	Type	Infl tire dimension		Static Loaded radius	Rolling circm.	Load Index	Infl. press.	Recommended load, kg (lbs)					
			SW	OD					Speed, km/h (mph)					
			mm/in	mm/in					mm/in	mm/in	Speed	bar	30	40
											Symbol	psi	19	25
9.5-20	W8	TT	241	945	434	2810	8PR TT	2.8	1080	975				
			9.5	37.2	17.1	110.6	107A8	41	2380	2150				

Size	Rim	Infl tire dimension		Static Loaded radius	Rolling circm.	Load Index	Infl. press.	Recommended load, kg (lbs)					
		SW	OD					Speed, km/h (mph)					
		mm/in	mm/in					mm/in	mm/in	Speed	bar	40	
										Symbol	psi	25	
250/80-18	W9X18	240	870	444	2610	8PR	3.9	1215					
		9.4	34.3	17.5	102.8		57	2680					

Size	Rim	Type	Infl tire dimension		Static Loaded radius	Rolling circm.	Load Index	Infl. press.	Recommended load, kg (lbs)					
			SW	OD					Speed, km/h (mph)					
			mm/in	mm/in					mm/in	mm/in	Speed	bar	30	40
											Symbol	psi	19	25
9.5-16	W8	TL	241	852	380	2530	8PR TL	2.8	890	800				
			9.5	33.5	15.0	99.6	100A8	41	1960	1760				
9.5-16	W8	TL	241	852	380	2530	12PR TL	3.4	1050	950				
			9.5	33.5	15.0	99.6	106A8	49	2310	2090				
8-16	W6	TT	211	775	349	2300	8PR TL	2.6	750	670				
			8.3	30.5	13.7	90.6	94A8	38	1650	1480				

Size	Type	LI/SS	PR	Rim	Unloaded Dimension		SLR	RC	Load Carrying Capacity		
					SW	OD			Infl. Pre	Max. Speed	Max Load
					mm/in	mm/in	bar	kmph	kg		
							psi	mph	lbs		
8.25-16	TT	94 A8	6	6.00F	225	820	372	2452	2	40	670
					8.8	32.3	14.6	96.5	29	25	1475

Size	LI/SS	PR	Rim	Unloaded Dimension		SLR	RC	Load Carrying Capacity		
				SW	OD			Infl. Pre	Max. Speed	Max Load
				mm/in	mm/in	bar	Kmph	kg		
						psi	mph	lbs		
7.50-16	99A8	8	5.50Fx16	215	805	372	2400	3.2	40	775
				8.5	31.7	14.6	94.5	46	25	1709

Size	TYPE	LI/SS	PR	Rim	Unloaded Dimension		SLR	RC	Load Carrying Capacity		
					SW	OD			Infl. Pre	Max. Speed	Max Load
					mm/in	mm/in	bar	kmph	kg		
							psi	mph	lbs		
7.50-16	TT	88 A8	6	5.50F	215	805	372	2400	2.2	40	570
					8.5	31.7	14.6	94.5	40	25	1255
6.50-16	TT	83 A8	6	5.50F	190	755	345	2248	2.7	40	490
					7.4	29.7	13.6	88.5	39	25	1080

Size	Rim	Type	Infl tire dimension		Static Loaded radius	Rolling circm.	Load Index	Infl. press.	Recommended load, kg (lbs)	
			SW	OD					Speed, km/h (mph)	
			mm/in	mm/in	mm/in	mm/in	Speed	bar	30	40
							Symbol	psi	19	25
12.4-16	10LB	TT	320	970	426	2880	6PR TL 101A8	1.65	920	825
			12.6	38.2	16.8	113.4		24	2030	1820
7-12	5JA	TL	183	620	288	1840	10PR TL 87A6	4	545	490
			7.2	24.4	11.3	72.4		58	1200	1080

Size	Rim	Infl tire dimension		Static Loaded radius	Rolling circm.	Load Index	Infl. press.	Recommended load, kg (lbs)	
		SW	OD					Speed, km/h (mph)	
		mm/in	mm/in	mm/in	mm/in	Speed	bar	40	
						Symbol	psi	25	
7-12	5JA X 12	183	620	288	1840	10PR TL 87A6	4	490	
		7.2	24.4	11.3	72.4		58	1080	