

FEATURES AND BENEFITS

Stepped lug design
Better grip



Stronger &
wider lugs
Longer life

Tilted lug tip
Lower vibration at
high speed



Lower lug angle at
the shoulder
Better traction

Wider tread width
Lower compaction



Rounded shoulder
Less crop damage



*CTR-Low Compaction, High Traction, High Roadability

TORQUEMAX

WITH THE POWER OF CTR*



TORQUEMAX VF

Size	Rim	Unloaded dimension		Static Loaded Radius	Rolling Circum	Speed Radius Index (SRI)	Load Index	Infl. press.	Maximum load, kg (lbs)							
		Speed, km/h (mph)								*Cyclic						
		Mixed Application							*Cyclic							
		SW	OD								10	20	30	40 to 65km/H	70	bar
mm/in	mm/in	mm/in	mm/in	mm/in	mm/in	mm/in	mm/in	psi	6	12	19	25 to 40mph	43	psi	6.2	
VF 750/ 75R46	DW25B	750 29.5	2294 90.3	1001 39.4	6774 266.7	1075	189D	0.8	6560	6200	6080	5960	5420	1.6	8340	
								12	14450	13660	13390	13130	11940	23	18370	
								1.2	8440	7980	7820	7670	6980	2	10740	
								17	18590	17580	17220	16890	15370	29	23660	
								1.6	10310	9740	9560	9370	8530	2.4	13120	
								23	22710	21450	21060	20640	18790	35	28900	
								2	11330	10710	10510	10300	9370	2.8	14420	
								29	24960	23590	23150	22690	20640	41	31760	

Size	Rim	Unloaded dimension		Static Loaded Radius	Rolling Circum	Speed Radius Index (SRI)	Load Index	Infl. press.	Maximum load, kg (lbs)							
		Speed, km/h (mph)								*Cyclic						
		Mixed Application							*Cyclic							
		SW	OD								10	20	30	40 to 65km/H	70	bar
mm/in	mm/in	mm/in	mm/in	mm/in	mm/in	mm/in	mm/in	psi	6	12	19	25 to 40mph	43	psi	6	
VF710/ 75R42	DW25B, DW23B, DW24B	715 28.1	2133 84.0	929 36.6	6265 246.7	1000	184D	0.6	4960	4690	4600	4510	4100	1.4	6310	
								9	10930	10330	10130	9930	9030	20	13900	
								1.2	7440	7030	6900	6760	6150	2	9460	
								17	16390	15480	15200	14890	13550	29	20840	
								1.5	8680	8210	8050	7890	7180	2.3	11050	
								22	19120	18080	17730	17380	15810	33	24340	
								1.8	9570	9050	8870	8700	7920	2.6	12180	
								26	21080	19930	19540	19160	17440	38	26830	
								2	9900	9360	9180	9000	8190	2.8	12600	
								29	21810	20620	20220	19820	18040	41	27750	

Size	Rim	Unloaded dimension		Static Loaded Radius	Rolling Circum	Speed Radius Index (SRI)	Load Index	Infl. press.	Maximum load, kg (lbs)							
		SW	OD						Speed, km/h (mph)						*Cyclic	
		mm	mm	mm	mm		Speed	bar	10	20	30	40 to 65km/H	70	bar	10	
		in	in	in	in		Symbol	psi	6	12	19	25 to 40mph	43	psi	6	
VF710/ 70R42	DW23B, DW25B	720 28.3	2061 81.1	902 35.5	6119 240.9	975.0	185D	0.8	5450	5150	5050	4950	4500	1.6	6930	
								12	12000	11340	11120	10900	9910	23	15260	
								1.2	7000	6610	6490	6360	5790	2	8900	
								17	15420	14560	14300	14010	12750	29	19600	
								1.6	8560	8090	7940	7780	7080	2.4	10890	
								23	18850	17820	17490	17140	15590	35	23990	
								2	9380	8870	8700	8530	7760	2.8	11940	
								29	20660	19540	19160	18790	17090	41	26300	
								2.4	10180	9620	9440	9250	8420	3.2	12950	
								35	22420	21190	20790	20370	18550	46	28520	

Size	Rim	Unloaded dimension		Static Loaded Radius	Rolling Circum	Speed Radius Index (SRI)	Load Index	Infl. press.	Maximum load, kg (lbs)							
		SW	OD						Speed, km/h (mph)						*Cyclic	
		mm	mm	mm	mm		Speed	bar	10	20	30	40 to 65km/H	70	bar	10	
		in	in	in	in		Symbol	psi	6	12	19	25 to 40mph	43	psi	6	
VF520/ 85R42	DW18L DW16L	536 21.1	1955 77.0	876 34.5	5804 228.5	925	174D	0.8	3990	3780	3700	3630	3300	1.6	5080	
								12	8790	8330	8150	8000	7270	23	11190	
								1.2	5140	4860	4760	4670	4250	2	6540	
								17	11320	10700	10480	10290	9360	29	14410	
								1.6	6270	5930	5810	5700	5190	2.4	7980	
								23	13810	13060	12800	12560	11430	35	17580	
								1.8	6600	6240	6120	6000	5460	2.6	8400	
								26	14540	13740	13480	13220	12030	38	18500	
								2.8	7370	6970	6830	6700	6100	3.6	9380	
								41	16230	15350	15040	14760	13440	52	20660	

Size	Rim	Unloaded dimension		Static Loaded Radius	Rolling Circum	Speed Radius Index (SRI)	Load Index	Infl. press.	Maximum load, kg (lbs)							
		SW	OD						Speed, km/h (mph)						*Cyclic	
		mm	mm	mm	mm		Speed	bar	10	20	30	40 to 65km/H	70	bar	10	
		in	in	in	in		Symbol	psi	6	12	19	25 to 40mph	43	psi	6	
VF 900/ 60R38	DW30B	891 35.1	2040 80.3	881 34.7	6024 237.2	900	193D	0.6	5310	5020	4930	4830	4400	1.4	6760	
								9	11700	11060	10860	10640	9690	20	14890	
								1.2	7960	7530	7380	7240	6590	2	10140	
								17	17530	16590	16260	15950	14520	29	22330	
								1.6	9740	9200	9030	8850	8050	2.4	12390	
								23	21450	20260	19890	19490	17730	35	27290	
								2.4	11670	11030	10820	10605	9650	3.2	14850	
								35	25700	24300	23830	23360	21260	46	32710	
								2.8	12650	11960	11730	11500	10470	3.6	16100	
								41	27860	26340	25840	25330	23060	52	35460	

Size	Rim	Unloaded dimension		Static Loaded Radius	Rolling Circum	Speed Radius Index (SRI)	Load Index	Infl. press.	Maximum load, kg (lbs)							
		SW	OD						Speed, km/h (mph)						*Cyclic	
		mm	mm	mm	mm		Speed	bar	10	20	30	40 to 65km/H	70	bar	10	
		in	in				in	in	Symbol	psi	6	12	19	25 to 40mph	43	psi
VF800/ 70R38	DW27B, DW28B, DW30B	810 28.3	2085 77.1	898 33.5	6124 228.3	975	187D	0.8	6280	5940	5820	5710	5200	1.6	7990	
								12	13830	13080	12820	12580	11450	23	17600	
								1.2	8070	7630	7490	7340	6680	2	10280	
								17	17780	16810	16500	16170	14710	29	22640	
								1.6	9870	9330	9150	8970	8160	2.4	12560	
								23	21740	20550	20150	19760	17970	35	27670	
								1.8	10380	9820	9630	9440	8590	2.6	13220	
								26	22860	21630	21210	20790	18920	38	29120	
								2.4	10730	10140	9950	9750	8870	3.2	13650	
								35	23630	22330	21920	21480	19540	46	30070	

Size	Rim	Unloaded dimension		Static Loaded Radius	Rolling Circum	Speed Radius Index (SRI)	Load Index	Infl. press.	Maximum load, kg (lbs)							
		SW	OD						Speed, km/h (mph)						*Cyclic	
		mm	mm	mm	mm		Speed	bar	10	20	30	40 to 65km/H	70	bar	10	
		in	in				in	in	Symbol	psi	6	12	19	25 to 40mph	43	psi
VF710/ 70R38	DW23B, DW25B	720 28.3	1959 77.1	841 33.5	5970 228.3	925	178D	0.8	5200	4920	4820	4730	4300	1.6	6620	
								12	11450	10840	10620	10420	9470	23	14580	
								1	5950	5630	5520	5410	4920	1.8	7570	
								15	13110	12400	12160	11920	10840	26	16670	
								1.2	6690	6320	6200	6080	5530	2	8510	
								17	14740	13920	13660	13390	12180	29	18740	
								1.4	7440	7030	6900	6760	6150	2.2	9460	
								20	16390	15480	15200	14890	13550	32	20840	
								1.6	8250	7800	7650	7500	6830	2.4	10500	
								23	18170	17180	16850	16520	15040	35	23130	

Size	Rim	Unloaded dimension		Static Loaded Radius	Rolling Circum	Speed Radius Index (SRI)	Load Index	Infl. press.	Maximum load, kg (lbs)							
		SW	OD						Speed, km/h (mph)						*Cyclic	
		mm	mm	mm	mm		Speed	bar	10	20	30	40 to 65km/H	70	bar	10	
		in	in				in	in	Symbol	psi	6	12	19	25 to 40mph	43	psi
VF710/60R 38 NRO	DW24B, DW25B, DW27B DW23B (nro)	710 28.0	1820 71.7	799 31.5	5375 211.6	850	171D	0.8	4280	4050	3970	3890	3540	1.6	5450	
								12	9430	8920	8740	8570	7800	23	12000	
								1	4900	4630	4540	4450	4050	1.8	6230	
								15	10790	10200	10000	9800	8920	26	13720	
								1.2	5510	5210	5110	5010	4560	2	7010	
								17	12140	11480	11260	11040	10040	29	15440	
								1.4	6120	5780	5670	5560	5060	2.2	7780	
								20	13480	12730	12490	12250	11150	32	17140	
								1.6	6770	6400	6270	6150	5600	2.4	8610	
								23	14910	14100	13810	13550	12330	35	18960	

Size	Rim	Unloaded dimension		Static Loaded Radius	Rolling Circum	Speed Radius Index (SRI)	Load Index	Infl. press.	Maximum load, kg (lbs)							
		SW	OD						Speed, km/h (mph)						*Cyclic	
		mm	mm	mm	mm		10	20	30	40 to 65km/H	70	bar	10			
		in	in	in	in		6	12	19	25 to 40mph	43	psi	6			
VF520/ 85R38	DW18L, DW16L	536 21.1	1849 72.8	823 32.4	5344 210.4	875.0	170D	0.8	3810	3600	3530	3460	3150	1.6	4840	
								12	8390	7930	7780	7620	6940	23	10660	
								1.2	4900	4630	4540	4450	4050	2	6230	
								17	10790	10200	10000	9800	8920	29	13720	
								1.6	6000	5670	5560	5450	4960	2.4	7630	
								23	13220	12490	12250	12000	10930	35	16810	
								1.8	6300	5960	5840	5730	5210	2.6	8020	
								26	13880	13130	12860	12620	11480	38	17670	
								2	6600	6240	6120	6000	5460	2.8	8400	
								29	14540	13740	13480	13220	12030	41	18500	

Size	Rim	Unloaded dimension		Static Loaded Radius	Rolling Circum	Speed Radius Index (SRI)	Load Index	Infl. press.	Maximum load, kg (lbs)							
		SW	OD						Speed, km/h (mph)						*Cyclic	
		mm	mm	mm	mm		10	20	30	40 to 65km/H	70	bar	10			
		in	in	in	in		6	12	19	25 to 40mph	43	psi	6			
VF 650/ 60R34	DW23B	650 25.6	1644 64.7	725 28.5	4865 191.5	775	168D	0.8	3550	3360	3290	3230	2940	1.6	4520	
								12	7820	7400	7250	7110	6480	23	9960	
								1.2	4570	4320	4230	4150	3780	2	5810	
								17	10070	9520	9320	9140	8330	29	12800	
								1.6	5580	5270	5170	5070	4610	2.4	7100	
								23	12290	11610	11390	11170	10150	35	15640	
								2	6160	5820	5710	5600	5100	2.8	7840	
								29	13570	12820	12580	12330	11230	41	17270	

Size	Rim	Unloaded dimension		Static Load- ed Radius	Rolling Circum	Speed Radius Index (SRI)	Load Index	Infl. press.	Maximum load, kg (lbs)							
		S	OD						Speed, km/h (mph)						*Cyclic	
		mm	mm	mm	mm		10	20	30	40 to 65km/H	70	bar	10			
		in	in	in	in		6	12	19	25 to 40mph	43	psi	6			
VF600/ 70R30	DW20L, DW21L	603 23.7	1602 63.1	692 27.3	4731 186.3	750.0	170D	0.8	3610	3410	3350	3280	2980	1.6	4590	
								12	7950	7510	7380	7220	6560	23	10110	
								1.2	4640	4390	4300	4220	3840	2	5910	
								17	10220	9670	9470	9300	8460	29	13020	
								1.6	5670	5360	5250	5150	4690	2.4	7210	
								23	12490	11810	11560	11340	10330	35	15880	
								2	6230	5890	5770	5660	5150	2.8	7920	
								29	13720	12970	12710	12470	11340	41	17440	
								2.4	6600	6240	6120	6000	5460	3.2	8400	
								35	14540	13740	13480	13220	12030	46	18500	

Size	Rim	Unloaded dimension		Static Loaded Radius	Rolling Circum	Speed Radius Index (SRI)	Load Index	Infl. press.	Maximum load, kg (lbs)									
									Speed, km/h (mph)									
		SW							OD		Mixed Application				*Cyclic			
		mm	mm						mm	mm	bar	10	20	30	40 to 65km/H	70	bar	10
in	in	in	in	psi	6	12	19	25 to 40mph	43	psi	6							
VF 650/ 65R34	DW23B, DW21B	650 25.6	1710 67.3	750 29.5	5061 199.2	800	167D	0.8	3930	3710	3640	3570	3250	1.6	5000			
								12	8660	8170	8020	7860	7160	23	11010			
								1.2	5050	4770	4680	4590	4180	2	6430			
								17	11120	10510	10310	10110	9210	29	14160			
								1.4	5520	5220	5120	5020	4570	2.2	7030			
								20	12160	11500	11280	11060	10070	32	15480			
								1.6	6000	5670	5560	5450	4960	2.4	7630			
								23	13220	12490	12250	12000	10930	35	16810			

Size	Rim	Unloaded dimension		Static Loaded Radius	Rolling Circum	Speed Radius Index (SRI)	Load Index	Infl. press.	Maximum load, kg (lbs)									
									Speed, km/h (mph)									
		SW							OD		Mixed Application				*Cyclic			
		mm	mm						mm	mm	bar	10	20	30	40 to 65km/H	70	bar	10
in	in	in	in	psi	6	12	19	25 to 40mph	43	psi	6							
VF 650/ 65R34	DW23B, DW21B	650 25.6	1710 67.3	750 29.5	5061 199.2	800	170D	0.8	3930	3710	3640	3570	3250	1.6	5000			
								12	8660	8170	8020	7860	7160	23	11010			
								1.2	5050	4770	4680	4590	4180	2	6430			
								17	11120	10510	10310	10110	9210	29	14160			
								1.4	5520	5220	5120	5020	4570	2.2	7030			
								20	12160	11500	11280	11060	10070	32	15480			
								2	6600	6240	6120	6000	5460	2.8	8400			
								29	14540	13740	13480	13220	12030	41	18500			

Size	Rim	Unloaded dimension		Static Loaded Radius	Rolling Circum	Speed Radius Index (SRI)	Load Index	Infl. press.	Maximum load, kg (lbs)									
									Speed, km/h (mph)									
		SW							OD		Mixed Application				*Cyclic			
		mm	mm						mm	mm	bar	10	20	30	40 to 65km/H	70	bar	10
in	in	in	in	psi	6	12	19	25 to 40mph	43	psi	6							
VF600/65R 28 NRO	DW20L, DW21L DW18L	597 23.5	1491 58.7	645 25.4	4403 173.3	700	163D	0.8	3180	3010	2950	2890	2630	1.6	4050			
								12	7000	6630	6500	6370	5790	23	8920			
								1.2	4090	3870	3790	3720	3390	2	5210			
								17	9010	8520	8350	8190	7470	29	11480			
								1.4	4480	4230	4150	4070	3700	2.2	5700			
								20	9870	9320	9140	8960	8150	32	12560			
								1.6	4850	4590	4500	4410	4010	2.4	6170			
								23	10680	10110	9910	9710	8830	35	13590			
								2	5360	5070	4970	4875	4440	2.8	6830			
								29	11810	11170	10950	10740	9780	41	15040			

Size	Rim	Unloaded dimension		Static Loaded Radius	Rolling Circum	Speed Radius Index (SRI)	Load Index	Infl. press.	Maximum load, kg (lbs)							
		SW	OD						Speed, km/h (mph)						*Cyclic	
		mm	mm	mm	mm		Speed	bar	10	20	30	40 to 65km/H	70	bar	10	
		in	in	in	in		Symbol	psi	6	12	19	25 to 40mph	43	psi	6	
VF540/65 R30 NRO	DW18L, DW20B DW16L	550 21.7	1464 57.6	641 25.3	4323 170.2	700	158D	0.8	2780	2630	2580	2530	2300	1.6	3540	
								12	6120	5790	5680	5570	5070	23	7800	
								1.2	3580	3380	3320	3250	2960	2	4550	
								17	7890	7440	7310	7160	6520	29	10020	
								1.4	3920	3700	3630	3560	3240	2.2	4980	
								20	8630	8150	8000	7840	7140	32	10970	
								1.6	4250	4010	3940	3860	3510	2.4	5400	
								23	9360	8830	8680	8500	7730	35	11890	
								2	4680	4420	4340	4250	3870	2.8	5950	
								29	10310	9740	9560	9360	8520	41	13110	

Size	Rim	Unloaded dimension		Static Loaded Radius	Rolling Circum	Speed Radius Index (SRI)	Load Index	Infl. press.	Maximum load, kg (lbs)							
		SW	OD						Speed, km/h (mph)						*Cyclic	
		mm	mm	mm	mm		Speed	bar	10	20	30	40 to 65km/H	70	bar	10	
		in	in	in	in		Symbol	psi	6	12	19	25 to 40mph	43	psi	6	
VF600/60R 28 NRO	DW21B, DW20B DW18L	597 23.5	1431 56.3	623 24.5	4226 166.4	675	157D	0.8	0	0	0		0	1.6	0	
								12	0	0	0	0	0	23	0	
								1.2	0	0	0		0	2	0	
								17	0	0	0	0	0	29	0	
								1.4	0	0	0		0	2.2	0	
								20	0	0	0	0	0	32	0	
								1.6	0	0	0		0	2.4	0	
								23	0	0	0	0	0	35	0	
								2	4540	4290	4210	4125	3750	2.8	5780	
								29	10000	9450	9270	9090	8260	41	12730	

Size	Rim	Unloaded dimension		Static Loaded Radius	Rolling Circum	Speed Radius Index (SRI)	Load Index	Infl. press.	Maximum load, kg (lbs)							
		SW	OD						Speed, km/h (mph)						*Cyclic	
		mm	mm	mm	mm		Speed	bar	10	20	30	40 to 65km/H	70	bar	10	
		in	in	in	in		Symbol	psi	6	12	19	25 to 40mph	43	psi	6.2	
VF 650/65 R42 NRO	DW23B, DW21B, DW20 (NRO)	650 25.6	1913 75.3	847 33.4	5649 222.4	900	174D	0.8	4330	4100	4020	3940	3590	1.6	5520	
								12	9540	9030	8850	8680	7910	23	12160	
								1.2	5570	5260	5160	5060	4600	2	7080	
								17	12270	11590	11370	11150	10130	29	15590	
								1.6	6600	6240	6120	6000	5460	2.4	8400	
								23	14540	13740	13480	13220	12030	35	18500	
								2	7370	6970	6830	6700	6100	2.8	9380	
								29	16230	15350	15040	14760	13440	41	20660	

Size	Rim	Unloaded dimension		Static Loaded Radius	Rolling Circum	Speed Radius Index (SRI)	Load Index	Infl. press.	Maximum load, kg (lbs)							
		SW	OD						Speed, km/h (mph)							
		mm	mm	Mixed Application					CFO							
		in	in	10	20		30	40 to 65km/H	50	15	30					
						Speed	bar	6	12	19	25 to 40mph	43	9	19		
						Symbol	psi	6	12	19	25 to 40mph	43	9	19		
VF 850/ 75R42	DW27B, DW30B, DW28B	857 33.7	2308 90.9	993 39.1	6779 266.9	1075	191 A8/B	0.8	7670	7250	7110	6970	6340	9270.1	7736.7	
								12	16890	15970	15660	15350	13960	20420	17040	
								1	8770	8290	8130	7970	7250	10600.1	8846.7	
								15	19320	18260	17910	17560	15970	23350	19490	
								1.2	9870	9330	9150	8970	8160	11930.1	9956.7	
								17	21740	20550	20150	19760	17970	26280	21930	
								1.4	10970	10370	10170	9970	9070	13260.1	11066.7	
								20	24160	22840	22400	21960	19980	29210	24380	
								1.6	11990	11340	11120	10900	9920	14497	12099	
								23	26410	24980	24490	24010	21850	31930	26650	

Size	Rim	Unloaded dimension		Static Loaded Radius	Rolling Circum	Speed Radius Index (SRI)	Load Index	Infl. press.	Maximum load, kg (lbs)							
		SW	OD						Speed, km/h (mph)						*Cyclic	
		mm	mm	10	20		30	40 to 65km/H	70	bar	10					
		in	in	6	12		19	25 to 40mph	43	psi	6					
						Speed	bar	6	12	19	25 to 40mph	43	psi	6		
						Symbol	psi	6	12	19	25 to 40mph	43	psi	6		
VF 650/65 R38 NRO	DW23B, DW21B, DW20 (NRO)	650 25.6	1815 71.5	798 31.4	5360 211.0	850	175D	0.8	4130	3900	3830	3750	3410	1.6	5250	
								12	9100	8590	8440	8260	7510	23	11560	
								1.2	5310	5020	4930	4830	4400	2	6760	
								17	11700	11060	10860	10640	9690	29	14890	
								1.6	6300	5960	5840	5730	5210	2.4	8020	
								23	13880	13130	12860	12620	11480	35	17670	
								2.4	7590	7180	7040	6900	6280	3.2	9660	
								35	16720	15810	15510	15200	13830	46	21280	

Size	Rim	Unloaded dimension		Static Loaded Radius	Rolling Circum	Speed Radius Index (SRI)	Load Index	Infl. press.	Maximum load, kg (lbs)							
		SW	OD						Speed, km/h (mph)						*Cyclic	
		mm	mm	10	20		30	40 to 65km/H	70	bar	10					
		in	in	6	12		19	25 to 40mph	43	psi	6					
						Speed	bar	6	12	19	25 to 40mph	43	psi	6		
						Symbol	psi	6	12	19	25 to 40mph	43	psi	6		
VF 620/ 70R42	DW21B, DW20B, DW23B	620 24.4	1935 76.2	842 33.2	5714 225.0	925	172D	0.6	3780	3580	3510	3440	3130	1.4	4820	
								9	8330	7890	7730	7580	6890	20	10620	
								0.8	4420	4180	4100	4020	3660	1.6	5630	
								12	9740	9210	9030	8850	8060	23	12400	
								1.2	5690	5380	5270	5170	4700	2	7240	
								17	12530	11850	11610	11390	10350	29	15950	
								1.4	6310	5970	5850	5740	5220	2.2	8040	
								20	13900	13150	12890	12640	11500	32	17710	
								1.6	6930	6550	6430	6300	5730	2.4	8820	
								23	15260	14430	14160	13880	12620	35	19430	



TORQUEMAX IF

Size	Rim	Unloaded dimension		Static Loaded Radius	Rolling Circum	Speed Radius Index (SRI)	Load Index	Infl. press.	Maximum load, kg (lbs)							
		SW mm in	OD mm in						Speed, km/h (mph)							CFO
				Mixed Application					CFO							
				10	20		30	40 to 65km/H 25 to 40mph	70	15	30					
Symbol	psi	6	12	19	43	9	19									
IF 710/75 R42 CFO	DW25B, DW23B, DW24B	715 28.1	2133 84.0	944 37.2	6306 248.3	1000	176D	0.8	5730	4870	4690	4510	4100	6990.5	5863	
								12	12620	10730	10330	9930	9030	15400	12910	
								1.0	6540	5560	5360	5150	4690	7982.5	6695	
								15	14410	12250	11810	11340	10330	17580	14750	
								1.2	7370	6260	6030	5800	5280	8990	7540	
								17	16230	13790	13280	12780	11630	19800	16610	
								1.6	9020	7670	7380	7100	6460	11005	9230	
								23	19870	16890	16260	15640	14230	159573	20330	

Size	Rim	Unloaded dimension		Static Loaded Radius	Rolling Circum	Speed Radius Index (SRI)	Load Index	Infl. press.	Maximum load, kg (lbs)							
		SW mm in	OD mm in						Speed, km/h (mph)							CFO
				Mixed Application					CFO							
				10	20		30	40 to 65km/H 25 to 40mph	70	15	30					
Symbol	psi	6	12	19	43	9	19									
IF710/70R 42 CFO	DW23B, DW25B	720 28.3	2061 77.1	932 33.5	6125 228.3	975	179D	0.8	5380	4580	4410	4240	3860	6572	5512	
								12	11850	10090	9710	9340	8500	14480	12140	
								1.2	6920	5890	5670	5450	4960	8447.5	7085	
								17	15240	12970	12490	12000	10930	18610	15610	
								1.6	8460	7190	6930	6660	6060	10323	8658	
								23	18630	15840	15260	14670	13350	22740	19070	
								2	9280	7890	7600	7310	6650	11330.5	9503	
								29	20440	17380	16740	16100	14650	24960	20930	
								2.4	9840	8370	8060	7750	7050	12012.5	10075	
								35	21670	18440	17750	17070	15530	174181	22190	

Size	Rim	Unloaded dimension		Static Loaded Radius	Rolling Circum	Speed Radius Index (SRI)	Load Index	Infl. press.	Maximum load, kg (lbs)							
		Speed, km/h (mph)														
		Mixed Application							CFO							
		SW	OD						10	20	30	40 to 65km/H	70	15	30	
mm	mm	bar	bar	bar	psi	psi	psi	psi	psi							
in	in	psi	psi	psi	psi	psi	psi	psi	psi							
IF850/75R 42 CFO	DW28B, DW30B	857	2308	993	6779	1075	186D	0.8	7590	6460	6220	5980	5440	9269	7774	
		33.7	90.9	39.1	266.9			12	16720	14230	13700	13170	11980	20420	17120	
								1	8670	7380	7100	6830	6220	10586.5	8879	
								15	19100	16260	15640	15040	13700	23320	19560	
								1.2	9770	8310	8000	7690	7000	11919.5	9997	
								17	21520	18300	17620	16940	15420	26250	22020	
								1.4	10850	9220	8880	8540	7770	13237	11102	
								20	23900	20310	19560	18810	17110	29160	24450	
								1.6	12070	10260	9880	9500	8650	14725	12350	
								23	26590	22600	21760	20930	19050	32430	27200	

Size	Rim	Unloaded dimension		Static Loaded Radius	Rolling Circum	Speed Radius Index (SRI)	Load Index	Infl. press.	Maximum load, kg (lbs)							
		Speed, km/h (mph)														
		Mixed Application							*Cyclic							
		SW	OD						10	20	30	40 to 65km/H	70	bar	10	
mm	mm	bar	bar	bar	psi	psi	psi	psi	psi							
in	in	psi	psi	psi	psi	psi	psi	psi	psi							
IF520/ 85R38	DW18L, DW16	536	1849	832	5402	875.0	167D	0.8	3770	3210	3090	2970	2700	1.6	4160	
		21.1	72.8	32.8	212.7			12	8300	7070	6810	6540	5950	23	9160	
								1.2	4850	4130	3970	3820	3480	2	5350	
								17	10680	9100	8740	8410	7670	29	11780	
								1.6	5930	5040	4860	4670	4250	2.4	6540	
								23	13060	11100	10700	10290	9360	35	14410	
								2	6500	5530	5320	5120	4660	2.8	7170	
								29	14320	12180	11720	11280	10260	41	15790	
								2.4	6920	5890	5670	5450	4960	3.2	7630	
								35	15240	12970	12490	12000	10930	46	16810	

Size	Rim	Unloaded dimension		Static Loaded Radius	Rolling Circum	Speed Radius Index (SRI)	Load Index	Infl. press.	Maximum load, kg (lbs)							
		Speed, km/h (mph)														
		Mixed Application							CFO							
		SW	OD						10	20	30	40 to 65km/H	70	15	30	
mm	mm	bar	bar	bar	psi	psi	psi	psi	psi							
in	in	psi	psi	psi	psi	psi	psi	psi	psi							
IF800/70R 38 CFO	DW28B, DW27B, DW30B	810	2085	925	6124	975	190D	0.8	6210	5280	5090	4890	4450	7580	6357	
		31.9	82.1	36.4	241.1			12	13680	11630	11210	10770	9800	16690	14000	
								1.2	7990	6790	6540	6290	5720	9750	8177	
								17	17600	14960	14410	13850	12600	21470	18010	
								1.6	9770	8310	8000	7690	7000	11920	9997	
								23	21520	18300	17620	16940	15420	26250	22020	
								2	10710	9100	8770	8430	7670	13067	10959	
								29	23590	20040	19320	18570	16890	28780	24140	
								2.4	11400	9700	9340	8980	8170	13919	11674	
								35	25110	21370	20570	19780	18000	30660	25710	
								3.2	13460	11450	11020	10600	9650	16430	13780	
								46	29650	25220	24270	23350	21260	36190	30350	

Size	Rim	Unloaded dimension		Static Loaded Radius	Rolling Circum	Speed Radius Index (SRI)	Load Index	Infl. press.	Maximum load, kg (lbs)							
									Speed, km/h (mph)							
		SW	OD						Mixed Application					CFO		
		mm	mm						10	20	30	40 to 65km/H	70	15	30	
in	in	in	in	in	in	in	in	in	in							
IF710/70R 38 CFO	DW23B, DW25B	720 28.3	1959 77.1	850 33.5	5800 228.3	925	178D	0.8	5140	4370	4210	4050	3690	6277.5	5265	
								12	11320	9630	9270	8920	8130	13830	11600	
								1.2	6620	5630	5420	5210	4740	8075.5	6773	
								17	14580	12400	11940	11480	10440	17790	14920	
								1.6	8090	6880	6620	6370	5800	9873.5	8281	
								23	17820	15150	14580	14030	12780	21750	18240	
								2	8880	7550	7270	6990	6360	10834.5	9087	
								29	19560	16630	16010	15400	14010	23860	20020	
								2.4	9530	8100	7800	7500	6830	11625	9750	
								35	20990	17840	17180	16520	15040	168563	21480	

Size	Rim	Unloaded dimension		Static Loaded Radius	Rolling Circum	Speed Radius Index (SRI)	Load Index	Infl. press.	Maximum load, kg (lbs)							
									Speed, km/h (mph)							
		SW	OD						Mixed Application					CFO		
		mm	mm						10	20	30	40	50	15	30	
in	in	in	in	in	in	in	in	in	in							
IF710/70 R38 CFO	DW23B, DW25B	720 28.3	1959 77.1	850 33.5	5800 228.3	925	181A8/ B	0.8	5140	4370	4210	4050	3690	6277.5	5265	
								12	11320	9630	9270	8920	8130	13830	11600	
								1.2	6620	5630	5420	5210	4740	8075.5	6773	
								17	14580	12400	11940	11480	10440	17790	14920	
								1.6	8090	6880	6620	6370	5800	9873.5	8281	
								23	17820	15150	14580	14030	12780	21750	18240	
								2.4	9460	8050	7750	7450	6780	11547.5	9685	
								35	20840	17730	17070	16410	14930	25440	21330	
								2.8	10480	8910	8580	8250	7510	12787.5	10725	
								41	23080	19630	18900	18170	16540	185419	23620	

Size	Rim	Unloaded dimension		Static Loaded Radius	Rolling Circum	Speed Radius Index (SRI)	Load Index	Infl. press.	Maximum load, kg (lbs)							
									Speed, km/h (mph)						*Cyclic	
		SW	OD						Mixed Application							
		mm	mm						10	20	30	40 to 65km/H	70	bar	10	
in	in	in	in	in	in	in	psi	psi	6							
IF600/ 70R34	DW20L, DW21L	603 23.7	1704 67.1	768 30.3	5086 200.2	800.0	160D	0.8	3770	3210	3090	2970	2700	1.6	4160	
								12	8300	7070	6810	6540	5950	23	9160	
								1	4310	3660	3530	3390	3080	1.8	4750	
								15	9490	8060	7780	7470	6780	26	10460	
								1.2	4850	4130	3970	3820	3480	2	5350	
								17	10680	9100	8740	8410	7670	29	11780	
								1.4	5380	4580	4410	4240	3860	2.2	5940	
								20	11850	10090	9710	9340	8500	32	13080	
								1.6	5750	4890	4710	4530	4120	2.4	6340	
								23	12670	10770	10370	9980	9070	35	13960	

Size	Rim	Unloaded dimension		Static Loaded Radius	Rolling Circum	Speed Radius Index (SRI)	Load Index	Infl. press.	Maximum load, kg (lbs)							
		SW	OD						Speed, km/h (mph)							*Cyclic
		mm	mm	mm	mm		Speed	bar	10	20	30	40 to 65km/H	70	bar	10	
		in	in	in	in		Symbol	psi	6	12	19	25 to 40mph	43	psi	6	
IF600/ 70R34	DW20L, DW21L	603 23.7	1704 67.1	768 30.3	5086 200.2	800	167D	0.8	3770	3210	3090	2970	2700	1.6	4160	
								12	8300	7070	6810	6540	5950	23	9160	
								1.2	4850	4130	3970	3820	3480	2	5350	
								17	10680	9100	8740	8410	7670	29	11780	
								1.6	5840	4970	4780	4600	4190	2.4	6440	
								23	12860	10950	10530	10130	9230	35	14190	
								2	6500	5530	5320	5120	4660	2.8	7170	
								29	14320	12180	11720	11280	10260	41	15790	
								2.4	6920	5890	5670	5450	4960	3.2	7630	
								35	15240	12970	12490	12000	10930	46	16810	

Size	Rim	Unloaded dimension		Static Loaded Radius	Rolling Circum	Speed Radius Index (SRI)	Load Index	Infl. press.	Maximum load, kg (lbs)							
		SW	OD						Speed, km/h (mph)							*Cyclic
		mm	mm	mm	mm		Speed	bar	10	20	30	40 to 65km/H	70	bar	10	
		in	in	in	in		Symbol	psi	6	12	19	25 to 40mph	43	psi	6	
IF 650/ 60R34	DW23B	650 25.6	1644 64.7	735 28.9	4855 191.1	775	159D	0.8	3520	2990	2880	2770	2520	1.6	3880	
								12	7750	6590	6340	6100	5550	23	8550	
								1.0	4020	3420	3290	3165	2880	1.8	4430	
								15	8850	7530	7250	6970	6340	26	9760	
								1.2	4520	3840	3700	3560	3240	2	4980	
								17	9960	8460	8150	7840	7140	29	10970	
								1.6	5560	4730	4550	4375	3980	2.4	6130	
								23	12250	10420	10020	9640	8770	35	13500	

Size	Rim	Unloaded dimension		Static Loaded Radius	Rolling Circum	Speed Radius Index (SRI)	Load Index	Infl. press.	Maximum load, kg (lbs)							
		SW	OD						Speed, km/h (mph)							*Cyclic
		mm	mm	mm	mm		Speed	bar	10	20	30	40 to 65km/H	70	bar	10	
		in	in	in	in		Symbol	psi	6	12	19	25 to 40mph	43	psi	6	
IF600/ 70R30	DW20L, DW21L	603 23.7	1602 63.1	726 28.6	4781 188.2	750	165D	0.8	3570	3030	2920	2810	2560	1.6	3930	
								12	7860	6670	6430	6190	5640	23	8660	
								1.2	4580	3900	3750	3610	3290	2	5050	
								17	10090	8590	8260	7950	7250	29	11120	
								1.6	5610	4770	4600	4420	4020	2.4	6190	
								23	12360	10510	10130	9740	8850	35	13630	
								2	6160	5240	5040	4850	4410	2.8	6790	
								29	13570	11540	11100	10680	9710	41	14960	
								2.4	6540	5560	5360	5150	4690	3.2	7210	
								35	14410	12250	11810	11340	10330	46	15880	