

FEATURES AND BENEFITS

Higher angle & lug
overlap at centre

Better roadability
& stability



Rounded shoulder
Reduced crop damage



Higher number
of lugs
Superior traction



D-rated
(65 kmph) tires

Improved
transportation speed

Strong carcass
& bead

Higher load
carrying capacity

ROW CROP AGRI RADIAL

TRA CODE : R-1/R-1W



FARMAX RC

Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommend load, kg (lbs)							
		SW	OD					Speed, km/h (mph)							
		mm/in	mm/in					mm/in	mm/in	Speed Symbol	bar psi	Field	10 6	25 16	40 25
320/90 R54	W10 W9 W11	325 12.8	1960 77.2	911 35.9	5880 231.5	153D/ 156A8	0.8	1630	2130	1680	1550	1490	1420	1290	
							12	3590	4690	3700	3410	3280	3130	2840	
							1.6	2450	3200	2520	2330	2240	2130	1940	
							23	5400	7050	5550	5130	4930	4690	4270	
							2.4	3110	4050	3200	2960	2840	2700	2460	
							35	6850	8920	7050	6520	6260	5950	5420	
							3.2	3680	4800	3790	3500	3360	3200	2910	
							46	8110	10570	8350	7710	7400	7050	6410	
							4	4200	5480	4330	4000	3830	3650	3320	
58	9250	12070	9540	8810	8440	8040	7310								

Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommend load, kg (lbs)							
		SW	OD					Speed, km/h (mph)							
		mm/in	mm/in					mm/in	mm/in	Speed Symbol	bar psi	Field	10 6	25 16	40 25
270/95 R54 (11.2R54)	W9 W8 W10	275 10.8	1886 74.3	892 35.1	5783 227.7	146D/ 149A8	0.8	1350	1760	1390	1280	1230	1170	1060	
							12	2970	3880	3060	2820	2710	2580	2330	
							1.6	2020	2640	2090	1930	1850	1760	1600	
							23	4450	5810	4600	4250	4070	3880	3520	
							2.4	2560	3350	2640	2440	2340	2230	2030	
							35	5640	7380	5810	5370	5150	4910	4470	
							3.4	3140	4100	3240	2990	2870	2730	2480	
							49	6920	9030	7140	6590	6320	6010	5460	
							4	3450	4500	3560	3290	3150	3000	2730	
58	7600	9910	7840	7250	6940	6610	6010								

Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommend load, kg (lbs)							
		SW	OD					Speed, km/h (mph)							
		mm/in	mm/in					mm/in	mm/in	Speed Symbol	bar psi	Field	10 6	25 16	40 25
300/95 R52 (12.4 R 52)	W9 W10	300 11.8	1891 74.4	892 35.1	5792 228.0	149D/ 152A8	0.8	1460	1910	1500	1390	1330	1270	1160	
							12	3220	4210	3300	3060	2930	2800	2560	
							1.6	2190	2850	2250	2080	2000	1900	1730	
							23	4820	6280	4960	4580	4410	4190	3810	
							2.4	2770	3620	2860	2640	2530	2410	2190	
							35	6100	7970	6300	5810	5570	5310	4820	
							3.4	3400	4440	3510	3240	3110	2960	2690	
							49	7490	9780	7730	7140	6850	6520	5930	
							4	3740	4880	3850	3560	3410	3250	2960	
58	8240	10750	8480	7840	7510	7160	6520								

Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommend load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
		mm/in	mm/in	mm/in	mm/in	Speed Symbol	bar psi	Field	10 6	25 16	40 25	50 31	65 40	70 43
380/90 R50 (14.9 R 50)	W12 W11 W13	390 15.4	1954 76.9	918 36.1	5951 234.3	151D/ 154A8	0.8	2090	2730	2160	1990	1910	1820	1660
							12	4600	6010	4760	4380	4210	4010	3660
							1.4	2900	3780	2990	2760	2650	2520	2290
							20	6390	8330	6590	6080	5840	5550	5040
							2	3570	4650	3670	3390	3260	3100	2820
							29	7860	10240	8080	7470	7180	6830	6210
							2.4	3970	5180	4090	3780	3620	3450	3140
							35	8740	11410	9010	8330	7970	7600	6920
							0.8	2090	2730	2160	1990	1910	1820	1660
						12	4600	6010	4760	4380	4210	4010	3660	
						1.6	3050	3980	3140	2900	2780	2650	2410	
						23	6720	8770	6920	6390	6120	5840	5310	
						2.6	4050	5280	4170	3850	3700	3520	3200	
						38	8920	11630	9190	8480	8150	7750	7050	
						3.2	4570	5960	4700	4350	4170	3970	3610	
						46	10070	13130	10350	9580	9190	8740	7950	
						3.6	4890	6380	5040	4650	4460	4250	3870	
						52	10770	14050	11100	10240	9820	9360	8520	

Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommend load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
		mm/in	mm/in	mm/in	mm/in	Speed Symbol	bar psi	Field	10 6	25 16	40 25	50 31	65 40	70 43
380/105 R50	W11 W12 W13	400 15.7	2050 80.7	952 37.5	6144 241.9	168D/ 171A8	0.8	2380	3110	2450	2270	2170	2070	1880
							12	5240	6850	5400	5000	4780	4560	4140
							1.6	3570	4650	3670	3390	3260	3100	2820
							23	7860	10240	8080	7470	7180	6830	6210
							2.4	4520	5900	4660	4300	4130	3930	3580
							35	9960	13000	10260	9470	9100	8660	7890
							3.6	5730	7470	5900	5450	5230	4980	4530
							52	12620	16450	13000	12000	11520	10970	9980
							4.0	6100	7950	6280	5800	5570	5300	4820
							58	13440	17510	13830	12780	12270	11670	10620
							4.4	6440	8400	6640	6130	5880	5600	5100
							64	14190	18500	14630	13500	12950	12330	11230

Size	Rim	Infl tire dimension		Static Loaded Radius	Circum	Load Index	Infl. Press	Recommend load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
		mm/in	mm/in	mm/in	mm/in	Speed Symbol	bar psi	Field	10 6	25 16	40 25	50 31	65 40	70 43
320/90 R50	W10 W9 W11	325 12.8	1846 72.7	867 34.1	5576 219.5	150D/ 153A8	0.8	1660	2160	1710	1580	1510	1440	1310
							12	3660	4760	3770	3480	3330	3170	2890
							1.6	2600	3390	2680	2470	2370	2260	2060
							23	5730	7470	5900	5440	5220	4980	4540
							2.4	3050	3980	3140	2900	2780	2650	2410
							35	6720	8770	6920	6390	6120	5840	5310
							3.2	3600	4700	3710	3430	3290	3130	2850
							46	7930	10350	8170	7560	7250	6890	6280
							3.6	3850	5030	3970	3670	3520	3350	3050
							52	8480	11080	8740	8080	7750	7380	6720

Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommend load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
		mm/in	mm/in					mm/in	mm/in	Speed	bar	Field	10	25
Symbol	psi	6	16	25	31	40	43							
340/85 R48	W12 W11	353.0 13.9	1797.0 70.7	841 33.1	5521 217.4	156D/ 159A8	0.8	1680	2190	1730	1600	1530	1460	1330
							12	3700	4820	3810	3520	3370	3220	2930
							1.6	2520	3290	2600	2400	2300	2190	1990
							23	5550	7250	5730	5290	5070	4820	4380
							2.4	3190	4160	3280	3030	2910	2770	2520
							35	7030	9160	7220	6670	6410	6100	5550
							3.2	3770	4920	3890	3590	3440	3280	2980
							46	8300	10840	8570	7910	7580	7220	6560
							4.5	4600	6000	4740	4380	4200	4000	3640
							65	10130	13220	10440	9650	9250	8810	8020

Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommend load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
		mm/in	mm/in					mm/in	mm/in	Speed	bar	Field	10	25
Symbol	psi	6	16	25	31	40	43							
340/85 R48	W12 W11	343.0 13.5	1797.0 70.7	841.2 33.1	5476.1 215.6	148D/ 151A8	0.8	1510	1970	1550	1430	1380	1310	1190
							12	3330	4340	3410	3150	3040	2890	2620
							1.6	2250	2940	2320	2150	2060	1960	1780
							23	4960	6480	5110	4740	4540	4320	3920
							2.4	2850	3720	2940	2720	2600	2480	2260
							35	6280	8190	6480	5990	5730	5460	4980
							3.2	3380	4410	3480	3220	3090	2940	2680
							46	7440	9710	7670	7090	6810	6480	5900
							3.6	3620	4730	3730	3450	3310	3150	2870
							52	7970	10420	8220	7600	7290	6940	6320

Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommend load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
		mm/in	mm/in					mm/in	mm/in	Speed	bar	Field	10	25
Symbol	psi	6	16	25	31	40	43							
270/95 R48 (11.2-48)	W9 W8 W10	275 10.83	1733 68.23	816 32.13	5281 207.91	142D/ 145A8	0.8	1320	1730	1360	1260	1210	1150	1050
							12	2910	3810	3000	2780	2670	2530	2310
							1.6	2070	2700	2130	1970	1890	1800	1640
							23	4560	5950	4690	4340	4160	3960	3610
							2.4	2430	3170	2500	2310	2220	2110	1920
							35	5350	6980	5510	5090	4890	4650	4230
							3.2	2860	3740	2950	2730	2610	2490	2270
							46	6300	8240	6500	6010	5750	5480	5000
							3.6	3050	3980	3140	2900	2780	2650	2410
							52	6720	8770	6920	6390	6120	5840	5310

Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommend load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
		mm/in	mm/in					Field	10	25	40	50	65	70
		mm/in	mm/in						6	16	25	31	40	43
230/95 R48	W7 W8	228 9.0	1657 65.2	785.2 30.9	5049.45 198.8	136D/ 139A8	0.8	1410	1850	1460	1350	1290	1230	1120
							12	3110	4070	3220	2970	2840	2710	2470
							1.6	2120	2760	2180	2010	1930	1840	1670
							23	4670	6080	4800	4430	4250	4050	3680
							2.4	2680	3500	2760	2550	2450	2330	2120
							35	5900	7710	6080	5620	5400	5130	4670
							3.4	3290	4290	3390	3130	3000	2860	2600
							49	7250	9450	7470	6890	6610	6300	5730
							4	3620	4730	3730	3450	3310	3150	2870
							58	7970	10420	8220	7600	7290	6940	6320

Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommend load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
		mm/in	mm/in					Field	10	25	40	50	65	70
		mm/in	mm/in						6	16	25	31	40	43
380/90 R46 (14.9 R 46)	W11 W12 W13	380 15.0	1852 72.9	975 38.4	5527 217.6	159D/ 162A8	0.8	1970	2570	2030	1870	1800	1710	1560
							12	4340	5660	4470	4120	3960	3770	3440
							1.6	2960	3860	3050	2810	2700	2570	2340
							23	6520	8500	6720	6190	5950	5660	5150
							2.4	3750	4890	3860	3570	3420	3260	2970
							35	8260	10770	8500	7860	7530	7180	6540
							3.6	4750	6200	4890	4520	4340	4130	3760
							52	10460	13660	10770	9960	9560	9100	8280
							4.0	5050	6590	5200	4810	4610	4390	3990
							58	11120	14520	11450	10590	10150	9670	8790
							4.5	5410	7050	5570	5150	4940	4700	4280
							65	11920	15530	12270	11340	10880	10350	9430

Size	Rim	Inflated dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommend load, kg (lbs)				
		SW	OD					Speed, km/h (mph)				
		mm/in	mm/in					Field	10	25	40	50
		mm/in	mm/in						6	16	25	31
380/90 R46 (14.9 R 46)	W11 W12 W13	380 15.0	1852 72.9	975 38.4	5527 217.6	165A8/ B	0.8	2040	2660	1960	1770	1770
							12	4490	5860	4320	3900	3900
							1.6	3210	4190	3100	2790	2790
							23	7070	9230	6830	6150	6150
							2.4	3750	4890	3620	3260	3260
							35	8260	10770	7970	7180	7180
							3.6	4730	6170	4560	4110	4110
							52	10420	13590	10040	9050	9050
							4.2	5200	6780	5020	4520	4520
							61	11450	14930	11060	9960	9960
							4.8	5920	7730	5720	5150	5150
							70	13040	17030	12600	11340	11340

Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommend load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
		mm/in	mm/in	mm/in	mm/in	Speed	bar	Field	10	25	40	50	65	70
				Symbol	psi		6		16	25	31	40	43	
380/90 R46 (14.9 R 46)	W11 W12 W13	380 15.0	1852 72.9	975 38.4	5527 217.6	162D/ 165A8	0.8	1910	2490	1970	1820	1740	1660	1510
							12	4210	5480	4340	4010	3830	3660	3330
							1.6	2860	3740	2950	2730	2610	2490	2270
							23	6300	8240	6500	6010	5750	5480	5000
							2.4	3630	4740	3740	3460	3320	3160	2880
							35	8000	10440	8240	7620	7310	6960	6340
							3.6	4610	6020	4750	4390	4210	4010	3650
							52	10150	13260	10460	9670	9270	8830	8040
							4.0	4910	6410	5060	4680	4480	4270	3890
							58	10810	14120	11150	10310	9870	9410	8570
							4.8	5460	7130	5630	5200	4990	4750	4320
70	12030	15700	12400	11450	10990	10460	9520							

Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommend load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
		mm/in	mm/in	mm/in	mm/in	Speed	bar	Field	10	25	40	50	65	70
				Symbol	psi		6		16	25	31	40	43	
340/85 R46	W11 W12	343 13.5	1746 68.7	816 32.1	5310 209.0	147D/ 150A8	0.8	1470	1920	1520	1400	1340	1280	1160
							12	3240	4230	3350	3080	2950	2820	2560
							1.6	2210	2880	2280	2100	2020	1920	1750
							23	4870	6340	5020	4630	4450	4230	3850
							2.4	2790	3650	2880	2660	2550	2430	2210
							35	6150	8040	6340	5860	5620	5350	4870
							3.2	3300	4310	3400	3140	3010	2870	2610
							46	7270	9490	7490	6920	6630	6320	5750
							3.6	3540	4610	3640	3370	3230	3075	2800
						52	7800	10150	8020	7420	7110	6770	6170	
						150D/ 153A8	0.8	1470	1920	1520	1400	1340	1280	1160
							12	3240	4230	3350	3080	2950	2820	2560
							1.8	2360	3080	2430	2240	2150	2050	1870
							26	5200	6780	5350	4930	4740	4520	4120
							2.6	2920	3810	3010	2780	2670	2540	2310
							38	6430	8390	6630	6120	5880	5590	5090
							3.4	3420	4460	3520	3250	3120	2970	2700
							49	7530	9820	7750	7160	6870	6540	5950
							4	3850	5030	3970	3670	3520	3350	3050
58	8480	11080	8740	8080	7750		7380	6720						

Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommend load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
		mm/in	mm/in	mm/in	mm/in	Speed	bar	Field	10	25	40	50	65	70
				Symbol	psi		6		16	25	31	40	43	
320/90 R46	W10 W9 W11	325 12.8	1744 68.7	817 32.2	5260 207.1	148D/ 151A8	0.8	1510	1970	1550	1430	1380	1310	1190
							12	3330	4340	3410	3150	3040	2890	2620
							1.6	2250	2940	2320	2150	2060	1960	1780
							23	4960	6480	5110	4740	4540	4320	3920
							2.4	2860	3740	2950	2730	2610	2490	2270
							35	6300	8240	6500	6010	5750	5480	5000
							2.8	3130	4080	3220	2980	2860	2720	2480
							41	6890	8990	7090	6560	6300	5990	5460
							3.6	3620	4730	3730	3450	3310	3150	2870
							52	7970	10420	8220	7600	7290	6940	6320

Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl.	Recommend load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
		mm/in	mm/in					mm/in	mm/in	Speed	bar	Field	10	25
Symbol	psi	6	16	25	31	40	43							
320/90 R46	W10 W9 W11	325 12.8	1744 68.7	817 32.2	5260 207.1	146D/ 149A8	0.8	1530	2000	1580	1460	1400	1330	1210
							12	3370	4410	3480	3220	3080	2930	2670
							1.6	2300	3000	2370	2190	2100	2000	1820
							23	5070	6610	5220	4820	4630	4410	4010
							2.4	2910	3800	3000	2770	2660	2530	2300
							35	6410	8370	6610	6100	5860	5570	5070
							2.8	3190	4160	3280	3030	2910	2770	2520
							41	7030	9160	7220	6670	6410	6100	5550
							3.2	3450	4500	3560	3290	3150	3000	2730
46	7600	9910	7840	7250	6940	6610	6010							

Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommend load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
		mm/in	mm/in					mm/in	mm/in	Speed	bar	Field	10	25
Symbol	psi	6	16	25	31	40	44							
300/95 R46 (12.4 R 46)	W9 W10	300 11.8	1738 68.4	815 32.1	5242 206.4	143D/ 146A8	0.8	1300	1700	1340	1240	1190	1130	1030
							11.6	2860	3740	2950	2730	2620	2490	2270
							1.6	1960	2550	2010	1860	1790	1700	1550
							23.2	4320	5620	4430	4100	3940	3740	3410
							2.4	2470	3230	2550	2350	2260	2150	1960
							34.8	5440	7110	5620	5180	4980	4740	4320
							3.2	2920	3810	3010	2780	2670	2540	2310
							46.4	6430	8390	6630	6120	5880	5590	5090
							3.6	3130	4090	3230	2970	2860	2725	2480
							52.2	6890	9010	7110	6540	6300	6000	5460
						148D/ 151A8	0.8	1300	1700	1340	1240	1190	1130	1030
							11.6	2860	3740	2950	2730	2620	2490	2270
							1.8	2090	2730	2160	1990	1910	1820	1660
							26.1	4600	6010	4760	4380	4210	4010	3660
							2.6	2590	3380	2670	2460	2360	2250	2050
							37.7	5700	7440	5880	5420	5200	4960	4520
							3.4	3290	4290	3390	3130	3000	2860	2600
							49.3	7250	9450	7470	6890	6610	6300	5730
							4	3620	4730	3730	3450	3310	3150	2870
							58	7970	10420	8220	7600	7290	6940	6320

Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommend load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
		mm/in	mm/in					mm/in	mm/in	Speed	bar	Field	10	25
Symbol	psi	6	16	25	31	40	43							
270/95 R46 (11.2R46)	W9 W8 W10	275 10.8	1682 66.2	790 31.1	5126 201.8	141D/ 144A8	0.8	1160	1520	1200	1110	1060	1010	920
							12	2560	3350	2640	2440	2330	2220	2030
							1.6	1740	2270	1790	1650	1590	1510	1370
							23	3830	5000	3940	3630	3500	3330	3020
							2.4	2200	2870	2260	2090	2010	1910	1740
							35	4850	6320	4980	4600	4430	4210	3830
							3.4	2690	3510	2770	2560	2460	2340	2130
							49	5930	7730	6100	5640	5420	5150	4690
							4	2960	3860	3050	2820	2700	2575	2340
							58	6520	8500	6720	6210	5950	5670	5150

Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommend load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
		mm/in	mm/in					mm/in	mm/in	Speed Symbol	bar	psi	Field	10
270/95 R44 (11.2R44)	W9 W8 W10	275 10.8	1632 64.3	765 30.1	4948 194.8	142D/ 145A8	0.8	1120	1460	1150	1060	1020	970	880
							12	2470	3220	2530	2330	2250	2140	1940
							1.6	1680	2190	1730	1600	1530	1460	1330
							23	3700	4820	3810	3520	3370	3220	2930
							2.4	2130	2780	2190	2030	1940	1850	1680
							35	4690	6120	4820	4470	4270	4070	3700
							3.6	2700	3530	2780	2570	2470	2350	2140
							52	5950	7780	6120	5660	5440	5180	4710
							4	2880	3750	2960	2740	2630	2500	2280
							58	6340	8260	6520	6040	5790	5510	5020
							4.4	3050	3980	3140	2900	2780	2650	2410
							64	6720	8770	6920	6390	6120	5840	5310

Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommend load, kg (lbs)							
		SW	OD					Speed, km/h (mph)							
		mm/in	mm/in					mm/in	mm/in	Speed Symbol	bar	psi	Field	10	25
270/95 R44 (11.2R44)	W9 W8 W10	275 10.8	1632 64.3	765 30.1	4948 194.8	140D/ 143A8	0.8	1120	1460	1150	1060	1020	970	880	
							12	2470	3220	2530	2330	2250	2140	1940	
							1.6	1680	2190	1730	1600	1530	1460	1330	
							23	3700	4820	3810	3520	3370	3220	2930	
							2.4	2130	2780	2190	2030	1940	1850	1680	
							35	4690	6120	4820	4470	4270	4070	3700	
							3.4	2610	3410	2690	2490	2380	2270	2070	
							49	5750	7510	5930	5480	5240	5000	4560	
							4	2880	3750	2960	2740	2630	2500	2280	
							58	6340	8260	6520	6040	5790	5510	5020	
							142D/ 145A8	0.8	1120	1460	1150	1060	1020	970	880
								12	2470	3220	2530	2330	2250	2140	1940
						1.6		1680	2190	1730	1600	1530	1460	1330	
						23		3700	4820	3810	3520	3370	3220	2930	
						2.4		2130	2780	2190	2030	1940	1850	1680	
						35		4690	6120	4820	4470	4270	4070	3700	
						3.6		2700	3530	2780	2570	2470	2350	2140	
						52		5950	7780	6120	5660	5440	5180	4710	
						4		2880	3750	2960	2740	2630	2500	2280	
						58		6340	8260	6520	6040	5790	5510	5020	
						4.4		3050	3980	3140	2900	2780	2650	2410	
						64		6720	8770	6920	6390	6120	5840	5310	

Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommend load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
		mm/in	mm/in					mm/in	mm/in	Speed	bar	Field	10	25
Symbol	psi	6	16	25	31	40	43							
230/95 R44	W7 W8	228 9.0	1556 61.3	735 28.9	4791 188.6	129D/ 132A8	0.8	890	1160	910	840	810	770	700
							12	1960	2560	2000	1850	1780	1700	1540
							1.6	1320	1730	1360	1260	1210	1150	1050
							23	2910	3810	3000	2780	2670	2530	2310
							2.4	1680	2190	1730	1600	1530	1460	1330
							23	2910	3810	3000	2780	2670	2530	2310
							3.2	1990	2600	2050	1890	1820	1730	1570
							35	3700	4820	3810	3520	3370	3220	2930
							3.6	2130	2780	2190	2030	1940	1850	1680
	52	4690	6120	4820	4470	4270	4070	3700						
	134D/ 137A8	0.8	1000	1310	1030	950	910	870	790					
		12	2200	2890	2270	2090	2000	1920	1740					
		1.8	1640	2150	1690	1570	1500	1430	1300					
		26	3610	4740	3720	3460	3300	3150	2860					
		2.8	2000	2610	2060	1910	1830	1740	1580					
		41	4410	5750	4540	4210	4030	3830	3480					
		3.4	2240	2930	2310	2140	2050	1950	1770					
		49	4930	6450	5090	4710	4520	4300	3900					
4		2440	3180	2510	2320	2230	2120	1930						
58	5370	7000	5530	5110	4910	4670	4250							

Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommend load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
		mm/in	mm/in					mm/in	mm/in	Speed	bar	Field	10	25
Symbol	psi	6	16	25	31	40	43							
210/95 R44 (8.3 R 44)	W7 W6	214 8.4	1518 59.8	719 28.3	4626 182.1	120D/ 123A8	0.8	840	1100	870	800	770	730	660
							12	1850	2420	1920	1760	1700	1610	1450
							1.2	1070	1400	1100	1020	980	930	850
							17	2360	3080	2420	2250	2160	2050	1870
							1.8	1360	1770	1400	1290	1240	1180	1070
							26	3000	3900	3080	2840	2730	2600	2360
							2.4	1610	2100	1660	1530	1470	1400	1270
							35	3550	4630	3660	3370	3240	3080	2800

Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommend load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
		mm/in	mm/in	mm/in	mm/in	Speed	bar	Field	10	25	40	50	65	70
						Symbol	psi		6	16	25	31	40	43
320/90 R42	W10 W9 W11	319 12.6	1643 64.7	764 30.1	4950 194.9	136D/ 139A8	0.8	1350	1760	1390	1280	1230	1170	1060
							12	2970	3880	3060	2820	2710	2580	2330
							1.6	2020	2640	2090	1930	1850	1760	1600
							23	4450	5810	4600	4250	4070	3880	3520
							2	2310	3020	2380	2200	2110	2010	1830
							29	5090	6650	5240	4850	4650	4430	4030
							2.4	2580	3360	2650	2450	2350	2240	2040
							35	5680	7400	5840	5400	5180	4930	4490
							144D/ 147A8	0.8	1350	1760	1390	1280	1230	1170
						12		2970	3880	3060	2820	2710	2580	2330
						1.8		2170	2840	2240	2070	1980	1890	1720
						26		4780	6260	4930	4560	4360	4160	3790
						2.6		2660	3470	2740	2530	2430	2310	2100
						38		5860	7640	6040	5570	5350	5090	4630
						3.2		3000	3920	3090	2860	2740	2610	2380
						46		6610	8630	6810	6300	6040	5750	5240
						3.6		3220	4200	3320	3070	2940	2800	2550
						52	7090	9250	7310	6760	6480	6170	5620	

Size	Rim	Inflated dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommend load, kg (lbs)				
		SW	OD					Speed, km/h (mph)				
		mm/in	mm/in	mm/in	mm/in	Speed	bar	Field	10	25	40	50
						Symbol	psi		6	16	25	31
320/80 R42	W10	320 12.6	1580 62.2	846 33.3	4686 184.5	141A8/ B	0.8	1320	1730	1280	1150	1150
							12	2910	3810	2820	2530	2530
							1.4	1830	2390	1760	1590	1590
							20	4030	5260	3880	3500	3500
							2.2	2380	3110	2300	2070	2070
							32	5240	6850	5070	4560	4560
							2.8	2740	3570	2640	2380	2380
							41	6040	7860	5810	5240	5240
							3.2	2960	3860	2860	2575	2580
							46	6520	8500	6300	5670	5680

Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommend load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
		mm/in	mm/in	mm/in	mm/in	Speed	bar	Field	10	25	40	50	65	70
						Symbol	psi		6	16	25	31	40	43
270/95 R42 (11.2R42)	W9 W8 W10	275 10.8	1581 62.2	740 29.1	4793 188.7	137D/ 140A8	0.8	1090	1430	1130	1040	1000	950	860
							12	2400	3150	2490	2290	2200	2090	1890
							1.6	1640	2150	1690	1570	1500	1430	1300
							23	3610	4740	3720	3460	3300	3150	2860
							2.4	2090	2730	2160	1990	1910	1820	1660
							35	4600	6010	4760	4380	4210	4010	3660
							3.2	2470	3230	2550	2350	2260	2150	1960
							46	5440	7110	5620	5180	4980	4740	4320
							3.6	2650	3450	2730	2520	2420	2300	2090
							52	5840	7600	6010	5550	5330	5070	4600

Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommend load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
		mm/in	mm/in	mm/in	mm/in	Speed	bar	Field	10	25	40	50	65	70
				Symbol	psi		6		16	25	31	40	43	
270/95 R42 (11.2R42)	W9 W8 W10	275 10.8	1581 62.2	740 29.1	4793 188.7	139D/ 142A8	0.8	1100	1440	1140	1050	1010	960	870
							12	2420	3170	2510	2310	2220	2110	1920
							1.6	1660	2160	1710	1580	1510	1440	1310
							23	3660	4760	3770	3480	3330	3170	2890
							2.4	2090	2730	2160	1990	1910	1820	1660
							35	4600	6010	4760	4380	4210	4010	3660
							3.4	2560	3350	2640	2440	2340	2230	2030
							49	5640	7380	5810	5370	5150	4910	4470
							4.0	2790	3650	2880	2660	2550	2430	2210
							57	6150	8040	6340	5860	5620	5350	4870

Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load	Infl. Press	Recommend load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
		mm/in	mm/in	mm/in	mm/in	Speed	bar	Field	10	25	40	50	65	70
				Symbol	psi		6		16	25	31	40	43	
230/95 R42	W8 W7	228 9.0	1505 59.3	709 27.9	4492 176.8	133D/ 136A8	0.8	930	1220	960	890	850	810	740
							12	2050	2690	2110	1960	1870	1780	1630
							1.6	1390	1820	1430	1320	1270	1210	1100
							23	3060	4010	3150	2910	2800	2670	2420
							2.4	1760	2300	1810	1680	1610	1530	1390
							35	3880	5070	3990	3700	3550	3370	3060
							3.4	2150	2810	2220	2050	1960	1870	1700
							49	4740	6190	4890	4520	4320	4120	3740
							4.0	2370	3090	2440	2260	2160	2060	1870
							58	5220	6810	5370	4980	4760	4540	4120

Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum		Infl. Press	Recommend load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
		mm/in	mm/in	mm/in	mm/in	Speed	bar	Field	10	25	40	50	65	70
				Symbol	psi		6		16	25	31	40	43	
230/95 R40	W8 W7	228 9.0	1454 57.2	684 26.9	4339 170.8	132D/ 135A8	0.8	950	1250	980	910	870	830	760
							12	2090	2750	2160	2000	1920	1830	1670
							1.6	1440	1880	1480	1370	1310	1250	1140
							23	3170	4140	3260	3020	2890	2750	2510
							2.4	1820	2370	1870	1730	1660	1580	1440
							35	4010	5220	4120	3810	3660	3480	3170
							3.2	2150	2810	2220	2050	1960	1870	1700
							46	4740	6190	4890	4520	4320	4120	3740
							3.6	2300	3000	2370	2190	2100	2000	1820
							52	5070	6610	5220	4820	4630	4410	4010

Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommend load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
		mm/in	mm/in	mm/in	mm/in	Speed	bar	Field	10	25	40	50	65	70
Symbol	psi	6	16	25	31	40	43							
270/95 R38 (11.2R38)	W9 W8 W10	275 10.8	1479 58.2	689 27.1	4447 175.1	140D/ 143A8	0.8	1020	1340	1050	970	930	890	810
							12	2250	2950	2310	2140	2050	1960	1780
							1.6	1540	2010	1590	1470	1410	1340	1220
							23	3390	4430	3500	3240	3110	2950	2690
							2.4	1960	2550	2010	1860	1790	1700	1550
							35	4320	5620	4430	4100	3940	3740	3410
							3.6	2480	3240	2560	2370	2270	2160	1970
							52	5460	7140	5640	5220	5000	4760	4340
							4	2650	3450	2730	2520	2420	2300	2090
							58	5840	7600	6010	5550	5330	5070	4600
							4.6	2880	3750	2960	2740	2630	2500	2280
67	6340	8260	6520	6040	5790	5510	5020							

Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommend load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
		mm/in	mm/in	mm/in	mm/in	Speed	bar	Field	10	25	40	50	65	70
Symbol	psi	6	16	25	31	40	43							
270/95 R38 (11.2R38)	W9 W8 W10	275 10.8	1479 58.2	689 27.1	4507 177.4	137D/ 140A8	0.8	1020	1340	1050	970	930	890	810
							12	2250	2950	2310	2140	2050	1960	1780
							1.6	1540	2010	1590	1470	1410	1340	1220
							23	3390	4430	3500	3240	3110	2950	2690
							2.4	1960	2550	2010	1860	1790	1700	1550
							35	4320	5620	4430	4100	3940	3740	3410
							3.4	2400	3140	2480	2290	2190	2090	1900
							49	5290	6920	5460	5040	4820	4600	4190
							4	2650	3450	2730	2520	2420	2300	2090
							58	5840	7600	6010	5550	5330	5070	4600

Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommend load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
		mm/in	mm/in	mm/in	mm/in	Speed	bar	Field	10	25	40	50	65	70
Symbol	psi	6	16	25	31	40	43							
270/95 R36 (11.2R36)	W9 W8 W10	275 10.8	1427 56.2	670 26.4	4349 171.2	136D/ 139A8	0.8	1000	1310	1030	950	910	870	790
							12	2200	2890	2270	2090	2000	1920	1740
							1.6	1510	1970	1550	1430	1380	1310	1190
							23	3330	4340	3410	3150	3040	2890	2620
							2.4	1910	2490	1970	1820	1740	1660	1510
							35	4210	5480	4340	4010	3830	3660	3330
							3.4	2350	3060	2420	2230	2140	2040	1860
							49	5180	6740	5330	4910	4710	4490	4100
							4	2580	3360	2650	2450	2350	2240	2040
							58	5680	7400	5840	5400	5180	4930	4490

Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommend load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
		mm/in	mm/in	mm/in	mm/in	Speed	bar	Field	10	25	40	50	65	70
		mm/in	mm/in	mm/in	mm/in	Symbol	psi		6	16	25	31	40	43
230/95 R36	W8 W7	228 9.0	1352 53.2	633 24.9	4035 158.9	130D/ 133A8	0.8	790	1040	820	760	720	690	630
							12	1740	2290	1810	1670	1590	1520	1390
							1.6	1180	1550	1220	1130	1080	1030	940
							23	2600	3410	2690	2490	2380	2270	2070
							2.4	1500	1950	1540	1420	1370	1300	1180
							35	3300	4300	3390	3130	3020	2860	2600
							3.6	1900	2480	1960	1810	1730	1650	1500
							52	4190	5460	4320	3990	3810	3630	3300
							4.0	2010	2630	2070	1920	1840	1750	1590
							58	4430	5790	4560	4230	4050	3850	3500
							4.6	2190	2850	2250	2080	2000	1900	1730
							67	4820	6280	4960	4580	4410	4190	3810

Size	Rim	Infl tire dimension		Static Loaded Radius	Circum	Load Index	Infl. Press	Recommend load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
		mm/in	mm/in	mm/in	mm/in	Speed	bar	Field	10	25	40	50	65	70
		mm/in	mm/in	mm/in	mm/in	Symbol	psi		6	16	25	31	40	43
230/95 R36	W8 W7	228 9.0	1352 53.2	633 24.9	4035 158.9	127D/ 130A8	0.8	780	1020	810	740	710	680	620
							12	1720	2250	1780	1630	1560	1500	1370
							2.0	1350	1760	1390	1280	1230	1170	1060
							29	2970	3880	3060	2820	2710	2580	2330
							2.0	1350	1760	1390	1280	1230	1170	1060
							29	2970	3880	3060	2820	2710	2580	2330
							3.0	1700	2220	1750	1620	1550	1480	1350
							44	3740	4890	3850	3570	3410	3260	2970
							4	2010	2630	2070	1920	1840	1750	1590
							58	4430	5790	4560	4230	4050	3850	3500

Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommend load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
		mm/in	mm/in	mm/in	mm/in	Speed	bar	Field	10	25	40	50	65	70
		mm/in	mm/in	mm/in	mm/in	Symbol	psi		6	16	25	31	40	43
210/95 R36 (8.3 R 36)	W7 W6	214 8.4	1310 51.6	616 24.2	3992 157.2	118D/ 121A8	0.8	700	920	720	670	640	610	560
							12	1540	2030	1590	1480	1410	1340	1230
							1.6	1060	1380	1090	1010	970	920	840
							23	2330	3040	2400	2220	2140	2030	1850
							2.4	1330	1740	1370	1270	1220	1160	1060
							35	2930	3830	3020	2800	2690	2560	2330
							3	1520	1980	1560	1450	1390	1320	1200
							44	3350	4360	3440	3190	3060	2910	2640

Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommend load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
		mm/in	mm/in					Field	10	25	40	50	65	70
									6	16	25	31	40	43
270/95 R32 (11.2 R 32)	W9 W8 W10	275 10.8	1327 52.2	613 24.1	4002 157.6	133D/ 136A8	0.8	930	1220	960	890	850	810	740
							12	2050	2690	2110	1960	1870	1780	1630
							1.6	1390	1820	1430	1320	1270	1210	1100
							23	3060	4010	3150	2910	2800	2670	2420
							2.4	1760	2300	1810	1680	1610	1530	1390
							35	3880	5070	3990	3700	3550	3370	3060
							3.4	2150	2810	2220	2050	1960	1870	1700
							49	4740	6190	4890	4520	4320	4120	3740
							4	2370	3090	2440	2260	2160	2060	1870
							58	5220	6810	5370	4980	4760	4540	4120

	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommend load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
		mm/in	mm/in					Field	10	25	40	50	65	70
									6	16	25	31	40	43
230/95 R32	W9 W8 W10	228 9.0	1251 49.3	582 22.9	3793 149.3	128D/ 131A8	0.8	820	1070	840	780	750	710	650
							12	1810	2360	1850	1720	1650	1560	1430
							1.6	1220	1590	1260	1160	1110	1060	960
							23	2690	3500	2780	2560	2440	2330	2110
							2.4	1540	2010	1590	1470	1410	1340	1220
							35	3390	4430	3500	3240	3110	2950	2690
							3.4	1890	2460	1940	1800	1720	1640	1490
							49	4160	5420	4270	3960	3790	3610	3280
							4	2070	2700	2130	1970	1890	1800	1640
							58	4560	5950	4690	4340	4160	3960	3610

Size	Rim	Infl tire dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. Press	Recommend load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
		mm/in	mm/in					Field	10	25	40	50	65	70
									6	16	25	31	40	43
210/95 R32 (8.3 R 32)	W7 W6	214 8.4	1213 47.8	567 22.3	3696 145.5	117D/ 120A8	0.8	660	860	680	620	600	570	520
							12	1450	1890	1500	1370	1320	1260	1150
							1.6	990	1290	1020	940	900	860	780
							23	2180	2840	2250	2070	1980	1890	1720
							2.4	1250	1640	1290	1190	1140	1090	990
							35	2750	3610	2840	2620	2510	2400	2180
							3.2	1480	1930	1520	1410	1350	1285	1170
							46	3260	4250	3350	3110	2970	2830	2580