

HW-2358

FEATURES & BENEFITS

- 32-bit high performance CPU
- Decoding Precision: 3mil
- Support 1D barcodes on paper
- Manual, Continuous mode
- USB dongle for 2.4GHz wireless
- USB interface, plug and play
- Highly cost-effective, highly sales volume



Application



Supermarket



Medical



Library



Logistic



Warehouse



Shopping mall

Technical Specification

HW-2358 Parameters

	Light Source	Visible laser diode	
		Support paper barcodes	
	Decoding capacity	1D: UPC/EAN、ISBN、ISSN、Code39、Code 39Full ASCII、Code32、Code128、Code11、Code93、Coda bar、industrial 2 of 5、Interleaved 2 of 5、MSI、GS1 Data Bar. etc. all normal 1D	
	Precision	3mil	
Reading performance	Light Source	617nm Visible red LED, white LED	
	Scan Angle	Rotation360° ,tilt±45° ,skew±60°	
	Min Contrast	20%	
	Scanning Speed	500 times/s	
	Typical DOF	5mm-150mm (3mil) 30mm-550mm (15mil)	5mm-400mm (10mil) 30mm-850mm (20mil)
		Performance may be impacted by bar code quality and environmental conditions	
	Interface	2.4G wireless,USB,USB Virtual	
	Working Voltage	DC 5V	
Mechanical and electrical	Current	50mA(working)	10mA(standby)
	Dimensions	158*60*90mm	
	Weight	260g(without cable)	
	Indication	Buzzer & LED	
	Cable length	1.5M	
Environment Request	Working Tem	-20~50℃	
	Storage Tem	-20~60℃	
	Humidity	5%-95%(Non-condensing)	
	Light Immunity	0~100,000Lux	
	Drop Test	1.5M	
	Static Protection	4KV (contact discharge) 10KV (air discharge)	