

## HW-2350

### FEATURES & BENEFITS

- 32-bit high performance CPU
- Decoding Precision: 3mil
- Support 1D barcodes on paper
- Manual, Continuous mode
- USB interface, plug and play
- Highly cost-effective, highly sales volume



### Application



Supermarket



Medical



Library



Logistic



Warehouse



Shopping mall

# Technical Specification

## HW-2350 Parameters

Reading performance	Light Source	Visible laser diode		
		Support paper barcodes		
	Decoding capacity	1D: UPC/EAN、ISBN、ISSN、Code39、Code 39Full ASCII、Code32、Code128、Code11、Code93、Coda bar、industrial 2 of 5、Interleaved 2 of 5、MSI、GS1 Data Bar. etc. all normal 1D		
	Precision	3mil		
	Light Source	617nm Visible red LED, white LED		
	Scan Angle	Rotation360° ,tilt±45° ,skew±60°		
	Min Contrast	20%		
	Scanning Speed	500 times/s		
	Typical DOF	5mm-150mm (3mil)	5mm-400mm (10mil)	
		30mm-550mm (15mil)	30mm-850mm (20mil)	
Performance may be impacted by bar code quality and environmental conditions				
Mechanical and electrical	Interface	USB,USB Virtual		
	Working Voltage	DC 5V		
	Current	50mA(working)	10mA(standby)	
	Dimensions	158*60*90mm		
	Weight	260g(without cable)		
	Indication	Buzzer & LED		
	Cable length	1.5M		
	Environment Request	Working Tem	-20~50℃	
Storage Tem		-20~60℃		
Humidity		5%-95%(Non-condensing)		
Light Immunity		0~100,000Lux		
Drop Test		1.5M		
Static Protection		4KV (contact discharge) 10KV (air discharge)		