

Page 1/11

*

*

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.06.2022

Version number 2 (replaces version 1)

Revision: 30.03.2022

Trade name: <u>MOTIP</u>	WHEELSPRAY SILVER 500 ML
No further relevant in Sector of Use SU21 Consumer uses SU22 Professional u Product category Pain Process category PROC7 Industrial sp PROC11 Non indust Application of the sul	ed uses of the substance or mixture and uses advised against formation available. s: Private households / general public / consumers ses: Public domain (administration, education, entertainment, services, craftsmen) nt remover praying rial spraying bstance / the mixture Spray varnish
1.3 Details of the sup Manufacturer/Suppli European Aerosols B. Wolfraamweg 2 NL-8471 XC Wolvega The Netherlands Tel : +31 (0)561 6944 e-mail: sds-nl@europ	V.* 400
*Formerly known as M	Motip Dupli B.V.
1.4 Emergency teleph +31 (0)561-694400 (0	
SECTION 2: Haz	ards identification
21 Classifianting for	the substance or mixture ing to Regulation (EC) No 1272/2008
Classification accord	29 Extremely flammable aerosol. Pressurised container: May burst if heated.
Classification accord	29 Extremely flammable aerosol. Pressurised container: May burst if heated.
Classification accord	29 Extremely flammable aerosol. Pressurised container: May burst if heated. Causes serious eye irritation. May cause drowsiness or dizziness.
Classification accords flame Aerosol 1 H222-H2 Eye Irrit. 2 H319 STOT SE 3 H336 2.2 Label elements	Causes serious eye irritation.

Page 2/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.06.2022

Version number 2 (replaces version 1)

Revision: 30.03.2022

Trade name: MOTIP WHEELSPRAY SILVER 500 ML

Hazard pictog	(Contd. of pag
^	∧
Jul /	
GHS02 GH	4S07
Signal word L	Danger
Hazard-detern	nining components of labelling:
acetone	
n-butyl acetat	
	nethylethyl acetate
Hazard staten	
	xtremely flammable aerosol. Pressurised container: May burst if heated.
	auses serious eye irritation.
	lay cause drowsiness or dizziness.
Precautionary	
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P260	Do not breathe spray.
P264	Wash hands thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves / eye protection.
P305+P351+P	P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, i
	present and easy to do. Continue rinsing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P337+P313	If eye irritation persists: Get medical advice/attention.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of contents / container in accordance with regional regulations.
Additional inf	
	pated exposure may cause skin dryness or cracking.
	plosive mixtures possible without sufficient ventilation.
2.3 Other haz	
	T and vPvB assessment
PBT: Not app	
vPvB: Not app	blicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

*

• Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

0		
CAS: 67-64-1	acetone	25-<50%
EINECS: 200-662-2	🚸 Flam. Liq. 2, H225	
Index number: 606-001-00-8	🚯 Eye Irrit. 2, H319; STOT SE 3, H336	
Reg.nr.: 01-2119471330-49	<i>ÉUH066</i>	
		Contd. on page 3)

GB

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.06.2022

Version number 2 (replaces version 1)

Revision: 30.03.2022

Trade name: MOTIP WHEELSPRAY SILVER 500 ML

CAS: 74-98-6	propane	10-<12.5%
EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21	Flam. Gas 1A, H220 Press. Gas (Comp.), H280	_
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32	butane (containing < 0,1 % butadiene (203-450-8))	5-<10%
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27	isobutane (containing < 0,1 % butadiene (203-450-8)) Flam. Gas IA, H220 Press. Gas (Comp.), H280	5-<10%
CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1 Reg.nr.: 01-2119485493-29	n-butyl acetate Flam. Liq. 3, H226 STOT SE 3, H336 EUH066	5-<10%
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29	2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226 STOT SE 3, H336	5-<10%
CAS: 7429-90-5 EINECS: 231-072-3 Index number: 013-002-00-1 Reg.nr.: 01-2119529243-45	aluminium powder (stabilised)	<2.5%
EC number: 905-588-0 Reg.nr.: 01-2119488216-32-xxxx	xylene Flam. Liq. 3, H226 STOT RE 2, H373; Asp. Tox. 1, H304 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	<2.5%
CAS: 9004-70-0	cellulose nitrate	<2.5%

• Additional information:

CAS 9004-70-0: GB CLP Note T

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

• 4.1 Description of first aid measures

- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- · After eye contact:

*

*

- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- \cdot 4.2 Most important symptoms and effects, both acute and delayed
- No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- \cdot 5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

(Contd. on page 4)

GB

Page 4/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.06.2022

Version number 2 (replaces version 1)

Revision: 30.03.2022

(Contd. of page 3)

GB

Trade name: MOTIP WHEELSPRAY SILVER 500 ML

- · 5.3 Advice for firefighters -
- · Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

 6.1 Personal precautions, protective equipment and emergency procedures Mount respiratory protective device.
 Wear protective equipment. Keep unprotected persons away.
 Keep away from ignition sources.

· 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

- 6.3 Methods and material for containment and cleaning up: Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
- 6.4 Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

SECTION 7: Handling and storage

• 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.

- Information about fire and explosion protection: Do not spray onto a naked flame or any incandescent material. Keep ignition sources away - Do not smoke. Keep respiratory protective device available.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles:
- Observe official regulations on storing packagings with pressurised containers.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 2 B
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control	parameters
-------------	------------

\cdot Ingredients with limit values that require monitoring at the workplace:		
67-64	-1 acetone	
WEL	Short-term value: 3620 mg/m³, 1500 ppm	
	Long-term value: 1210 mg/m³, 500 ppm	
106-9	7-8 butane (containing < 0,1 % butadiene (203-450-8))	
WEL	Short-term value: 1810 mg/m ³ , 750 ppm	
	Long-term value: 1450 mg/m³, 600 ppm	
	Carc (if more than 0.1% of buta-1.3-diene)	
123-8	6-4 n-butyl acetate	
WEL	Short-term value: 966 mg/m³, 200 ppm	
	Long-term value: 724 mg/m³, 150 ppm	
108-6	5-6 2-methoxy-1-methylethyl acetate	
WEL	Short-term value: 548 mg/m³, 100 ppm	
	Long-term value: 274 mg/m³, 50 ppm	
	Sk	
	(Contd. on page 5)	

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.06.2022

Version number 2 (replaces version 1)

Revision: 30.03.2022

Trade name: MOTIP WHEELSPRAY SILVER 500 ML

7429-	90-5 aluminium powder (stabilised) (Contd. of page
	Long-term value: 10* 4** mg/m ³
,, EE	*inhalable dust ** respirable dust
xylen	
-	Short-term value: 441 mg/m³, 100 ppm
,, LL	Long-term value: 220 mg/m ³ , 50 ppm
	Sk; BMGV
Ingre	dients with biological limit values:
xylen	e
BMG	V 650 mmol/mol creatinine
	Medium: urine
	Sampling time: post shift
	Parameter: methyl hippuric acid
Addit	ional information: The lists valid during the making were used as basis.
8.2 E.	xposure controls
	opriate engineering controls No further data; see item 7.
	idual protection measures, such as personal protective equipment
	ral protective and hygienic measures:
	uitable respiratory protective device in case of insufficient ventilation. away from foodstuffs, beverages and feed.
	diately remove all soiled and contaminated clothing
	hands before breaks and at the end of work.
	ot inhale gases / fumes / aerosols.
	contact with the eyes and skin.
	contact with the eyes.
Respi	ratory protection:
	In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
Filter	A2/P3
Hand	protection
П	
1112	Protective gloves
Mate	rial of gloves
	rubber, BR
	election of the suitable gloves does not only depend on the material, but also on further marks of
qualit	ty and varies from manufacturer to manufacturer.
	tration time of glove material
	rubber gloves with a thickness of 0.4 mm are resistant to: one: 480 min
	one: 480 min l acetate: 60 min
•	l acetate: 170 min
	ne: 42 min
-	rubber gloves with a thickness of 0.4 mm are solvent resistant for 42-480 minutes. As protective
	ire, we recommend that users and responsible persons for work safety assume solvent resistance leng
	minutes. Considering the data in section 3 of this SDS, one can assume longer resistance length in
partic	(Contd. on page
	(Cond. of page

2

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.06.2022

Version number 2 (replaces version 1)

Revision: 30.03.2022

Trade name: MOTIP WHEELSPRAY SILVER 500 ML

(Contd. of page 5) · Eye/face protection Tightly sealed goggles **SECTION 9: Physical and chemical properties** · 9.1 Information on basic physical and chemical properties · General Information · Physical state Aerosol · Colour: Different according to colouring · Odour: Solvent-like Not determined. · Odour threshold: • Melting point/freezing point: Undetermined. · Boiling point or initial boiling point and boiling Not applicable, as aerosol. range · Flammability Not applicable. · Lower and upper explosion limit 1.7 Vol % (74-98-6 propane) · Lower: · Upper: 13 Vol % (67-64-1 acetone) · Flash point: Not applicable, as aerosol. 333 °C (631.4 °F) (108-65-6 2-methoxy-1-methylethyl · Ignition temperature: acetate) Not determined. · Decomposition temperature: $\cdot pH$ Not determined. · Viscosity: · Kinematic viscosity Not determined. · Dynamic: Not determined. · Solubility Not miscible or difficult to mix. · water: · Partition coefficient n-octanol/water (log value) Not determined. · Vapour pressure at 20 °C (68 °F): 3500 hPa (2625.2 mm Hg) · Density and/or relative density • Density at 20 •C (68 •F): 0.7 g/cm³ (5.8 lbs/gal) Not determined. · Relative density Not determined. · Vapour density • 9.2 Other information · Appearance: · Form: Aerosol · Important information on protection of health and environment, and on safety. Not determined. · Explosive properties: · Solvent content: · Organic solvents: 93.6 % · Water: 0.2 % \cdot VOC (EC) ---688.6 g/l · VOC-EU% 93.58 % · Solids content: 6.3 % · Change in condition Not applicable. · Evaporation rate · Information with regard to physical hazard classes · Explosives Void

(Contd. on page 7)

GB

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.06.2022

Version number 2 (replaces version 1)

Revision: 30.03.2022

GB

Trade name: MOTIP WHEELSPRAY SILVER 500 ML

	(Contd. of page 6)
· Flammable gases	Void
· Aerosols	Extremely flammable aerosol. Pressurised container:
	May burst if heated.
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flamn	nable
gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

*

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

· 10.3 Possibility of hazardous reactions No dangerous reactions known.

• 10.4 Conditions to avoid No further relevant information available.

- \cdot 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute	toxicity
-------	----------

· LD/LC50	· LD/LC50 values relevant for classification:		
67-64-1 ac	67-64-1 acetone		
Oral	LD50	5800 mg/kg (rat)	
Dermal	LD50	>15800 mg/kg (rabbit)	
Inhalative	LC50 / 4h	76 mg/l (rat)	
123-86-4 n	123-86-4 n-butyl acetate		
Oral	LD50	10800 mg/kg (rat) (OECD 401)	
Dermal	LD50	>17600 mg/kg (rabbit)	
Inhalative	LC50 / 4 h	>21 mg/m3 (rat)	
108-65-62	-methoxy-1	-methylethyl acetate	
Oral	LD50	8530 mg/kg (rat)	
Dermal	LD50	>5000 mg/kg (rabbit)	
Inhalative	LC50 / 4 h	>10000 mg/m3 (rat)	
xylene	xylene		
Oral	LD50	3523 mg/kg (rat)	
Dermal	LD50	2000 mg/kg (rabbit)	
Inhalative	LC50 / 4 h	29000 mg/m3 (rat)	
		(Contd. on page 8)	

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.06.2022

Version number 2 (replaces version 1)

Revision: 30.03.2022

(Contd. of page 7)

Trade name: MOTIP WHEELSPRAY SILVER 500 ML

- · Skin corrosion/irritation No irritant effect.
- Serious eye damage/irritation Causes serious eye irritation.
- Respiratory or skin sensitisation No sensitising effects known.
- STOT-single exposure May cause drowsiness or dizziness.
- 11.2 Information on other hazards
- Endocrine disrupting properties None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

*

*

· Aquatic toxicity:

67-64-1 acetone

- LC50/96h 8300 mg/l (fish)
- EC50/96h 7200 mg/l (algae)
- LC50 / 48 h 8450 mg/l (crustacean (water flea))

108-65-6 2-methoxy-1-methylethyl acetate

EC50 / 48 h >500 mg/l (daphnia magna)

LC50 / 96 h 100-180 mg/l (oncorhynchus mykiss / Regenbogenforelle)

xylene

EC50 / 48 h 7.4 mg/l (daphnia magna)

- LC50/96 h 13.5 mg/l (fish)
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- Additional ecological information:

· General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation:

Disposal must be made according to official regulations. Disposal must be made according to official regulations.

(Contd. on page 9)

Page 9/11

*

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.06.2022

Version number 2 (replaces version 1)

Revision: 30.03.2022

Trade name: MOTIP WHEELSPRAY SILVER 500 ML

(Contd. of page 8)

GB

SECTION 14: Transport information	
14.1 UN number or ID number ADR, IMDG, IATA	UN1950
14.2 UN proper shipping name	1050 / ED 0001 0
ADR IMDG	1950 AEROSOLS AEROSOLS
IATA	AEROSOLS AEROSOLS, flammable
14.3 Transport hazard class(es)	
ADR	
Class	2 5F Gases.
Label	2.1
Class	2.1 Gases.
Class Label	2.1 Gases. 2.1
14.4 Packing group	
ADR, IMDG, IATA	not regulated
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user Hazard identification number (Kemler code): EMS Number: Stowage Code	Warning: Gases. - F-D,S-U SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1litre:Segregation as for class 9. Stow "separated from" class1 except for division 1.4.For AEROSOLS with a capacity above 1 litre:Segregation as for the appropriate subdivision of class2.For WASTE AEROSOLS:Segregation as for the appropriate subdivision of class2.Segregation as for the appropriate subdivision of class2.Segregation as for the appropriate subdivision of class2.
14.7 Maritime transport in bulk according to IM instruments	O Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
	Code: E0

Page 10/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.06.2022

Version number 2 (replaces version 1)

Revision: 30.03.2022

Trade name: MOTIP WHEELSPRAY SILVER 500 ML

	(Contd. of page 9)
	Not permitted as Excepted Quantity
· Transport category	2
• Tunnel restriction code	D
· IMDG	
\cdot Limited quantities (LQ)	1L
\cdot Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
	Code: E0
	Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- \cdot Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · National regulations:
- · Other regulations, limitations and prohibitive regulations

· Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients is listed.

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H201 Explosive; mass explosion hazard.
- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H228 Flammable solid.
- H261 In contact with water releases flammable gases.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.

EUH066 Repeated exposure may cause skin dryness or cracking.

· Department issuing SDS: R&D legislation and regulatory advisor

· Contact: e-mail: sds-nl@european-aerosols.com

• Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

(Contd. on page 11)

GB

Page 11/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.06.2022

Version number 2 (replaces version 1)

Revision: 30.03.2022

Trade name: MOTIP WHEELSPRAY SILVER 500 ML

 IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative Expl. 1.1: Explosives – Division 1.1 Flam. Gas 1A: Flammable gases – Category 1A Aerosol 1: Aerosols – Category 1 Press. Gas (Comp.): Gases under pressure – Compressed gas 	
EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative Expl. 1.1: Explosives – Division 1.1 Flam. Gas 1A: Flammable gases – Category 1A Aerosol 1: Aerosols – Category 1	
EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative Expl. 1.1: Explosives – Division 1.1 Flam. Gas 1A: Flammable gases – Category 1A Aerosol 1: Aerosols – Category 1	
CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative Expl. 1.1: Explosives – Division 1.1 Flam. Gas 1A: Flammable gases – Category 1A Aerosol 1: Aerosols – Category 1	
VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative Expl. 1.1: Explosives – Division 1.1 Flam. Gas IA: Flammable gases – Category IA Aerosol 1: Aerosols – Category 1	
LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative Expl. 1.1: Explosives – Division 1.1 Flam. Gas 1A: Flammable gases – Category 1A Aerosol 1: Aerosols – Category 1	
LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative Expl. 1.1: Explosives – Division 1.1 Flam. Gas 1A: Flammable gases – Category 1A Aerosol 1: Aerosols – Category 1	
PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative Expl. 1.1: Explosives – Division 1.1 Flam. Gas 1A: Flammable gases – Category 1A Aerosol 1: Aerosols – Category 1	
SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative Expl. 1.1: Explosives – Division 1.1 Flam. Gas 1A: Flammable gases – Category 1A Aerosol 1: Aerosols – Category 1	
vPvB: very Persistent and very Bioaccumulative Expl. 1.1: Explosives – Division 1.1 Flam. Gas 1A: Flammable gases – Category 1A Aerosol 1: Aerosols – Category 1	
Expl. 1.1: Explosives – Division 1.1 Flam. Gas 1A: Flammable gases – Category 1A Aerosol 1: Aerosols – Category 1	
Flam. Gas 1A: Flammable gases – Category 1A Aerosol 1: Aerosols – Category 1	
Aerosol 1: Aerosols – Category 1	
Press. Gas (Comp.): Gases under pressure – Compressed gas	
Flam. Liq. 2: Flammable liquids – Category 2	
Flam. Liq. 3: Flammable liquids – Category 3	
Flam. Sol. 1: Flammable solids – Category 1	
Water-react. 2: Substances and mixtures which in contact with water emit flammable gases – Category 2	
Acute Tox. 4: Acute toxicity – Category 4	
Skin Irrit. 2: Skin corrosion/irritation – Category 2	
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2	
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3	
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2	
Asp. Tox. 1: Aspiration hazard – Category 1	
* Data compared to the previous version altered.	
	GB