




DOMINO SPC ACOUSTIC

Technical datasheet

| Technical parameter | Standard | Unit | Result |
|-----------------------------|---|-------------------|---|
| DESCRIPTION | | | |
| Construction | Rigid modular flooring with SPC core | | |
| Total thickness | EN ISO 24346 | mm | 4,0 + 1,0 |
| Wear layer thickness | EN ISO 24340 | mm | 0,4 |
| Plank size | EN ISO 24341 | mm | 180 x 1250 |
| Tile size | EN ISO 24341 | mm | 310 x 620 |
| Thickness of IXPE foam | EN ISO 24340 | mm | 1,0 |
| Total weight | EN ISO 23997 | kg/m ² | 7,8 |
| CLASSIFICATION | | | |
| European classification | EN 685 | class | 23/32/41 |
| PERFORMANCE | | | |
| Abrasion group | MSZ EN 660-1 | class | T |
| Residual indentation | EN ISO 24343 | max. mm | 0,1 |
| Dimensional stability | EN ISO 23999 | max.% | 0,25 |
| Wear resistance IP method A | EN 13329 | min. cycles | 1200 |
| Fire resistance | EN 13501-1 | class | Bfl-s1 |
| Slip resistance | DIN 51130 | | R10 |
| | EN 13893 | | DS |
| Impact sound reduction | EN ISO 717-2 | dB | 21 |
| Chemical resistance | EN ISO 26987 | | ✓ |
| Light fastness | EN 20105 B02 | grade | 6 |
| Surface treatment |  | | iGuard PUR Surface |
| VOC | ISO 16000 | | ✓ |
| Environmental attributes |   | | Phthalate, Solvent and Heavy metal free product |
| Content of PCP | EN 12673 | | does not contain |
| Formaldehyde emission | ENV 717-1 | | E1 (no emission) |
| Warranty | Commercial | year | 5 |
| | Residential | year | 10 |
| CE MARKING | EN 14041 | | ✓ |