



Spectra 40 C multi alloy films are carefully designed to act selectively on the spectrum of solar light, offering the best possible compromise between transparency and performance. Soapy water solution (ref. sun pose 0808 or 0805 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film. To find out the cleaning frequency, see chapter 2 of our gathering of information.

Certifications



Warranty SOLAR SCREEN®

10 years
See the 'New guarantees for outdoor products' notice



Fire-Resistance Rating

M1



Storage From -5°C To +40°C

3 years



Reach Rohs Compliant

Respected



Widths Available

152cm 183cm

Construction

1. Hard scratch resistant layer, for durability and ease of maintenance during window cleaning
2. High optical quality polyester, with anti IR metal particles deposit
3. Bonding adhesive
4. High optical quality polyester
5. PS adhesive, glass polymerization within 15 days
6. Protection release liner, disposable after installation

Maintenance Instructions

Soapy water solution (ref. 600-F0355 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film. To prevent a possible oxidation of the metal alloys, it is mandatory to use our sealing varnish (reference number 0771) on the corners of the film, after installation._

Technical Datasheet

Ultraviolet Transmission	1%
Visible Light Transmission	62%
Reflection Of External Visible Light	14%
Reflection Of Internal Visible Light	14%
Total Solar Energy Rejected	57%
Total Solar Energy Rejected 2*	54%
Solar Ratio :	
Solar Energy Reflection	34%
Solar Energy Absorption	29%
Solar Energy Transmission	37%
Reduction In Solar Glare	34%
G-Value	0.44
U-Value	4.9
Rejected Infrared (760-2500 Nm)	+/-80%
Shading Coefficient	0.5
Installation Type	Interior
Roll Length	30.5 meters m
Film Composition	PET
Thickness	55µ
Colour From The Outside	LIGHT CHAMPAGNE

Installation Advice

Vertical position and standard glass surface*

Clear Single Pane	✓
Tinted Single Pane	✓
Reflective Tinted Single Pane	✓
Clear Double Pane	✓
Tinted Double Pane	✓
Reflective Tinted Double Pane	✓
Gas-Filled Double Pane - Low E	!
Stadip Ext. Clear Double Pane	✓
Stadip Int. Clear Double Pane	!

✓ Yes ✗ Not Recommended ! Caution

*Recommendations provided on the basis of a glazed surface covering up to 2.5m², contact us for definitive details or to obtain a thermal chock analysis report.

The information on this data sheet is not binding; SOLAR SCREEN® reserves the right to change the composition of its products at any time. Please consult our warranty terms and general sales conditions.