

CELEST

Presented in a black tinted floral motif, the Castel decorative film allows you to tastefully customize windows and partitions.



SOLAR SCREEN® Warranty
5 YEARS



Fire-resistance rating
M1



Storage from -5°C to +40°C
3 YEARS



REACH RoHS compliant
RESPECTED

WIDTHS AVAILABLE:

↔ **152 cm**

TECHNICAL DATASHEET

Data calculated based on film applied to clear glass 3 mm thick (*on double glazing 4-16-4)

Ultraviolet transmission	NC %
Visible light transmission	- %
Reflection of external visible light	- %
Reflection of internal visible light	- %
Total solar energy rejected	- %
Total solar energy rejected 2*	- %
Solar ratio :	
Solar energy reflection	- %
Solar energy absorption	- %
Solar energy transmission	- %
Reduction in Solar Glare	- %
g-value	-
u-value	-
Shading coefficient	NC


Installation type : Internal application

Roll length	50 m
PET / PVC composition	PET
Thickness	40 µ

Colour : BLACK

CONSTRUCTION

1. High optical quality polyester with printed design
2. PS adhesive, glass polymerization within 15 days
3. Protection release liner, disposable after installation



INSTALLATION ADVICE

Vertical installation and on standard glass surface**

Clear single pane	✓
Tinted single pane	✓
Reflective tinted single pane	✓
Clear double pane	✓
Tinted double pane	✓
Reflective tinted double pane	✓
Gas-filled double pane - Low E	✓
STADIP EXT. clear double pane	✓
STADIP INT. clear double pane	!

✓ Yes ! Caution ✗ Not recommended

*Recommendations provided on the basis of a glazed surface covering up to 2.5m², contact us for definitive details or to obtain a thermal shock analysis report.

MAINTENANCE INSTRUCTIONS

Soapy water solution (ref. 0805 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

Non-contractual data, SOLAR SCREEN® reserves the right to modify the composition of its films at any time. Consult our guarantee vouchers and our general conditions of sale.