



Silver 480 C films are highly effective at reducing solar heat gain, whilst at the same time continuing to allow most natural light to pass through. Solar glare is greatly diminished and its one-way mirror aspect guarantees privacy from prying eyes, whilst affording a modern feel to the exterior of a building. A highly resilient film, it helps to secure your windows by ensuring that the glass does not shatter in the event of an impact or explosion. Conforms to European Standard EN 12600.

Certifications



Warranty SOLAR SCREEN®

10 years
See the 'New guarantees for outdoor products' notice



Fire-Resistance Rating

M1



Storage From -5°C To +40°C

3 years



Reach RoHS Compliant

Respected



European Standard EN 12600

2B2



Widths Available

122cm 152cm

Construction

1. Hard scratch resistant layer, for durability and ease of maintenance during window cleaning
2. High optical quality polyester, with anti IR metal particles deposit
3. Bonding adhesive
4. High optical quality polyester
5. Reinforced PS Adhesive to accompany the elasticity of the film in case of impact, glass polymerization within 30 days
6. Protection release liner, disposable after installation

Maintenance Instructions

Safety film with reinforced PS adhesive requiring a suitable application solution (Film On ref 600-F0355 and 2cl/litre of water) and a suitable safety squeegee 150-054/150-055/150-056. Do not clean for at least 1 month and do not apply stickers or other adhesives to the film.

Technical Datasheet

Ultraviolet Transmission	1%
Visible Light Transmission	18%
Reflection Of External Visible Light	60%
Reflection Of Internal Visible Light	58%
Total Solar Energy Rejected	80%
Total Solar Energy Rejected 2*	75%
Solar Ratio :	
Solar Energy Reflection	56%
Solar Energy Absorption	33%
Solar Energy Transmission	11%
Reduction In Solar Glare	83%
G-Value	0.2
U-Value	5.1
Shading Coefficient	0.2
Installation Type	Interior
Roll Length	30.5 meters m
Film Composition	PET
Thickness	125µ
Colour From The Outside	SILVER

Installation Advice

Vertical position and standard glass surface*

Clear Single Pane	✓
Tinted Single Pane	✓
Reflective Tinted Single Pane	✓
Clear Double Pane	✓
Tinted Double Pane	✗
Reflective Tinted Double Pane	✓
Gas-Filled Double Pane - Low E	!
Stadip Ext. Clear Double Pane	!
Stadip Int. Clear Double Pane	✗

✓ Yes ✗ Not Recommended ! Caution

*Recommendations provided on the basis of a glazed surface covering up to 2.5m², contact us for definitive details or to obtain a thermal chock analysis report.

The information on this data sheet is not binding; SOLAR SCREEN® reserves the right to change the composition of its products at any time. Please consult our warranty terms and general sales conditions.

