



Husqvarna XP Synthetic

Husqvarna's fully synthetic, biodegradable and low smoke XP Synthetic 2-stroke oil is developed for tough use with high loads and engine speed.

XP Synthetic contains a high performance additive package and is virtually ashless. XP Synthetic gives extremely good lubrication, a cleaner engine and less deposits on the piston and in the crankcase compared to competing oils.

XP Synthetic is an appropriate choice for all Husqvarna 2-stroke products.

HUSQVARNA VEF VERIFIED ENGINE FORMULA

Nobody knows our 2-stroke engines better than we do. Husqvarna's 2-stroke oils and 2-stroke fuels have been tested and optimized to work perfectly with our engines. Our 2-stroke oils are therefore awarded with **VEF – Verified Engine Formula**.

CHARACTERISTIC	TYPICAL RESULT	TEST METHOD	PNC	NAME
Appearance	Clear, blue and free from sediments and other impurities	Visual examination	578180303	2T OIL XP Synthetic 0.1L
Density at 20°C [kg/dm ³]	0,895	ISO 12185	578037003	2T OIL XP Synthetic 1L Dosage
Flash Point [°C]	94	ISO 2719	578037103	2T OIL XP Synthetic 4L
Pour Point [°C]	-42	ISO 3016	578180003	2T OIL XP Synthetic 10L
Total Acid Number [mg KOH/g]	0,5	ISO 6619	578180403	2T OIL XP Synthetic 208L
Total Base Number [mg KOH/g]	2,5	ISO 3771		
Kinematic viscosity [mm ² /s]				
at 100° C	7,8			
at 40° C	39			
Dynamic viscosity at -25°C [mPa.S]	2225	NFT 60152		
Sulphated ash – Mass fraction [%]	0,1	ISO 3987		
Biodegradability [%]	64	OECD 301B		
Renewable carbon content [%]	39			
Shelf life [years]	2			

XP Synthetic exceeds the performance level of ISO L-EGD and JASO FD standards.

Safety data sheet available at Husqvarna.com