

MAT FROST PVC

Design Opalescent adhesive film



Mat Frost PVC privacy films are designed to provide protection against the scrutiny of prying eyes. Whilst completely opalescent, the film still allows most natural light to pass through. With disposable plastic liner or silicone paper liner for digital cutting.

Certifications



Warranty SOLAR SCREEN® 5 ans

See the 'New guarantees for outdoor products' notice



Fire-Resistance Rating



Storage From -5°C To +40°C 3 ans



Reach Rohs Compliant Respected



Widths Available

152cm

Construction

- 1. 100μ Frosted monomer PVC
- Half Permanent Adhesive, allowing the "degassing" of the actual surface, and limits the adhesive transfer during removal
- 3. Disposable plastic liner or silicone paper liner for digital cutting

Maintenance Instructions

Soapy water solution (ref. 600-F0355 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

Technical Datasheet

Ultraviolet Transmission	>25%
Visible Light Transmission	76%
Reflection Of External Visible Light	15%
Reflection Of Internal Visible Light	15%
Total Solar Energy Rejected	18%
Total Solar Energy Rejected 2*	19%
Solar Ratio : Solar Energy Reflection	10%
•	
Solar Energy Absorption	17%
Solar Energy Transmission	73%
Reduction In Solar Glare	20%
G-Value	0.77
U-Value	5.6
Shading Coefficient	
Installation Type	Interior
Roll Length	30.5 mètres m
Film Composition	PVC
Thickness	100μ
Colour From The Outside	FROSTED

Installation Advice

Vertical position and standard glass surface*

С	Clear Single Pane	~
Т	ïnted Single Pane	~
R	Reflective Tinted Single Pane	~
С	Clear Double Pane	~
Т	inted Double Pane	~
R	Reflective Tinted Double Pane	~
G	as-Filled Double Pane - Low E	✓
S	Stadip Ext. Clear Double Pane	✓
S	Stadip Int. Clear Double Pane	✓

✓ Yes

X Not Recommended

Caution

Cautio

*Recommendations provided on the basis of a glazed surface covering up to $2.5 \, \text{m}^2$.

The information on this data sheet is not binding; SOLAR SCREEN® reserves the right to change the composition of its products at any time. Please consult our warranty terms and general sales conditions.