



The Black Opaque blackout film provides comprehensive two-way privacy. Blocking almost all light penetration, this film provides an immediate and effective privacy solution, ideally suited for concealing stock, a storage area, etc.

### Certifications



**Warranty SOLAR SCREEN®**  
 10 years  
 See the 'New guarantees for outdoor products' notice



**Fire-Resistance Rating**  
 M1



**Storage From -5°C To +40°C**  
 3 years



**Reach Rohs Compliant**  
 Respected



**Widths Available**  
 152cm

### Construction

1. Hard scratch resistant layer, for durability and ease of maintenance during window cleaning
2. Dyed polyester without optical distortion
3. Bonding adhesive
4. High optical quality polyester
5. PS adhesive, glass polymerization within 15 days
6. Protection release liner, disposable after installation

### Maintenance Instructions

Soapy water solution (ref. 600-F0355 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

### Technical Datasheet

Ultraviolet Transmission	1%
Visible Light Transmission	<1%
Reflection Of External Visible Light	13%
Reflection Of Internal Visible Light	13%
Total Solar Energy Rejected	72%
Total Solar Energy Rejected 2*	65%
Solar Ratio :	
Solar Energy Reflection	11%
Solar Energy Absorption	88%
Solar Energy Transmission	1%
Reduction In Solar Glare	100%
G-Value	0.26
Shading Coefficient	0.2
Installation Type	Interior
Roll Length	30.5 meters m
Film Composition	PET
Thickness	60µ
Colour From The Outside	BLACK

### Installation Advice

Vertical position and standard glass surface\*

Clear Single Pane	!
Tinted Single Pane	×
Reflective Tinted Single Pane	✓
Clear Double Pane	!
Tinted Double Pane	×
Reflective Tinted Double Pane	✓
Gas-Filled Double Pane - Low E	×
Stadip Ext. Clear Double Pane	×
Stadip Int. Clear Double Pane	×

✓ Yes ✗ Not Recommended ! Caution

\*Recommendations provided on the basis of a glazed surface covering up to 2.5m², contact us for definitive details or to obtain a thermal chock analysis report.

The information on this data sheet is not binding; SOLAR SCREEN® reserves the right to change the composition of its products at any time. Please consult our warranty terms and general sales conditions.