



HOME

ABOUT US

PRODUCTS

GREEN SOLUTIONS

FOCUS ARCHIVE

NEWS ARCHIVE

DOWNLOAD

CONTACT

English



Home / 3000/3600 rpm / LAMPO PRO SERIES - GASOLINE AIR COOLED

PRINT THIS PAGE

3000 rpm 50 Hz – $\cos \phi$ 0,8 230V – 400/230V 3600 rpm 60 Hz – $\cos \phi$ 0,8 **voltage on request**

LAMPO PRO SERIES








STANDARD EQUIPMENT

- Protection frame with metal sheet top cover
- Lifting eye
- Exhaust gas silencer
- Air filter
- Fuel tank 20 lt
- Distribution panel with output sockets with circuit breaker, 0,03 A ELCB optional
- Low oil level protection
- 12V Battery on electric started models

POWERED BY
HONDA™


LAMPO PRO SERIES

MODEL	kVA max	kVA cont	kVA max	kVA cont	Starting	Brand		Cylinder	cm3	Hp (max) 3600	Cons. 75%(h/l)	Standard panel	Automatic panel						
	50 Hz	60 Hz	Engine Technical Data											Tank l	L	W	H	Kg	LWA (•)
SINGLE-PHASE																			
G5000HMP-P	4,5	4,1	5,4	5	M	Honda	GX270	1	270	9	1,5	QM105	--	20	75	56	62	77	95
G5000HMPE-P	4.5	4.1	5.4	5	E	Honda	GX270	1	270	9	1.5	QM105	QS32 ATS	20	75	56	62	84	95
G7000HMP-P	7.2	6.5	8	7.2	M	Honda	GX390	1	389	13	1.9	QM105	--	20	75	56	62	88	96
G7000HMPE-P	7.2	6.5	8	7.2	E	Honda	GX390	1	389	13	1.9	QM105	QS32 ATS	20	75	56	62	95	96
G12010HMPE-P	11.5	10.5	--	--	E	Honda	GX630	2	688	20.8	4	QM107	QS32 ATS	20	99	55	67	123	98*
G13010HMPE-P	13	12	--	--	E	Honda	GX690	2	688	22.1	7	QM107	QS32 ATS	20	99	55	67	133	98*
THREE-PHASE																			
G6000HTP-P	5.4	4.9	6.5	5.6	M	Honda	GX270	1	270	9	1.5	QM305	--	20	75	56	62	77	95
G6000HTPE-P	5.4	4.9	6.5	5.6	E	Honda	GX270	1	270	9	1.5	QM305	QS32 ATS	20	75	56	62	84	95
G8000HTP-P	7.5	6.8	8.3	7.5	M	Honda	GX390	1	389	13	1.9	QM305	--	20	75	56	62	88	96
G8000HTPE-P	7.5	6.8	8.3	7.5	E	Honda	GX390	1	389	13	1.9	QM305	QS32 ATS	20	75	56	62	95	96
G12510HTPE-P	12	10.9	--	--	E	Honda	GX630	2	688	20.8	4	QM307	QS32 ATS	20	99	55	67	123	98*
G13510HTPE-P	13	12	--	--	E	Honda	GX690	2	688	22.1	7	QM307	QS32 ATS	20	99	55	67	133	98*

Edit Table

Legend: * Noise level not compliant with European regulation 2000/14/CE (•) = Tested value; noise level compliant with European regulation 2000/14/CE


> CONTROL PANEL



QM 105




QM 305



QM 107



QM 307



QS32 ATS



BRUNO SRL

S.S. 91 Km 0,600 – 83035 Grottaminarda (AV) –
ITALY | VAT IT 01713250643

ITALY SALES DEPARTMENT

Tel: +39 0825 421035

Fax: +39 0825 421654

E mail: venditeitalia@brunogenerators.it

EXPORT DEPARTMENT

Tel. +39.0825.421005

Fax.+39.0825.426169

export@brunogenerators.it