

PUBLIC ADDRESS / SPEAKERS / SURFACE

## BSP-121T

100 V LINE TRANSFORMER, LOW IMPEDANCE LOUDSPEAKER PAIR



ESPECIALLY RECOMMENDED IN:



All sectors

### DESCRIPTION

Pair of ultraslim surface mount loudspeakers, manufactured with special low profile loudspeakers. Special slim and discreet design.



+ Info:  
<https://fonestar.com/BSP-121T>

## TECHNICAL CHARACTERISTICS

FEATURES	Pair of ultraslim low impedance loudspeakers with 100 V line transformer.
POWER	30 W maximum. 20 W RMS
LOUDSPEAKERS	1 x 5 ¼" ultraslim woofer: Neodymium magnet 1 tweeter
RESPONSE	75-20,000 Hz
IMPEDANCE	High Z 100 V line: 1,650 Ohm (6 W), 3,300 Ohm (3 W) Low Z: 4 Ohm
SENSITIVITY	87 dB at 1 W/1 m
SOUND PRESSURE	98 dB at maximum power at 1 m
CROSSOVER	2 ways
CONNECTORS	Spring terminals
COLOUR	Black (RAL 9017)
DIMENSIONS	184 x 272 x 37 mm depth
WEIGHT	2 x 1.2 kg



+ Info:  
<https://fonestar.com/BSP-121T>