

- Measuring force: ≤ 0.01 N.

NEW



Item No.	Measuring range/mm	Resolution mm	Insert length/mm	Price EUR
910.087	0.5	0.01	13	
Option:				
836.535	Spare battery			0.70

Lever-type digital test indicator

Lever-type digital test indicator with tolerance judgement. Suitable for measurements in both directions. Equipped with three dovetail mountings.

- Measuring range: up to 0.5 mm.
- Resolution: 0.001 mm.
- Accuracy: ±0.02 mm.
- mm/inch conversion.
- On/off switch.
- Reset.
- Measuring force: ≤ 0.6 N.
- With dovetail joint and clamping stems ø6 and ø8 mm.
- Ruby stylus tip: ø2 mm.



- 230° adjustable measuring insert.
- Adjustable tolerance limits.
- Power supply: 1 battery type V357.



Item No.	Measuring range/mm	Resolution mm	Insert length/mm	Price EUR
907.574	0.5	0.001	17	166.00
Options:				
836.535	Spare battery			0.70
907.769	Spare stylus tip			12.50

Lever-type test indicators

- Measuring range: up to 0.8 mm.
- Graduation: 0.01 or 0.002 mm.
- With dovetail joint and clamping stems ø6 and ø8 mm.
- Dial diameter: 40 mm.

- Rotatable dial.
- Stylus tip: ø2 mm.
- Delivery with an inspection report.

Item No.	Measuring range/mm	Graduation mm	Scale numbering	Insert length/mm	Price EUR
907.941	0.8	0.01	0-40-0	19	31.70
907.942	0.2	0.002	0-100-0	13	57.00
Options:					
909.114	Spare stylus tip for 907.941				7.60
909.115	Spare stylus tip for 907.942				7.60



302.EN.20180925