



Product: [1305A](#)

CatSnake® Category 5E Tactical Upjacketed Cable, 4 Bonded-Pairs, U/UTP

Product Description

CatSnake® Category 5E Upjacketed Tactical Cable, 4 Bonded-Pairs, 24 AWG Stranded Bare Copper Conductors, U/UTP, Inner PVC jacket, Outer PVC Jacket

Technical Specifications

Product Overview

| | |
|------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Suitable Applications: | Category 5e Patch, CobraNet, eSnake, Ethersound, Digital Audio Over Ethernet, PoE, PoE+ |
| Patent: | This product has one or more applicable patents. More information on patents can be found at https://www.belden.com/patents . |

Construction Details

Conductor

| Size | Stranding | Material | No. of Pairs |
|--------|-----------|------------------|--------------|
| 24 AWG | 7x32 | BC - Bare Copper | 4 |

Insulation

| Material | Color Code |
|-----------------|----------------------------------------------------------------------------------------------------------------|
| PO - Polyolefin | White/Blue Stripe & Blue, White/Orange Stripe & Orange, White/Green Stripe & Green, White/Brown Stripe & Brown |

| | |
|--------------|-----|
| Bonded-Pair: | Yes |
|--------------|-----|

Inner Jacket

| Material | Nom. Diameter | Ripcord |
|--------------------------|--------------------|---------|
| PVC - Polyvinyl Chloride | 0.236 in (5.99 mm) | No |

Outer Jacket

| Separator | Material | Nom. Diameter | Ripcord |
|----------------|--------------------------|--------------------|---------|
| Central Filler | PVC - Polyvinyl Chloride | 0.298 in (7.57 mm) | No |

| | |
|-----------------------------------|--------------------|
| Overall Cable Diameter (Nominal): | 0.298 in (7.57 mm) |
|-----------------------------------|--------------------|

Electrical Characteristics

Electricals

| Max. Conductor DCR | Max. Capacitance Unbalance |
|-------------------------------|----------------------------|
| 93.8 Ohm/km (28.6 Ohm/1000ft) | 90 pF/100m |

Delay

| Frequency | Max. Delay | Max. Delay Skew | Nom. Velocity of Prop. |
|-----------|---------------|-----------------|------------------------|
| 100 MHz | 537.6 ns/100m | 45 ns/100m | 70% |

High Frequency

| Frequency [MHz] | Max. Insertion Loss (Attenuation) | Min. NEXT [dB] | Min. PSNEXT [dB] | Min. ACR [dB] | Min. PSACR [dB] | Min. ACRF (ELFEXT) [dB] | Min. PSACRF (PSELFEXT) [dB] | Min. RL (Return Loss) [dB] | Max./Min. Input Impedance (unFitted) [Ohm] | Max./Min. Fitted Impedance [Ohm] |
|-----------------|-----------------------------------|----------------|------------------|---------------|-----------------|-------------------------|-----------------------------|----------------------------|--------------------------------------------|----------------------------------|
| 1 | 2.4 dB/100m | 65.3 | 62.3 | 63.3 | 60.3 | 63.8 | 60.8 | 20.0 | 100 +/- 15 | 105 +/- 10 |
| 4 | 4.9 dB/100m | 56.3 | 53.3 | 52.2 | 49.2 | 51.8 | 48.8 | 23.0 | 100 +/- 15 | 100 +/- 10 |
| 8 | 6.9 dB/100m | 51.8 | 48.8 | 46.0 | 43.0 | 45.7 | 42.7 | 24.5 | 100 +/- 15 | 100 +/- 10 |
| 10 | 7.8 dB/100m | 50.3 | 47.3 | 43.8 | 40.8 | 43.8 | 40.8 | 25.0 | 100 +/- 15 | 100 +/- 10 |

| | | | | | | | | | | |
|-------|--------------|------|------|------|------|------|------|------|------------|------------|
| 16 | 9.9 dB/100m | 47.2 | 44.2 | 39.0 | 36.0 | 39.7 | 36.7 | 25.0 | 100 +/- 15 | 100 +/- 10 |
| 20 | 11.1 dB/100m | 45.8 | 42.8 | 36.5 | 33.5 | 37.8 | 34.8 | 25.0 | 100 +/- 15 | 100 +/- 10 |
| 25 | 12.5 dB/100m | 44.3 | 41.3 | 33.9 | 30.9 | 35.8 | 32.8 | 24.3 | 100 +/- 15 | 100 +/- 10 |
| 31.25 | 14.1 dB/100m | 42.9 | 39.9 | 31.2 | 28.2 | 33.9 | 30.9 | 23.6 | 100 +/- 15 | 100 +/- 10 |
| 62.5 | 20.4 dB/100m | 38.4 | 35.4 | 21.4 | 18.4 | 27.9 | 24.9 | 21.5 | 100 +/- 15 | 100 +/- 10 |
| 100 | 26.4 dB/100m | 35.3 | 32.3 | 13.3 | 10.3 | 23.8 | 20.8 | 20.1 | 100 +/- 15 | 100 +/- 10 |
| 155 | 33.7 dB/100m | 32.4 | 29.4 | 4.4 | 1.4 | 20.0 | 17.0 | 18.8 | 100 +/- 18 | 100 +/- 10 |
| 200 | 38.9 dB/100m | 30.8 | 27.8 | | 9.2 | 17.8 | 14.8 | 18.0 | 100 +/- 20 | 100 +/- 10 |
| 250 | 44.2 dB/100m | 29.3 | 26.3 | | 0 | 15.8 | 12.8 | 17.3 | 100 +/- 20 | 100 +/- 10 |
| 300 | 49.2 dB/100m | 28.1 | 25.1 | | | 14.3 | 11.3 | 16.8 | 100 +/- 20 | 100 +/- 10 |
| 310 | 50.1 dB/100m | 27.9 | 24.9 | | | 14.0 | 11.0 | 16.7 | 100 +/- 20 | 100 +/- 10 |
| 350 | 53.8 dB/100m | 27.1 | 24.1 | | | 12.9 | 9.9 | 16.3 | 100 +/- 22 | 100 ± 10 |
| 310 | 49.5 dB/100m | 27.9 | 27.9 | | | | | 18 | | |
| 350 | 53.2 dB/100m | 27.2 | 27.2 | | | | | 17 | | |

Voltage

| Voltage Rating |
|----------------|
| 300 V |

Mechanical Characteristics

Temperature

| Operating | Installation | Storage |
|----------------|--------------|----------------|
| -20°C To +75°C | 0°C To +50°C | -20°C To +75°C |

Bend Radius

| Stationary Min. | Installation Min. |
|-------------------|-------------------|
| 1.25 in (31.8 mm) | 3.0 in (76 mm) |

| | |
|--------------------|----------------|
| Max. Pull Tension: | 40 lbs (18 kg) |
| Bulk Cable Weight: | 38 lbs/1000ft |

Standards and Compliance

| | |
|--------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| Environmental Suitability: | Indoor/Outdoor, Indoor, Outdoor, Sunlight Resistance |
| ICEA Compliance: | S-90-661 |
| NEMA Compliance: | NEMA WC-63.1 |
| Data Category: | Category 5e |
| TIA/EIA Compliance: | ANSI/TIA-568.2-D Category 5e |
| ISO/IEC Compliance: | ISO/IEC 11801-1, IEC 61156-6 |
| European Directive Compliance: | EU Directive 2015/863/EU (RoHS 2 amendment), REACH, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE), REACH: 2020-01-16 |
| APAC Compliance: | China RoHS II (GB/T 26572-2011) |

Product Notes

| | |
|--------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Notes: | Electrical values are expected performance based on cable testing and representative performance within a typical Belden system. Operating Temperatures Are Subject to Length De-rating. |
|--------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

History

| | |
|----------------------|--------------------------------------------------|
| Update and Revision: | Revision Number: 0.562 Revision Date: 12-12-2023 |
|----------------------|--------------------------------------------------|

Part Numbers

Variants

| Item # | Color | Putup Type | Length | UPC |
|---------------|--------------|------------|----------|--------------|
| 1305A B59500 | Black, Matte | Reel | 500 ft | 612825111184 |
| 1305A B591000 | Black, Matte | Reel | 1,000 ft | 612825111177 |

© 2024 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product

Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.