

Technical Datasheet

POLYESTER FLEECE PSF 30

Polyester fabric for reinforcing waterproofing membranes

Description - Fields of application

Thin polyester fabric of 30 g/m². It is used in order to locally or totally reinforce waterproofing coatings (e.g. for ISOFLEX or AQUAMAT-ELASTIC membranes, etc.), in case the surface shows local or total cracks, as well as at wall-to-floor junctions, corners etc.

Packaging

1 m x 200 m rolls (200 m²), 1 m x 100 m rolls (100 m²), 10 cm x 50 m rolls.

Storage

Stored in its original, unopened packaging, protected from humidity and UV radiation.

Technical data

Weight:	30 g/m ²
Material thickness:	0.23 mm
Tensile strength:	
- Long.:	55 N/5cm
- Trans.:	50 N/5cm
Elongation at break:	
- Long.:	20%
- Trans.:	20%
Shrinkage:	
- Long.:	2.0%
- Trans.:	0.8%

ISOMAT S.A.
BUILDING CHEMICALS, MORTARS & PAINTS
HEADQUARTERS – THESSALONIKI, GREECE
17th km Thessaloniki – Ag. Athanasios Road
P.O. BOX 1043, 570 03 Ag. Athanasios, Greece
T +30 2310 576000
www.isomat.eu e-mail: support@isomat.eu