

All in one solar charge inverter

HF4850S80-145 HF2430S60-100 HF4830S60-145











Efficiency

Advanced MPPT with up to 99.9% efficiency

SRNE

Multiple charge and discharge modes are available

Safety

- 360 degrees of security from hardware to software
- With IEC, SAA, cETL, FCC certification

all in one

- Support for many types of batteries
- Supports Li-ion battery BMS communication

Reliable

- Outputs high-quality pure sine wave AC powe
- Reliable output for long periods at rated power

User-Friendly

- Industrial design with a modern aesthetic look
- Easy to install and simple to use

Intelligent

- Exclusive Li-ion battery BMS dual activation
- Support for remote monitoring of operating parameters



MODEL	HF4850S80-145	HF4830S60-145	HF2430S60-100	CAN B SET
INVERTER OUTPUT	1			
Rated Output Power	5,000W	3,000W	3,000W	
Max.Peak Power	10,000VA	6,000VA	6,000VA	
Rated Output Voltage	230Vac (L/N/PE single phase)		√	
Load Capacity of Motors	4HP	2HP	2HP	
Rated AC Frequency	50Hz/60Hz			
Waveform	Pure Sine Wave			
Switch Time	10ms (typical)			
BATTERY				
Battery Type	Li–io	n/Lead-Acid/User De	efined	1
Rated Battery Voltage	48Vdc 24Vdc		24Vdc	
Voltage Range	40~60Vdc		20~33Vdc	√
Max.MPPT Charging Current	80A 60		0A	√
Max.Mains/Generator Charging Current	60A		80A	√
Max.Hybrid Charging Current	140A	120A	140A	V
PV INPUT				
Num. of MPPT Trackers		1		
Max.PV Array Power	4,400W	3,400W	1,600W	
Max.Input Current	50A 40A			
Max.Voltage of Open Circuit	145	Vdc	100Vdc	
MPPT Voltage Range	60~115Vdc 30~85Vdc			
MAINS/GENERATOR INPUT				
Input Voltage Range	UPS: 170~280Vac APL: 90~280Vac		V	
Frequency Range	50Hz/60Hz		V	
Bypass Overload Current	40A	3	0A	
EFFICIENCY				
MPPT Tracking Efficiency	99.9%			
Max. Battery Inverter Efficiency	92%			
GENERAL				
Dimensions	426*322*124mm	378*280*103mm		
Weight	10.8kg	6.1	2kg	
Protection Degree	IP20, Indor Only			
Operating Temperature Range	–15°C~55°C			
Noise	<60dB			
Cooling Method	Internal Fan			
Warranty	2 years			
COMMUNICATION				
Embedded Interfaces	RS4	85/CAN/USB/Dry coi	ntact	
External Modules (Optional)	Wi-Fi/GPRS			

www.srnesolar.com