Universal Adjustable Wheel Bearing Lock Nut Wrench

9HBN01

3/4"

- For disassemble and assemble vario nut and cap
- Extra slim design suitable to reach narrow space for special nut
- Use with 3/4" DR. tools and suggest to lock by torque wrench
- · Application for 6PT, 8PT and round nut
- · Adjustable open jaw 50~150mm
- · Contents:
- 3 pairs round adapter for round nut : 6mm, 8mm, 10mm
- 3 pairs square adapter for round nut : 1/4", 5/16", 3/8"









Drop Forged Coil Spring Compressor Set

9BF11

9BF21

- Drop forged SCM435 jaws & leaded screws
- Both 21mm 6-point sockets and 1/2" wrench are available
- · Suitable for limited space under wheel arch











KT NO.	L mm	0	mm	K al	8/8
9BF11	85 / 370	1/2"	21	2.40	1/6
9BF21	85 / 270	1/2"	21	3.36	1/6

Coil Spring Compressor Set

9BF31

- Developed for "Macpherson" suspensions, using a range of 3 sets interchangeable monobloc forks
- · Spring specification / use :

A: Ø80~115mm

B: Ø110~150mm

C: Ø140~195mm


 Suitable for BMW, Ford, VW, Audi, Porsche, Saab, Opel, Volvo, Nissan, Honda, Mitsubishi, Subaru, Toyota

> 8 PC.









KT NO.	L mm	Capacity mm	₩ a	@/ @
9BF31	460	40~300	15.00	1 / 1

Steering Wheel Puller Set

9BG11

- Easy to remove and install steering wheel for cars and trucks
- 2 sets 17mm hex head puller with pointed and flat cups
- 4 sets side bolts
- Small plate Dia. : 1"~3-11/16" 25~95mm
- Large plate Dia. : 1-1/8"~5" 28~125mm
- · Side bolts size :
 - 3 PC. 5/16" UNC x 3-1/2" lon g puller bolts
 - 3 PC. 5/16" UNF x 3" long puller bolts
- 3 PC. 3/8" UNC x 3" long puller bolts
- 3 PC. 3/8" UNF x 3" long puller bolts

4.10 🕏 / 🕮 1/6





