



COMPACT FILTER SYSTEM



Designed for eat set-up domestic pool, compact Series filtration combo offers the right solution for home user who is looking for user-friendly and excellent filtration performance. Compact Series Filtration Combo includes top mount plastic filter tank, 4 way multiport valve and swimming pool pumps attached with base.



FSP390-4W



FSP300-4W



Remarks: Flow curve information based on 220V/50Hz motor.

Technical Information

Code	Model No	Filter	Pump	Max Flow Rate	Sand(kg)
88030230	FSP300-4W	P300	ST013	501pm 3.00m³/h	19
88030201	FSP300-4W	P300	ST020	581pm 3.50m³/h	19
88030202	FSP300-4W	P300	ST033	671pm 4.02m³/h	19
88033718	FSP390-4W	P390	SD075	1331pm 8.00m³/h	35




Product Dimension

Model No	A mm	B mm	C mm	D mm	Filter & Pump In/Out Connections	Adaptor
FSP300-4W	145	540	485	330	1.5inch 50mm	1inch 32&38mm
FSP300-4W	145	540	485	330	1.5inch 50mm	1inch 32&38mm
FSP300-4W	145	540	485	330	1.5inch 50mm	1inch 32&38mm
FSP390-4W	235	724	760	527	1.5inch 50mm	1inch 32&38mm



Highlight Features:

- Suggested Installation: Domestic swimming pool
- Easy installation with pre-installed plumbing system and base
- Simple operation with 4-way multiport valve
- Filter structure with UV resistance material
- Max operating pressure 28psi / 2.0 bar
- Max temperature of 40°C (104 °F)
- Suggested size of media : 0.5-0.8mm



FSP390-4W

FSP300-4W