LOADER PRO HD

Telehandler Tires in USA

Construction & Industrial Telehandler Bias

1 **(FEATURE)**
Skid steer for industrial and construction applications , Strong nylon casing , Step down lugs , Rim guard , Abrasion resistant compounds , Deeper tread depth , Solid center lug with deep shoulder

2 **(BENEFIT)** Heavy duty service , Excellent durability , Self - cleaning , Cut and chip resistant , Reduces damage in side wall and rim flange area , Excellent traction and puncture resistant

Sizes

Sizes	RIM
14-17.5	10.5 X 17.5
15-19.5	11.75 X 19.5

Table of Specifications

Sizes	RIM	Infl tire dimension		SLR	RC	SRI	PR	LI/SS	Infl. press.	Recommend load, kg (lbs)
										Speed, km/h (mph)
		SW	OD							Max Load
		mm	mm	mm	mm				bar	40
		in	in	in	in				psi	25
14-17.5	10.5 X 17.5	350 13.8	930 36.6	433 17.0	2743 108.0	-	14	140 A8	5.5	2500
									80	5510

Sizes	RIM	Infl tire dimension		SLR	RC	SRI	PR	LI/SS	Infl. press.	Recommend load, kg (lbs)
										Speed, km/h (mph)
		SW	OD							Max Load
		mm	mm	mm	mm				bar	15
		in	in	in	in				psi	10
15-19.5	11.75 X 19.5	395 13.8	1030 36.6	465 18.3	3045 120.0	-	14	-	4.8	3605
									70	7945