

LOADPRO RADIAL

Telehandler & Compact Wheeled Loader Tires in USA

 Construction & Industrial
  Telehandler
  Compact Wheeled Loader
  Radial



- 1 **(EXTRA REINFORCED SIDEWALLS)** Additional lateral stability
- 2 **(GREATER LUG OVERLAP AND MORE LUGS IN FOOTPRINT)** Uniform load distribution
- 3 **(STRONG BEAD)** Better carcass strength and load carrying capacity
- 4 **(STEEL BELTED RADIAL CONSTRUCTION)** Protection from Punctures

Sizes

Sizes	RIM
460/70R24	W15L, W16L

Table of Specifications

Sizes	RIM	Infl tire dimension		SLR	RC	SRI	LI/SS	Infl. press.	Recommend load, kg (lbs)								
		SW	OD						Speed, km/h (mph)						Cyclic operation		
				Constant load					Cyclic operation								
				bar	10				20	30	40	50	bar	10	15		
mm	mm	mm	mm	mm	mm	psi	6	12	19	25	31	psi	6	9			
in	in	in	in	in	in												
460/70R24	W15L, W16L	455 17.9	1254 49.4	566 22.3	3713 146	575	159A8/B	1.6	2630	2290	2180	2100	2100	1.6	3150	2810	
								2.3	5790	5040	4800	4630	4630	2.3	6940	6190	
								2.4	3630	3160	3020	2900	2900	2.4	4350	3890	
								3.5	8000	6960	6650	6390	6390	3.5	9580	8570	
								3.0	4340	3780	3610	3470	3470	3.0	5210	4650	
								4.4	9560	8330	7950	7640	7640	4.4	11480	10240	
								3.6	5030	4380	4180	4020	4020	3.6	6030	5390	
								5.2	11080	9650	9210	8850	8850	5.2	13280	11870	
								4	5470	4770	4550	4375	4375	4	6560	5860	
5.8	12050	10510	10020	9640	9640	5.8	14450	12910									