CEAT SPECIALTY
AGRICULTURE & OTR TIRES

LOADPRO RADIAL

Telehandler & Compact Wheeled Loader Tires in USA

Construction & Industrial | Telehandler | Compact Wheeled Loader | Radial

1. **(EXTRA REINFORCED SIDEWALLS)** Additional lateral stability
2. **(GREATER LUG OVERLAP AND MORE LUGS IN FOOTPRINT)** Uniform load distribution
3. **(STRONG BEAD)** Better carcass strength and load carrying capaciy
4. **(STEEL BELTED RADIAL CONSTRUCTION)** Protection from Punctures

Sizes

Sizes	RIM
440/80R28	W14L,W15L,W16L

Table of Specifications

Sizes	RIM	Infl tire dimension		SLR	RC	SRI	LI/SS	Infl. press.	Recommend load, kg (lbs)							
									Speed, km/h (mph)							
									Constant load					Cyclic operation		
		SW	OD													
		mm	mm	mm	mm			bar	10	20	30	40	50	bar	10	15
		in	in	in	in			psi	6	12	19	25	31	psi	6	9
440/80R28	W14L,W15L,W16L	441 17.4	1415 55.7	637 25.1	4223 166	-	156A8/B	1.6	2860	2500	2380	2290	2290	1.6	3440	3070
								23	6300	5510	5240	5040	5040	23	7580	6760
								2.2	3700	3230	3080	2960	2960	2.2	4440	3970
								32	8150	7110	6780	6520	6520	32	9780	8740
								2.8	4490	3910	3730	3590	3590	2.8	5390	4810
								41	9890	8610	8220	7910	7910	41	11870	10590
								3.2	5000	4360	4160	4000	4000	3.2	6000	5360
								46	11010	9600	9160	8810	8810	46	13220	11810