

TYROCK SUPER

Telehandler Tires in USA

Construction & Industrial Telehandler Bias



- 1 **(EXTRA WIDE LUGS)** Excellent resistance to tearing and cracking
- 2 **(OPEN SHOULDERS)** Improved Self cleaning
- 3 **(SPECIALLY DESIGNED TREAD WITH HEAVY CENTER MASS)** Heavy duty service
- 4 **(LARGE WIDE CENTRE LUGS)** Excellent Ground Contact for maximum Stability
- 5 **(HEAT & CUT RESISTANT COMPOUND)** Improved Product life

Sizes

| Sizes | RIM |
|---------|------|
| 16.9-30 | W15L |

Table of Specifications

| Sizes | RIM | Infl tire dimension | | SLR | RC | SRI | PR | LI/SS | Infl. press. | Recommend load, kg (lbs) | |
|---------|------|---------------------|------|------|-------|-----|----|--------|--------------|--------------------------|----|
| | | SW | OD | | | | | | | Speed, km/h (mph) | |
| | | mm | mm | | | | | | | Load capacity | |
| | | in | in | | | | | | | mm | mm |
| 16.9-30 | W15L | 442 | 1490 | 673 | 4395 | - | 14 | 156 A8 | 3.1 | 4000 | |
| | | 17.4 | 58.7 | 26.5 | 173.0 | | | | 45 | 8818 | |