

# FARM IMPLEMENT 800R

## Fronts & Implements Tires in USA

 Agriculture  Fronts & Implements  Radial



- 1 **(RIB PATTERN)** Wider footprint & lower ground pressure
- 2 **(SPECIAL SHOULDER DESIGN)** Strong grip
- 3 **(LUGS WITH ROUNDED SHOULDERS)** Excellent self-cleaning capabilities
- 4 **(STEEL BELTED CONSTRUCTION)** Protection from punctures

### Sizes

Sizes	RIM
380/55R16.5	AG12.00

### Table of Specifications

Sizes	RIM	Infl tire dimension		SLR	RC	SRI	LI/SS	Infl. press.	Recommend load, kg (lbs)							
		SW	OD						Speed, km/h (mph)							
									Drive wheel				Free rolling			
									10	40	50	bar	10	40	50	
mm	mm	mm	mm	psi	10	40	50	psi	10	40	50					
in	in	in	in	in	in											
380/55R16.5	AG12.00	380 15.0	840 33.1	378 14.9	2454 96.6	-	150A8 138A8	0.8	2120	1660	1390	0.8	1250	1110	920	
								12	4670	3660	3060	12	2750	2440	2030	
								1.6	3170	2480	2080	1.6	1880	1670	1380	
								23	6980	5460	4580	23	4140	3680	3040	
								2.4	4030	3150	2640	2.4	2380	2120	1750	
								35	8880	6940	5810	35	5240	4670	3850	
								3.2	4760	3730	3130	3.2	2820	2500	2070	
								46	10480	8220	6890	46	6210	5510	4560	
								3.6	5110	4000	3350	3.6	3020	2690	2220	
								52	11260	8810	7380	52	6650	5930	4890	
								4	3070	2360	3560	4	3210	2860	-	
								58	6760	5200	7840	58	7070	6300	5200	