

FLOATMAX FT

Trailer Tires in USA

 Agriculture  Trailer  Radial



- 1 **(DIRECTIONAL LUG & ROBUST LUG)** Better traction , Self cleaning , Better grip
- 2 **(HIGHER V/R RATIO)** Longer life
- 3 **(ROUNDED SHOULDER)** Reduced soil disturbance
- 4 **(ROBUST CENTRE BLOCKS & FLAT TREAD PROFILE)** Low vibration and smoother ride hard surfaces , Larger footprint increases flotation

Sizes

Sizes	RIM
710/45R22.5 FT	AG24.00

Table of Specifications

Sizes	RIM	Infl tire dimension		SLR	RC	SRI	LI/SS	Infl. press.	Recommend load, kg (lbs)				
		SW	OD						Speed, km/h (mph)				
		mm	mm	Recommended Load									
		in	in	10	30				40	50	65		
				mm	mm			bar	6	19	25	31	40
				in	in			psi	6	19	25	31	40
710/45R22.5 FT	AG24.00	745	1209	541	3661	575	165D	0.8	3620	3040	2730	2430	2010
								12	7970	6700	6010	5350	4430
								1.8	5810	4880	4390	3910	3230
								26	12800	10750	9670	8610	7110
								2.6	7200	6040	5440	4840	4000
								38	15860	13300	11980	10660	8810
								3.4	8420	7070	6360	5660	4680
								49	18550	15570	14010	12470	10310
								4	9270	7780	7000	6230	5150
58	20420	17140	15420	13720	11340								