

FLOTATION T422

Trailer Tires in USA

 Agriculture  Trailer  Bias



- 1 (LARGER VOLUME AND FOOTPRINT) Reduced compaction
- 2 (ROUNDED SHOULDER) Reduced soil disturbance
- 3 (HIGH LOAD CARRYING) Tough nylon casing , Strong bead bundle
- 4 (LARGER VOLUME AND FOOTPRINT) Reduced compaction

Sizes

| Sizes | RIM |
|-------------|----------|
| 700/50-26.5 | 24.00 DC |

Table of Specifications

| Sizes | RIM | Inft tire dimension | | SLR | RC | SRI | PR | L/SS | Infl. press. | Recommend load, kg (lbs) | | | |
|-------------|----------|---------------------|--------------|-----|---------------|-----|--------|---|--------------|--------------------------|-----|-------------|----|
| | | SW | OD | | | | | | | Speed, km/h (mph) | | | |
| | | | | | | | | | | Free Rolling | | Drive wheel | |
| | | | | | | | | | | bar | 40 | bar | 40 |
| mm | mm | mm | mm | psi | 25 | psi | 25 | | | | | | |
| in | in | in | in | | | | | | | | | | |
| 700/50-26.5 | 24.00 DC | 700 27.6 | 1333 52.5 | - | 3986 156.9 | - | 12, 16 | 169 / 165,157 / 154 , 174 / 170,162 / 158, A8 / B | 1.8 | 5800 | 1.8 | 4125 | |
| | | | | | | | | | 26 | 12787 | 26 | 9094 | |
| | | | | | | | | | 2.4 | 6700 | 2.4 | 4750 | |
| | | | | | | | | | 35 | 14771 | 35 | 10472 | |