

# FLOATMAX FT

## Trailer Tires in USA

 Agriculture  Trailer  Radial



- 1 **(DIRECTIONAL LUG & ROBUST LUG)** Better traction , Self cleaning , Better grip
- 2 **(HIGHER V/R RATIO)** Longer life
- 3 **(ROUNDED SHOULDER)** Reduced soil disturbance
- 4 **(ROBUST CENTRE BLOCKS & FLAT TREAD PROFILE)** Low vibration and smoother ride hard surfaces , Larger footprint increases flotation

### Sizes

Sizes	RIM
750/60R30.5 FT	AG24.00

### Table of Specifications

Sizes	RIM	Infl tire dimension		SLR	RC	SRI	LI/SS	Infl. press.	Recommend load, kg (lbs)				
		SW	OD						Speed, km/h (mph)				
		mm	mm	Recommended Load									
		in	in	10	25				40	50	65		
				mm	mm								
				in	in								
				in	in								
				in	in								
750/60R30.5 FT	AG24.00	754	1680	759	4961	800	181D	0.8	4810	4220	3630	3230	2670
								12	10590	9300	8000	7110	5880
								1.6	7540	6620	5700	5070	4190
								23	16610	14580	12560	11170	9230
								2.4	9970	8750	7530	6700	5540
								35	21960	19270	16590	14760	12200
								3	11750	10320	8880	7900	6530
								44	25880	22730	19560	17400	14380
								3.6	13630	11960	10300	9160	7570
								52	30020	26340	22690	20180	16670
								4.0	14850	13040	11220	9980	8250
								58	32710	28720	24710	21980	18170