

FARMAX R85

Tractor Tires in USA

 Agriculture  Tractor  Radial



- 1 **(HIGHER ANGLE AND LUG OVERLAP AT CENTER)** Better roadability
- 2 **(ROUNDED SHOULDER)** Reduced damage to soil and crop
- 3 **(RI-W TREAD DEPTH)** Longer tire life
- 4 **(LOWER ANGLE AT SHOULDER)** Superior traction
- 5 **(REDUCED SOIL COMPACTION)** Wider tread , Larger inner volume

Sizes

Sizes	RIM
460/85R38	W16L, W15L, W14L

Table of Specifications

Sizes	RIM	Infl tire dimension		SLR	RC	SRI	LI/SS	Infl. press.	Recommend load, kg (lbs)					
		SW	OD						Speed, km/h (mph)					
		mm	mm						Recommended Load					
		in	in						10	20	30	40	50	65
460/85R38	W16L, W15L, W14L	480 18.9	1747 68.8	796 31.3	5214 205.3	-	153D/156A8	bar	10	20	30	40	50	65
								psi	6	12	19	25	31	40
								0.8	3260	2670	2500	2380	2280	2170
								12	7180	5880	5510	5240	5020	4780
								1.2	4130	3380	3160	3010	2890	2750
								17	9100	7440	6960	6630	6370	6060
								1.6	4880	4000	3740	3560	3410	3250
								23	10750	8810	8240	7840	7510	7160
								2.4	5480	4490	4200	4000	3830	3650
								35	12070	9890	9250	8810	8440	8040