

# FARMAX R65

## Tractor Tires in USA

 Agriculture  Tractor  Radial



- 1 **(RI W TREAD DEPTH)** Longer tire life
- 2 **(TILTED LUG TIP)** Lesser vibration and noise
- 3 **(LOWER ANGLE AT SHOULDER)** Superior traction
- 4 **(MUD BREAKER)** Better self cleaning
- 5 **(ROUNDED SHOULDER)** Reduced damage to soil and crop
- 6 **(HIGHER ANGLE AND LUG OVERLAP AT CENTER)** Better roadability
- 7 **(REDUCED SOIL COMPACTION)** Wider tread , Larger inner volume

### Sizes

Sizes	RIM
540/65R38	W16L, W18L

### Table of Specifications

Sizes	RIM	Infl tire dimension		SLR	RC	SRI	LI/SS	Infl. press.	Recommend load, kg (lbs)							
									Speed, km/h (mph)							
									Non cyclic operation				Cyclic operation			
		SW	OD								bar		10		15	
mm	mm	mm	mm	mm	mm	bar	10	15	bar	10	15					
in	in	in	in	in	in	psi	6	9	psi	6	9					
540/65R38	W16L, W18L	550 21.7	1667 65.6	767 30	4975 196	-	153D	0.8	2410	2220	2130	2030	1	3450	3150	
								12	5310	4890	4690	4470	15	7600	6940	
								1.4	3330	3080	2950	2810	1.8	4780	4360	
								20	7330	6780	6500	6190	25	10530	9600	
								2.0	4050	3740	3590	3420	2.5	5810	5300	
								29	8920	8240	7910	7530	36	12800	11670	
								2.4	4330	4000	3830	3650	3	6210	5660	
								35	9540	8810	8440	8040	44	13680	12470	