

FARMAX RC

Row Crop Tires in USA

 Agriculture  Row Crop  Radial



- 1 **(D-RATED (40 MPH) TIRES)** Improved transportation speed
- 2 **(HIGHER ANGLE AND LUG OVERLAP AT CENTER)** Better roadability and stability
- 3 **(ROUNDED SHOULDER)** Reduced crop damage
- 4 **(HIGHER NUMBER OF LUGS)** Superior traction
- 5 **(STRONG CARCASS AND BEAD)** Higher load carrying capacity

Sizes

Sizes	RIM
320/90 R42	W10, W9, W11

Table of Specifications

Sizes	RIM	Infl tire dimension		SLR	RC	SRI	LI/SS	Infl. press.	Recommend load, kg (lbs)					
		SW	OD						Speed, km/h (mph)					
		mm	mm						Recommended Load					
		in	in						10	25	40	50	65	70
320/90 R42	W10, W9, W11	319	1643	764	4950	-	136D/139A8	0.8	1760	1390	1280	1230	1170	1060
		12.6	64.7	30.1	194.9			12	3880	3060	2820	2710	2580	2330
								1.6	2640	2090	1930	1850	1760	1600
								23	5810	4600	4250	4070	3880	3520
								2	3020	2380	2200	2110	2010	1830
								29	6650	5240	4850	4650	4430	4030
								2.4	3360	2650	2450	2350	2240	2040
								35	7400	5840	5400	5180	4930	4490