

TORQUEMAX

Tractor Tires in USA

 Agriculture  Tractor  Radial



- 1 **(WIDER TREAD WIDTH)** Lower Compaction
- 2 **(STEPPED LUG DESIGN)** Better Grip
- 3 **(TILTED LUG GRIP)** Lower Vibration At High Speeds
- 4 **(LOWER LUG ANGLE AT THE SHOULDER)** Better Traction
- 5 **(STRONGER AND WIDER LUGS)** Longer Life
- 6 **(ROUNDED SHOULDER)** Less Soil/crop Damage

Sizes

Sizes	RIM
IF710/75R42 CFO	DW25B, DW23B, DW24B

Table of Specifications

Sizes	RIM	Infl tire dimension		SLR	RC	SRI	LI/SS	Infl. press.	Recommend load, kg (lbs)							
		SW	OD						Speed, km/h (mph)							
				Mixed Application					Cyclic							
				mm	mm				mm	mm	mm	bar	15	30		
in	in	in	in	in	psi	9	19									
IF710/75R42 CFO	DW25B, DW23B, DW24B	715	2133	944	6306	1000	176D	0.6	5730	4870	4690	4510	4100	0.6	6990.5	5863
		28.1	84.0	37.2	248.3			9	12620	10730	10330	9930	9030	9	15400	12910
		0.8	5730	4870	4690			4510	4100	0.8	6990.5	5863				
		12	12620	10730	10330			9930	9030	12	15400	12910				
		1.0	6540	5560	5360			5150	4690	1.0	7982.5	6695				
		15	14410	12250	11810			11340	10330	15	17580	14750				
		1.2	7370	6260	6030			5800	5280	1.2	8990	7540				
		17	16230	13790	13280			12780	11630	17	19800	16610				
		1.6	9020	7670	7380			7100	6460	1.6	11005	9230				
		23	19870	16890	16260			15640	14230	23	159573	20330				