

# FARMAX RC

## Row Crop Tires in USA

 Agriculture  Row Crop  Radial



- 1 **(D-RATED (40 MPH) TIRES)** Improved transportation speed
- 2 **(HIGHER ANGLE AND LUG OVERLAP AT CENTER)** Better roadability and stability
- 3 **(ROUNDED SHOULDER)** Reduced crop damage
- 4 **(HIGHER NUMBER OF LUGS)** Superior traction
- 5 **(STRONG CARCASS AND BEAD)** Higher load carrying capacity

### Sizes

Sizes	RIM
340/85R48	W12, W11

### Table of Specifications

Sizes	RIM	Infl tire dimension		SLR	RC	SRI	LI/SS	Infl. press.	Recommend load, kg (lbs)					
		SW	OD						Speed, km/h (mph)					
									Recommended Load					
									bar	10	25	40	50	65
mm	mm	mm	mm	psi	6	16	25	31	40	43				
in	in	in	in											
340/85R48	W12, W11	343.0 13.5	1797.0 70.7	841.2 33.1	5476.1 215.6	-	148D/151A8	0.8	1970	1550	1430	1380	1310	1190
								12	4340	3410	3150	3040	2890	2620
								1.6	2940	2320	2150	2060	1960	1780
								23	6480	5110	4740	4540	4320	3920
								2.4	3720	2940	2720	2600	2480	2260
								35	8190	6480	5990	5730	5460	4980
								3.2	4410	3480	3220	3090	2940	2680
								46	9710	7670	7090	6810	6480	5900
								3.6	4730	3730	3450	3310	3150	2870
								52	10420	8220	7600	7290	6940	6320